

This is to certify that I, D. L. Hibbard County Surveyor of Montgomery County, Kansas was ordered by R. M. Dobson to Survey and Subdivide Sections Six & Seven (67 & 7) Township (34) Range 15 East. On the 18th day of February the following named parties were notified that a Survey of the above named Sections would be made the Survey to begin on Feb 26, 1901

William I. Measum
A. M. Dobson
J. F. Downe
Van H. Jackson
E. A. Clarke
G. H. Rowley Estate
Bruce Barnett
J. S. Joburg
D. B. Snell
Marshall Leuzick
Grayson D. Orr
W. C. Sewell
Wesley Finney
A. D. Hornack
Ed Anderson
Lucy Neal
Mabel Smith
O. H. Finney
Etta Mason
L. G. Kinney

On Feb 26, 1901 the Survey was postponed until March 5, 1901 on acct of sickness. On March 5, 1901 I began the Survey, Elmer Farlow & Edward Austin were selected as chainmen. From the Government 1/4 post on the township line on the North line of Section 6 Township 34 R. 15 E. I ran N. 89° 45' W. at 326 ft East Bank of Union Creek at 2640 ft drove stake as temporary north East corner section 6. T. 34 R. 15 E. From this temporary North East corner of Section 6 I ran N. 89° 45' West at 2640 ft drove stake as temporary 1/4 post on North line of Sec 6. From this temporary 1/4 post I ran on same bearing at 2637 ft drove stake as temporary N.W. cor. Sec. 6 on Range line. From this temporary N.W. corner Sec 6 I ran South 0° 30' E. at 1320 ft drove stake at 2640 ft drove stake at 2640 ft drove stake at 5290 ft drove stake as temporary South West corner Sec 6. From this temporary South West cor. Sec 6 I ran S. 89° 45' E. at 2640 ft drove stake at 5250 ft. drove stake as temporary South East corner section 6, T. 34 R. 15 E. Quit for the Day. March 6, 1901 Survey continued. From the stake the N.E. cor. Sec. 6, T. 34, R. 15 E. I ran S. 0° 30' E. at 965 ft. Plum Creek at 1320 ft drove stake at 2695 ft drove stake for temporary 1/4 post on East line section 6. From this temporary 1/4 post on East line Section 6 I ran South 30° E. at 1320 ft drove stake as temporary S.E. cor. N.W. Sec 4 Sec 6. offset 20 ft West on acct of ridge ran south from this stake S. 0° 30' E. 1320 ft drove stake as temporary S.E. cor. Sec 6 T. 34 R. 15 E. From this last temporary corner I ran south on East line sec 7 T. 34 R. 15 E. at 450 bottom bluff at 1320 ft stake temporary S.E. corner N.W. Sec 4 Sec 7, at 2175 ft draw at 2640 ft. Drove stake as temporary 1/4 post on East line section 7. From this stake I ran south 2650' to Road drove stake as temporary South East corner of section 7 T. 34 R. 15 E. From this temporary South East cor. Sec 7 I ran N. 89° 45' W. at 2650' drove stake as temporary 1/4 post on South line Sec 7. Heavy hedges on east side of the Road indicate the place where the Government 1/4 post stood. From this temporary 1/4 post on South line Sec 7 I ran N. 89° 45' W. 2665' drove stake as temporary S.W. cor. Sec 7. From this stake I ran N. 0° 15' W. at 1320' drove stake as temporary S.W. cor. N.W. Sec 4 Sec 7 at 2640' drove stake as temporary 1/4 post on West line Sec 7. From this stake I ran N. 0° 15' W. at 1320' drove stake as temporary N.W. corner S.W. Sec 4 Sec 7. T. 34, R. 15 E. at 2653' stake as driven as temporary N.W. cor. Sec 7, corrected this stake 1 1/2 ft. South 1/4 det a land stone 32 x 12 x 7" marked 1111 as corner to sections 6, 7, 11 & 12

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. HALEY, Topeka, Kansas.)

Kansas, 189.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

on Range line. At a point 1321 1/4 ft south of corrected S.E. cor. sec. 6 I set a line stone March 7, 1901, at a point 2640' East on Section line from S.W. cor. sec 6, I set a line stone 34" x 12" x 3 1/2" marked 1/4 for 1/4 post on South line Section 6 T. 34 R. 15 E. At a point 2642 1/2 ft South of N.E. cor. Sec 7. Set a line stone 28 x 16 x 8 marked 1/4 for 1/4 post on East line Section 7 at the South East corner of section 7 at a line stone 30" x 15" x 7" marked 1111 for corner to sections 7, 8, 17 & 18. For 1/4 post on South line section 7 set a line stone 30" x 12" x 8" marked 1/4 this stone is 2646 ft west of South East corner of section 7. T. 34 R. 15 E. At the South West corner of section 7 I set a line stone 27" x 15" x 6" marked 1111. This stone is 2666 ft west of 1/4 post on South line section 7. At a point 1322 1/2 ft north of the South West corner section 7 set a line stone 24" x 18" x 3" marked X as N.W. corner S.E. South West 1/4 section 7 at a point 2645 1/2 ft North of S.W. cor. sec 7 set a line stone 24" x 12" x 6" marked 1/4 for 1/4 post on West line section 7. At a point 3968 1/4 ft North of South West corner section 7 set a line stone 24 x 18 x 4 marked X as N.W. corner S.W. Sec 4 Sec 7. At a point 5291 ft N.W. cor. sec 7. At a point 1322 1/2 ft north of S.W. cor. Sec 6 T. 34 R. 15 E. set a line stone 20" x 14" x 6" marked X as N.W. corner S.W. Sec 4 Sec 6. At a point 2645 ft North of S.W. cor. Sec 6 set a line stone 28 x 14 x 8" marked 1/4 for 1/4 post on West line section 6. Quit for the Day. March 8, 1901. At a point 1322 1/2 ft North of 1/4 post on West line section 6 set a line stone 26 x 16 x 4" marked X as the South West corner of the N.W. Sec 4 section 6. At the North West corner section 6 on Range line set a line stone 38 x 18 x 8" marked 1111. At a point 2638 ft East of N.W. cor. Section 6 set a line stone 24 x 16 x 5" marked 1/4 on North line Section 6 at the North East corner section 6 set a line stone 27 x 12 x 7" marked 1111. This stone is 2670 ft east of the 1/4 post on the North line of section 6. At a point 1375 ft South, of the N.E. cor. section 6, set a line stone 26 x 16 x 4" as the South East cor. to Fractional lot on north side sec 6. At a point 2695 ft. South of the North East Cor. sec 6, set a line stone. 24" x 15" x 5" marked 1/4 for 1/4 post on East line section 6 T. 34 R. 15 E. At the South East cor. section 6, set a line stone 24" x 15" x 5" marked 1111. Bearing of East line S.E. Sec 6 is N. 0° 30' E. At a point 1321 ft. N. of S.E. cor. sec 6. set a line stone 24 x 18 x 4" marked X as N.E. cor. S.E. Sec 4 Sec 6. At a point 1320 ft East of N.W. cor. S.W. Sec 4 Sec 6 I set a line stone 18 x 12 x 3" marked X as S.E. cor. N.W. Sec 4 Sec 6. T. 34 R. 15 E. This completed the survey on March 9, 1901

Dated at Independence Montgomery Co, Kansas, March 26, 1901

D. L. Hibbard Co, Surveyor.