

This is to certify that L. S. Hibbard County Surveyor of Montgomery County Kansas was ordered by S. F. Brant to Survey & Subdivide Section 17, Township 31 Range 17 East. This Survey was made in connection with Section 16 T31, R17E called for by Jacob Shoemaker the parties interested in the Survey of Section 17 were notified on March 14<sup>th</sup> 1901 that a Survey of Section 17, would be made on the 22 day of March 1901 the parties notified were

|                   |                   |                  |                   |
|-------------------|-------------------|------------------|-------------------|
| J. E. Hetzel      | Pleasant A. Batis | E. B. Arnold     | C. H. Lamb        |
| Catherine Boyle   | Jerry Patterson   | J. J. Snider     | Jacob Shoemaker   |
| Mahitable Bronson | W. H. Overfield   | L. F. Bauer      | J. B. Klinefelter |
| Mary E. Keeler    | L. J. Howard      | E. T. Meers Aft. | A. M. Bracken     |

On April 4<sup>th</sup> 1901 I began the Survey as on March 22<sup>nd</sup> was wet & stormy the parties were notified that the Survey was postponed until April 3<sup>rd</sup> 1901 on April 3<sup>rd</sup> 1901 I was working on Sec. 16 in connection with this Survey Joseph Liebert & Floyd Walker were selected as Chainmen Barker as Flagman. From temporary S.E. cor. of Sec 17 I ran S 89° W at 1320 ft drove stake at 2640 ft, drove stake at 4064 ft came out 8 feet south of the 29 mile stone on the Osage treaty line I examined this stone & compared it with the Government field notes & found it the Original Stone Marked XXIX. a small portion of the top had been broken off the portion broken off was near by, I drove an Iron Rod beside the Stone to witness the same. From this stone I ran S 89° W at 800 ft, came out 100 ft, North of a stone the South West corner of Sec 17, T31, R17E. Quit for the day, postponed until April 8<sup>th</sup> 1901. On April 8<sup>th</sup> 1901, I ran S 88° 30' W, From the N.E. cor. sec 17 T31, R17 at 1320 ft drove stake at 2640 ft, drove stake at temporary 1/4 post on North line sec 17 at 2950 ft, draw at 4522 ft, drove stake at temporary 28 mile post on treaty line in draw at 5300 ft drove stake in North & South Road 240 ft, North of the center of the cross Roads where N.W. corner of Section 17 is supposed to be I drove a stake as temporary North West corner of Section 17 T31, R17E, at or near center cross Roads. From this stake I ran South 1° East at 2640' drove stake as temporary 1/4 post on West line at 3520' draw at 3960' stake, at 4060' draw, At 5285 ft came out 13 ft west of S. West cor. of sec 17. From 28 mile post on the South line Section 17, T31, R17E I ran North 0° 30' West at 1320 ft, drove stake at 2640' drove stake 536 ft, stake North line Sec 17 We dug down here as there had been a fill in Road We found the 28 mile post a rock 3 feet under the ground bearing the Government Mark XXVIII Put a flag on this 28 mile post & one at the North East corner of Section 17 Ran straight line between, At a point 2640 ft S. 87° 50' W from the North East Corner of Sec 17 I set a line stone 22"x9"x6" Marked 4 for the 1/4 post on the North line of sec 17 T31, R17E & quit for the day - Adjourned until Apr. 18<sup>th</sup> 1901 on account of wet weather Thursday April 18<sup>th</sup> 1901 At a point 1320 ft S. 87° 50' W from the N.E. corner sec 17 I set a line stone 24"x10"x8" Marked X as the N.W. corner of the N.E. 1/4 N.E. 1/4 Sec 17. On top of the 28 mile Post on the Treaty Line I set a line stone 28"x10"x6" Marked XXVIII as witness to the four corner. The Bearing of the North line of Section 17 from the 28 mile Post to the N.W. corner of Sec 17 is South 75° W 815 feet here I set a line stone 22"x12"x7" marked 1111. This stone is in center of the cross roads & is the corner to sections 7, 8, 17 & 18. Bearing of West line sec 17 is N 0° 45' W At a point 2640 ft south on Sec line from the N.W. cor. sec 17 I set a line stone 18"x7"x6" Marked 4 found old stone put beside it for 1/4 post on West line sec 17. At a point 1320 ft South of this 1/4 post I set a line stone 22"x7"x6" marked X From South West corner sec 17 I ran to the 29 mile stone N. 81° 15' E 806 ft. At a point 2680 ft North on Treaty line from 29 mile post I established permanent 1/4 post. Set line stone 26"x9"x8" Marked O. D. R. 4. From this 1/4 post I ran N. 2° E on Random line 2032 stake temporary center to sec 17 at 3300 ft. Stake edge of Public Road at 4215 ft creek at 4450' creek in timber at 4730 ft came out

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.  
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

Kansas, 189.....

M.....  
You are hereby notified that, at ..... o'clock A. M., on the ..... day of ..... 189....., I will begin a survey on Section ..... Town ..... South, Range ..... in which you are interested, and shall continue the same from day to day until completed. Commencing at the ..... corner of said Section, I shall permanently establish

..... County Surveyor,  
..... County, State of Kansas.

36 ft north of the 1/4 post on the east line of sec 17. Bearing of the South line of sec 17 is S 89° 30' W. to the 29 mile post from S.E. cor. of sec 17. Friday April 19<sup>th</sup> 1901 At a point 1435 ft. West of S.E. corner of Sec 17 on Sec line I set a line stone 36"x15"x6" marked X as the South West corner of the S.E. 1/4 sec 17, T31, R17E. At a point 2876 feet west on sec line from the South East cor. of sec 17. I set a line stone 24"x15"x6" marked 4 for 1/4 post on the South line of sec 17. I ran straight line between the 1/4 posts at their intersection I set a line stone 35"x16"x5" marked X as the center of sec 17. This stone after corrections were made from temporary center corner, was 1922 ft N. 1° 40' E. From the 1/4 post on Treaty line. The distance from the center of Sec 17 to 1/4 post on East line by measurement is 2808 ft. At a point 1340 ft. North on treaty line from 29 mile post I set a line stone 25"x8"x3" marked X At a point 1340 ft. North of the 1/4 post on the Treaty line I set a line stone 19"x7"x5" marked X. This stone is 1340 ft South of the 28 mile stone Bearing of 1/4 line N. 2° E. Through Sec 17 is N. 2° E. At the South East corner of Lot 1 of Sec 17. I set a line stone on 1/4 line 24"x17"x6" Marked X 1350 1/2 ft. South of 1/4 post on North line of sec 17. At a point on 1/4 line 1404 ft. East of center sec 17 I set a line stone 24"x12"x4" marked X as S.W. corner, S.E. 1/4 N.E. 1/4 sec 17. This stone is in the bottom of a draw witnessed by a Black Jack 6 in diameter S. 62° W. 27 ft distant a Black Jack 8" diameter due East 33 ft. distant At the South West corner of the N.E. 1/4 of the N.E. 1/4 of Sec 17. I set a line stone 18"x16"x4" Marked X This finished the Survey of sec. 17 Township 31 R 17 E. on the 19 day of April 1901, East line of Sec 17 see survey of Sec 16 Var S. E.

Dated at Independence Montgomery County Kansas May 11<sup>th</sup> 1901

L. S. Hibbard Co. surveyor