

Survey No. , Section 24, Town 33, South, Range 15

This is to certify that I, L. D. Hibbard County Surveyor of Montgomery County Kansas was ordered by J. E. Kingard to survey & subdivide section 24 Township 33 Range 15 East - On the 18 day of April 1901 the following named parties were notified that a survey of the above named section would be made to begin on the 24 day of April 1901

J. E. Kingard Samuel Adams J. F. Adams J. L. Thompson B. F. Devore A. Conale
Mrs. Killcorn E. T. Means A. J. Henry Bradyhoft J. M. Thompson A. J. Collins Henry Noble
Tom Lye Oscar Bauer R. L. Erieham Ed Allen J. B. Compton

Notice as follows you are hereby notified that I will be at the N.E. corner of Section 24 Township 33 Range 15 E on the 24 day of April 1901 at 10 o'clock A. M. for the purpose of surveying the lands of J. E. Kingard & others lying in section 24 Township 33 Range 15 E. You will therefore be prepared to pay your proportionate part of the expense of said survey in accordance with sections 7 & 11 Chapter 89 of the Laws of 1891. Dated at Independence Kansas this 18 day of April 1901 L. D. Hibbard Surveyor of Montgomery County. On April 24 I began the survey & M. Thompson & W. E. Smith were selected as chainmen. From the North East corner the Government stone I ran S 89° 45' W from the N.E. corner of Sec. 24 T. 33 R. 15 E. at 50 ft break at 600 ft draw at 1320 ft draw stake at 2640 ft draw stake as temporary 1/4 post on the North line of Sec. 24. From this temporary 1/4 post I ran S 89° 45' W at 1320 ft stake at 2640 ft draw stake in center of Cross Roads as temporary N.W. corner of Section 24 - P.M. From this temporary N.W. corner of Sec. 24 T. 33 R. 15 E. I ran South 0° 30' E at 2640 ft draw stake as temporary 1/4 post on West line of Sec. 24. From this temporary 1/4 post on the West line of Sec. 24 I ran S 24° 15' E at 2632 ft draw stake as temporary S.W. corner of Sec. 24 in center of Cross Roads. From this temporary S.W. cor. of Sec. 24 I ran East at 1320 ft draw stake at 1600 ft West branch Coal Creek at 2100 ft East branch Coal Creek at 2635 ft came out 3 ft north of a stone supposed to be the 1/4 post but bearing no marked draw stake as temporary 1/4 post on the South line of Section 24. From this temporary 1/4 post on the South line of Sec. 24 T. 33 R. 15 E. I ran East at 1320 ft draw stake at 2634 ft draw stake as temporary South East corner of Section 24. On Range line N 0° 40' W at 900 ft draw at 1320 ft stake at 2638 1/2 ft post marked came out 6 ft east of the 1/4 post. From 1/4 post on East line Sec. 24 which was broken I ran N 0° 40' W. 450 ft House 10 ft West of line at 712 ft Coal Creek at 1375 ft Rock Bluff at 1600 ft House 25 ft West of line at 2600 ft break or draw at 2641 ft N.E. cor. of Sec. 24. Quit for the day. Thursday April 25, 1901 corrected temporary 1/4 post on North line of Section 24 T. 33 R. 15 E. at a point 2629 ft West of the N.E. corner Sec. 24 set a Lime stone 26" x 22" x 4" marked 1/4 for 1/4 post on North line Sec. 24. At a point 1314 1/2 ft West of the 1/4 post on the North line of Sec. 24 I set a Lime stone 21" x 14" x 3" marked X as the N.E. corner of the West 1/2 of the N.W. 1/4 of Sec. 24. At the N.W. corner of Sec. 24 I set a Lime stone 26" x 10" x 5" marked 1111 Glass & brockery put around the stone at bottom to mark the location. At a point 1314 1/2 ft West of the North East corner of Sec. 24 I set a Lime stone 30" x 10" x 5" marked X as the N.E. corner of the N.E. 1/4 of the N.E. 1/4 of Sec. 24. At a point 2640 ft South on Sec. line from the N.W. corner of Sec. 24 I set a Lime stone 30" x 8" x 4" marked 1/4 for the 1/4 post on the West line of Sec. 24. Also drove an Iron pin beside it 3 ft long. At a point 2640 ft South of the 1/4 post on the West line Sec. 24 I set a Lime stone 30" x 18" x 4" marked 1111 in center Cross Roads drove Iron pin 3 ft long. At a point 1315 ft East of the S.W. corner of Sec. 24 I set a Lime stone 24" x 12" x 3" marked X as the S.E. corner of the N.E. 1/4 of the N.W. 1/4 of Sec. 24. At a point 2636 ft East of S.W. cor. Sec. 24 I set a Lime Stone 24" x 14" x 3" marked 1/4 for the 1/4 post on South line of Sec. 24. At a point 1348 ft East of this last named set a Lime stone 25" x 11" x 5" marked X as the S.W. cor. of the E 1/2 of the S.E. 1/4 Sec. 24, with Glass & Iron around stone. At the South East corner of Sec. 24 on the Range line I set a Lime stone 30" x 18" x 4" marked 1111 for S.E. cor. of Sec. 24 with Glass & Iron about it. At a point 1320 ft North on the Range line of Sec. 24 from the S.E. corner I set a Rand stone 24" x 14" x 4" marked X as the N.E. corner S.E. 1/4, S.E. 1/4 Sec. 24. Quit for the day - Friday April 26, 1901 Survey of Sec. 24 T. 33 R. 15 E. continued as the 1/4 post on the East line of Sec. 24 was in two pieces of soft sand stone - I set in its place a Lime stone 36" x 16" x 4" marked 1/4 for the 1/4 post on the East line of Sec. 24 set old 1/4 post beside it with broken glass & slack coal as witness. I put flag on the 1/4 post & ran straight lines between at the intersection of the 1/4 lines I set a Lime stone 26" x 12" x 3 1/2" marked X as center of Section 24 with Glass & slack coal as witness. At a point on the 1/4 line 1320 ft South of the center of Sec. 24 I set a Lime stone 42" x 8" x 4" as the S.W. corner of the N.W. 1/4 of the S.E. 1/4 of Sec. 24 T. 33 R. 15 E. at a point on the 1/4 line where the 1/2 line intersected it running N & S on E 1/2 of Sec. 24 I set a Lime stone 32" x 10" x 6" marked X with broken glass brockery & Iron beside it as the S.E. cor. N.E. 1/4 Sec. 24, T. 33 R. 15 E. At the intersection of the 1/2 line running N & S on the West 1/2 of Sec. 24 with the 1/4 line running East & West I set a Lime stone 30" x 12" x 3" marked X as the S.E. corner of the N.E. 1/4 of the N.W. 1/4 of Sec. 24, T. 33 R. 15 E. which completed the survey of Section 24

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 1891.

M

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 1891, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

posts & ran straight lines between at the intersection of the 1/4 lines I set a Lime stone 26" x 12" x 3 1/2" marked X as center of Section 24 with Glass & slack coal as witness. At a point on the 1/4 line 1320 ft South of the center of Sec. 24 I set a Lime stone 42" x 8" x 4" as the S.W. corner of the N.W. 1/4 of the S.E. 1/4 of Sec. 24 T. 33 R. 15 E. at a point on the 1/4 line where the 1/2 line intersected it running N & S on E 1/2 of Sec. 24 I set a Lime stone 32" x 10" x 6" marked X with broken glass brockery & Iron beside it as the S.E. cor. N.E. 1/4 Sec. 24, T. 33 R. 15 E. At the intersection of the 1/2 line running N & S on the West 1/2 of Sec. 24 with the 1/4 line running East & West I set a Lime stone 30" x 12" x 3" marked X as the S.E. corner of the N.E. 1/4 of the N.W. 1/4 of Sec. 24, T. 33 R. 15 E. which completed the survey of Section 24

Var 8° E

Dated at Independence Montgomery County Kansas May 10, 1901

L. D. Hibbard Co. Surveyor