Survey No. ....., Section 8, Town 33 South, Range 16

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I S.L. Hibbard County Surveyor of Montgomery Co. Kansas was ordered by Frank De Geer to Survey & Subdivide Section Eight (8), Township (33), Range 16 East. On July 15th 1901. The following named parties were notified that a Survey of Sections 8 Township 33 Range 16 would be made beginning on July 23rd 1901

Mary Mc Laughlin C.C. Shank Frank D. Holland William Mc Dougal Mary Ann Simpkins
James Gillard John Barts Samuel Chamberlain Travellers Insurance Co. O.P. Gamble
Frank De Geer Levi Snyder Nellie C. Williams Mary Bourquin J. Olthoff

Samuel Bailey appeared on the survey. On July 23 1901 I began the survey J Olthoff & J Marks were selected as Chainmen & J.F. Loyd as Flagman. From the South West Corner of Sec 8 T33 R16 E, a stone I ran N 1°15' West, at 1320 ft drove stake as temporary N.W. corner of S.W.¼ S.W.¼ Sec 8 at 2640 ft drove stake as temporary ¼ post on West line of Sec 8. From this temporary ¼ post I ran N 3°45' W in center of public Road at 1320 ft drove stake as temporary N.W. corner S.W.¼, N.W.¼ Sec 8, at 2600 ft drove Stake on north side Public Road, running East & west Finding the section short I went north ¼ for the ¼ post on the west line of Sec 8. T. 33 R. 16 At a point 1307 feet S 1°15' E. from the ¼ post on West line sec 8 I set a lime stone 14"x4"x3" marked X as the N.W. Corner of the S.W. ¼ of the S.W.¼ of sec 8. From the ¼ post on the south line of Sec 8 I ran, random line N 2°25' W. at 1320 ft found stone west of where I drove stake as temporary Cor at 2640 ft drove stake as temporary center sec 8. Ran line on same bearing to north line of sec 8, I came out 20½ ft east of the ¼ post on North line of sec 8 Correction would be 10 ¼ feet west for center sec 8 Bearing of W. & South ¼ line is N 2°30' W July 25 1901 At a point 2698 ft South 40' E from North East Corner of Section 8 I set a sand stone marked ¼ for ¼ post on East line Sec 8, Size of Stone 24"x9"x7" - Measured from the stone West at 2565 ft center sec 8, Here we drilled a hole in the rock & drove in an Iron pin broke glass as witness to center Come, from this center of sec 8 Ran west at 2545 ft ¼ post on West line sec 8. At a point midway between center section 8 & the ¼ post on the west line sec 8 I set a sand stone 24"x8"x6" marked ¼ for the N.W. Corner N. E¼ S.W.¼ sec 8, Set a stone 80 rods N. 2° 30' W of the ¼ post on the South line Sec 8 or at a point on ¼ line midway between the ¼ post on the south line of section 8 and the center to the ⅛ stone 80 rods north from the South line of Section 8 T. 33 R. 16. From this Stone I measured north 80 rods to the ¼ post on west line of Sec 8 found this ¼ post but it was out of the ground, I established the N.W. Corner of Section 8 12 ft. South & 4 feet west of the stake driven as temporary N.W. Cor, sec 8. Making the west line of Sec 8 2578 ft in length. From this true point as North West Corner Sec 8, I ran North 89° E. between Sections 5 & 8 at 2600 ft. Temporary ¼ post on north line sec 8. From this temporary ¼ post I ran N 89° 15' E at 2647 ft a stone the North East Corner of Sec 8. From the North East corner sec 8. I ran S 0° 35' E at 2737 feet a stone bore no marks at 2640 ft I drove a stake as temporary ¼ post on East line Sec 8. From this Stone I ran S 0° 35' E at 1310 stone at 2621 Sec Cor S.E. Cor. sec 8, a stone. At the North West Corner of sec 8 T 33. R. 16 I set a Lime stone 23"x12"x4" marked IIII, At a point 2600 feet N. 89° E. From N. West Corner of sec 8. I set a Lime stone 18"x8"x4" Marked ¼ for the ¼ post on north line Sec 8, near center of Cross roads. At a point 1307 feet S 3°45' E. from the north west Corner of sec 8, I set a Lime stone 24"x8"x3" marked X as the S.W. Corner of the N.W.¼ of the N.W.¼ Sec 8. T. 33 R. 16 at a point 2614 ft. S. 3°45' E from the N.W. corner of Sec. 8 I set a Lime stone 23"x8"x7" marked ¼ I put flags at the now established out side center corners to the South west ¼ of Sec 8 T 33 R. 16 Ran straight lines between ay their intersection I set a Sand stone 20"x9"x6" marked X as the center of the South west ¼ of Sec 8, I also measured East from the S.E. Corner of the N.E ¼ of the S.W. ¼ of Sec 8, Found the distance East to Sec line Distance 2554 ft. At the middle point on this line I set a sand stone as the South west corner of the N.E¼ of the S.E.¼ of Sec 8 At a point midway between the ¼ post on the East line of sec 8 & the center of sec 8 I set a Sand Stone 14"x8"x8" marked X as the N.W. Corner of the N.E.¼ of the S.E. ¼ of Sec 8. The last ¼ of the day Leroy Holland flaged This finished the Survey of Sec 8. T 33 R 16 E.

Var. 8° E

Dated at Independence Montgomery County Kansas August 3rd 1901

S.L. Hibbard County Surveyor

NOTICE—Surveyor's Permanent Record, State of Kansas.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description.

....., Kansas, ... 189....

M.....

You are hereby notified that, at ..... o'clock A. M., on the ..... day of ....., 189....., I will begin a survey on Section ....., Town ..... South, Range ....., in which you are interested, and shall continue the same from day to day until completed. Commencing at the ..... corner of said Section, I shall permanently establish

.....

.....

.....

.....

..... County Surveyor,

..... County, State of Kansas.