

This is to certify that I, L. L. Hibbard, County Surveyor of Montgomery County Kansas was ordered by Roy Gore to survey & subdivide Section 31 Township 34 Range 15 S. On October 11th 1901 the following named parties were notified that a survey of the above named section would be made the survey to begin on the 22 day of Oct 1901.

L. H. Pennington, H. H. Tacker, A. D. Melander, A. M. Sherman, L. H. Preyton, Ed Mason,
H. J. Gore, J. M. Smith, J. D. Banay, M. J. Moody, E. H. Aorish,
T. Wood, Ben Duff, Hazzard Reed, A. J. Cook, Roy P. Gore

On October 22nd 1901 I began the survey of Section 31. Mathies & D. E. Schofield were selected as chainmen & were duly sworn. From the South West corner a stone of Section 31, T. 34 R. 15 S. I ran North on the Range line at 1320 ft drove stake at 2645 ft. stone the 1/4 post on the west line sec 31. From this 1/4 post I ran North 2640 ft on Range line & dug down 12 inches & found the corner stone. The North West corner of Sec 31. From this corner stone I ran East at 1320 ft stake at 2800 ft. Drove stake as temporary 1/4 post on North line of Sec 31. From this temporary 1/4 post I ran East at 900 ft, draw at 1800 ft, draw at 2645 ft. a stone the North East corner of Section 31. From this stone the North East corner Sec 31. I ran S 0° 40' E. at 2640 ft drove stake as temporary 1/4 post on East line of Sec 31. From this temporary 1/4 post I ran South 1320 ft. drove stake as temporary 1/4 post at 2640 ft. drove Iron pin as temporary C. C. corner to sec 31 I offset North 10 ft. ran due west on South line of Sec 31 at 2640 ft. drove stake as temporary 1/4 post on the South line of Sec 31. From this temporary 1/4 post I ran west at 900 ft. drove stake & quit for the day. Oct. 23, 1901. From the stake 900 ft west of the 1/4 post on the South line of Section 31 I ran West at 1400 ft. drove stake at 2842 ft. out 10 ft. north of stone offset back ten ft to line, correction for South line drove stake 15 ft west of temporary 1/4 post on South line sec 31 as true point for 1/4 post at a point 1320 ft. west true point for the C. C. corner of the East 1/2, S. 1/2 Sec 31 leaving the fractional West 1/2 South West 1/4 1499 ft on South line. I adjourned the survey until Oct 25, 1901. October 25, 1901 the survey of Section 31 Township 34 Range 15 S. continued. At a point 2794 ft East of the North West corner of sec 31 I set a line stone 27x18x3" marked 1/4 for the 1/4 post on the North line of sec 31. This corner was located by measurement from the west 1/2 road north I found a stone standing on this North 1/4 South line. At a point 2640 ft S 0° 45' E from the North East corner of Sec 31 I set a line stone 21x14x5" marked 1/4 for the 1/4 post on East line of Sec 31, also drove an iron bar beside the stone. At a point 1320 ft. South of the 1/4 post on the East line of Sec 31, I set a line stone 16x9x3" marked X as the N. E. cor S 1/2 S. E. 1/4 Sec 31. At a point 1320 ft South of the last described corner I set a sand stone 22x12x6" marked 1111. This stone is on the Township line & is the corner to Sections 31, 32, 33 & 34. Bearing of the East line of the South East 1/4 of Sec 31 is S 0° 20' E. At a point 2655 ft. west of the South East corner of Sec 31 I set a line stone 22x10x3" marked 1/4 for the 1/4 post on the South line of sec 31. At a point 1320 ft. west of the 1/4 post on the South line of sec 31 I set a stone as South West corner of the East 1/2 of the South West 1/4 of Sec 31 at a point 30' north of this stone I drove an Iron pipe as N. E. corner of the Sherman tract at points on West line of Sec 31, 30 ft north of the center of the D. M. & A. R. R. track also 80 ft north of center of track Drove Iron Rod as West corner of the Sherman tract. also drove Iron Rod at the angles of the North line of right of way of the above mentioned road & the South line of Sec 31 intersects the north line of D. M. & A. R. R. also at a point 30 ft north of the intersections of the South line Section 31 & the North line of the right of way of the D. M. & A. R. R. at point where the lines of the Sherman tract deflected I put flags on the 1/4 posts ran straight lines between, at their intersection I set a sand stone 25x12x5" marked X as the center of Sec 31. At a point 1350 1/2 ft west of the center of Sec 31 I set a sand stone 10x7x2 1/2" marked X as the N. W. corner of the East 1/2 of the S. 1/2 of Sec 31. At a point midway between the 1/4 post on the South line of Sec 31 & the center of this Section 31 I set a sand stone 18x12x6" marked X as the N. W. corner of the S. E. 1/4 of the S. E. 1/4 of Sec 31 T. 34 R. 15 S. A. D. Jordan assisted as chainman & marker for 2 days. This completed the survey on Oct 26, 1901.

NOTICE—Surveyor's Permanent Record, State of Kansas.
[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

I, _____, Kansas, _____ 189____

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
_____, County, State of Kansas.

Var 8° E. Dated at Independence Montgomery Co Kansas November 20th 1901
L. L. Hibbard, Co Surveyor