

This is to certify that I S. L. Hibbard County Surveyor of Montgomery Co, Kansas was ordered by T. B. Mc Nulty to survey and subdivide Section Seven (7) Township 35 Range 17 East. On the 28th day of October the following named persons were notified that a survey of Section Seven T. 35 R. 17 E. would begin on Oct 28th 1901.

Gladys M. Benson Archie Cooper Elmina Howell J. F. Gentner Mary Powell
Chas. C. Lyons Joseph A. Good J. D. Slatter T. B. Mc Nulty Pauline Sprowl
William McCloud J. B. Bentley E. J. Wand Adam Beatty

On October 28th 1901 I began the survey E. C. Lipey & M. C. Bentley were selected as chainmen & were duly sworn. From the South East corner of Sec 7. T. 35 R. 17 E. a stone ran North 1° 10' at 1320 ft. drove stake at 2640 ft drove stake as temporary 1/2 post on the east line of Sec 7 at 3960 ft drove stake at 5300 ft a stone the North East corner of Sec 7. From the North East corner of Sec 7. I ran North 87° West at 1320 ft drove stake at 2640 ft same out 15 ft North of the 1/2 post a stone on the North line of Sec 7. From this stone the 1/2 post on the North line of Sec 7 I ran North 87° 15' West at 1326 ft drove stake & quit for the day Oct 29 1901. From the Stake driven 1326 ft West of the 1/2 post on the North line of Sec 7. T. 35 R. 17 E. I ran N. 87° 15' W. 3260 ft I came out 8 ft North of the North West corner of Sec 7, a stone. From this North West corner of Sec 7 I ran S. 1° 30' E. at 2640 ft a stone the 1/2 post on the West line of Sec 7. From this 1/2 post I ran South 2° E. at 1320 ft a stone at 2640 ft a stone the South West corner of Sec 7. From this South West corner of Sec 7 I ran S. 87° E. at 1882 ft drove stake. From this Stake I ran S. 87° E. at 975 ft. ran over a top of bluff at 1350 ft. came out 17 ft North of a stone adjourned for dinner. P. M. From this stone the S. E. corner of Lot 11 Sec 7. T. 35 R. 17 E. I ran S. 87° 15' E. at 1317 ft 1/2 post at 2637 ft. stone From this stone it is 1317 ft to Sec cor. S. E. corner Sec 7. From the Stone at the South West corner of the S. E. 1/4 Sec 7 T. 35 R. 17 E. I ran South at 1316 ft in Sec 18, a stone From this last named Stone, I ran N. 87° W. at 1320 ft. drove & set a stone 20" x 5" x 6" marked X. At a point 231 ft. West of this stone I put in a stone drove an Iron pin as South West corner of the 1/4 rod tract, also measured West on Sec line from the 1/2 post on the South line of Sec 7 231 ft. set a stone as the N. W. cor. to 1/4 rod tract. Also set corners to 1/2 acre tract in Sec Lot 1, Sec 18 T. 35 R. 17 E. adjoining Sec 7 on South. Oct 30 1901 Survey of Sec 7 continued Bearing of East line of Sec 7 is N. 1° 10' W. At a point 1327 1/2 ft. North on Sec line from the South East corner of Sec 7 I set a lime stone 23" x 15" x 12" marked X as the N. E. corner of the S. E. 1/4 of the S. E. 1/4 Sec 7 T. 35 R. 17 E. at a point 1327 1/2 ft. North of last named corner I set a lime stone 26" x 16" x 10" marked 1/4 for the 1/4 post on the East line of Sec 7. At a point 1323 ft North of the 1/4 post on East line of Sec 7 I set a lime stone 24" x 19" x 6" marked X as the S. E. cor. N. E. 1/4 N. E. 1/4 Sec 7 T. 35 R. 17 E. At a point 1323 1/2 ft. West on Sec line from the N. E. cor. of Sec 7, I set a lime stone 20" x 14" x 8" marked X as the N. W. cor. N. E. 1/4 N. E. 1/4 Sec 7. At a point 1327 ft N. 87° 15' W. of the 1/4 post on the North line of Sec 7 I set a lime stone 26" x 10" x 10" marked X. This in place of stone as the N. W. cor. Lot 1. Sec 7 T. 35 R. 17 E. I ran a straight line from the 1/4 post on the South line of Sec 7 to the 1/4 post on the North line Sec 7 also from the 1/4 post on the East line to the 1/4 post on the West line at the intersection of the 1/4 line I set a lime stone 22" x 6" x 6" marked X X as the center cor. Sec 7. At a point midway between the center Sec 7 & the 1/4 post on the East line I set a lime stone 24" x 9" x 4" marked X as the N. W. cor. N. E. 1/4 S. E. 1/4 Sec 7. From the center Sec 7 I ran N. 87° 15' West at 1320 ft. drove stake. Oct 31, 1901 From the stake driven 2640 ft W. on 1/4 line from center Sec 7 I ran N. 87° 15' W. at 1925 ft the 1/4 post on West line of Sec 7. At a point 2640 ft. West on 1/4 line from center Sec 7 I set a lime stone 10" x 6" x 15" marked X as N. W. cor. lot 8 of Sec 7. at the N. E. cor. lot 8 I set a lime stone. At a point 1320 ft N. 1° 10' W. From the N. E. cor. Lot 8 of Sec 7 I found a stone at N. W. cor. lot 6, Sec 7. I set the center of the N. E. 1/4 Sec 7 by putting flags on the out side.

NOTICE—Surveyor's Permanent Record, State of Kansas. (Geo. W. Crane & Co., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description.)

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

_____, Kansas, 189____.

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor, _____ County, State of Kansas.

corners also set the center of the S. E. 1/4 of Sec 7 by running straight lines between its 1/4 corners I set lime stones at the center of each of the above mentioned 1/4 sections I also set a stone 19 1/2 ft. S. 87° 15' E. from the South West cor. of Sec 7. In digging down I found old Stone 2 ft under the ground I set a lime stone on top of it as the South West corner of Lot 11 Sec 7. T. 35 R. 17 E. This completed the Survey on October 31, 1901

Var. S. E. Dated at Independence Montgomery County Kansas Nov 29th 1901
S. L. Hibbard Co. Surveyor.