

This is to certify that S. L. Hibbard County Surveyor of Montgomery Co. Kansas, was ordered by Alexander Hannah & J. E. Williamson to survey and subdivide Section 14 Township 32 Range 16 East. On the 5 day of November 1901 the following named parties were notified that a survey of the above named section would be made to begin on November 13 - 1901.

J. E. Williamson Jeremiah Mahoney Joseph Miller E. Dyer
J. H. Sherman Walter P. Alexander Peter Cannon Stephen M. Benson
Alexander Hannah J. Beeghly J. A. Devine Mrs. O. Brady

Mr. John Rowland & the Magredy boys were present during the survey.

On November 13, 1901 I began the survey John Hannah & Armond Schierlman were selected as chainmen & Walter P. Alexander as flagman. Who were duly sworn. From the North East corner of Sec 14, T. 32, R. 16 E. ran South 1° 0' E. at 1320 ft. drove stake at 1339 ft. Center Southern Kansas Rail Road at 2640 ft. drove stake as temporary 7/8 post on East line Sec 14, at 5280 ft. drove stake as temporary S.E. corner of Sec 14. From this temporary S.E. corner of Sec 14 ran N. 89° 45' W. at 1320 ft. drove stake at 2661 ft. Drove stake as temporary 7/8 post on the South line of Sec 14. From this temporary 7/8 post of Ran N. 89° 45' W. 2647 ft. drove stake as temporary South West corner Sec. 14, T. 32 R. 16 E. From this temporary S.W. cor. Section 14 ran N. 0° 45' W. At 2189 ft. Center S. K. R. R. at 2640 ft. drove stake as temporary 7/8 post on the West line of Sec. 14. From this temporary 7/8 post ran N. 0° 45' W. at 900 ft. Bridge at 1320 ft. drove stake From this Ran N. 0° 45' W. at 1325 ft. drove stake as temporary N.W. cor Sec. 14. From this temporary N.W. cor Sec 14, ran East 1320 ft. drove stake at 1960 ft. bridge over draw at 2640 ft. drove stake as temporary 7/8 post on North line Sec 14. From this stake as temporary 7/8 post ran East at 1545 ft. bridge over draw at 1800 ft. bridge over draw at 2655 ft. a stone the North East corner Sec. 14 T. 32 R. 16 E. At the South West corner Sec 14 set a line stone 24" x 12" x 6" marked 1111 for South East cor. Sec. 14 at a point 2640 ft. N. 1° W. from S.W. cor. set a line stone 24" x 12" x 12" for the 7/8 post on East line Sec. 14. At a point 1327 ft. West from S.E. cor. Sec. 14 set line stone 22" x 16" x 7" marked X as the South West corner S.E. 1/4 of the S.E. 1/4 Sec. 14 At a point 2654 ft. West of S.E. cor Sec 14 set a line stone 22" x 11" x 10" for 7/8 post on South line Sec. 14 At a point 2654 ft. west of the 7/8 post on South line Sec 14 set a line stone 22" x 18" x 8" marked 1111 for the South West corner Sec 14. Bearing of the South line Sec 14 is East & West At a point 2640 ft. N. 0° 45' W. from the South West cor Sec. 14. I set a line stone 27" x 15" x 6" marked 7/8 for the 7/8 post on West line of Sec 14

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

_____, Kansas, 189____.

M. _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

18" x 7" x 7" marked X as N.W. cor. S.W. 1/4 S.E. 1/4 Sec 14. At the center of the South East 1/4 of Sec 14, I set a sand stone 24" x 9" x 7" marked X at a point midway between the center Sec 14 and the 7/8 post on the North line Sec 14 I set a line stone 18" x 9" x 6" marked X as the S.E. cor N. 1/2 N. 1/4 Sec 14 T. 32 R. 16 E. This completed the survey.

Var 8° E.

Dated at Independence Montgomery County Kansas Dec. 13 1901
S. L. Hibbard County Surveyor