

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, S. L. Hibbard County Surveyor of Montgomery County Kansas was ordered by James Bell to survey and subdivide Section 16 Township 34 R. 14 East. On December 3rd 1901 the following named parties were notified that a survey of the above named section would be made the survey to begin on 10th day of December 1901.

Frank Hagerman	David John	E. J. Mearns - Ayt	Francis Braddock
H. E. Luwertzel	Lda M. Sinclair	J. H. Bowersock	Joseph Schneider
Valentine Bowersock	James Bell	Josiah B. Ross	Catherine Hering

On the 10 day of December 1901 I began the survey. Sherman John and James Henderson were selected as chainmen and were duly sworn. I went to the North West corner of Section 16. T. 34. Range 14. E. A stone and drove South 0° 30' East at 2645 feet a stone, the 1/4 post on the West line of Sec. 16. From this 1/4 post I ran S 0° 30' East at 2645 ft. a stone the South West corner of Sec. 16. From this stone the South West cor of Sec 16. I ran North 89° 50' E. at 2670 ft a stone the 1/4 post on the South line of Sec 16. From this stone the 1/4 post on the South line of Sec. 16 I ran N 89° 50' E. at 2670 ft. Made X mark on sand stone, as temporary South East corner of Sec 16. From this temporary S. E. corner of Sec 16 I ran N 0° 35' E. at 2672 ft. drove stake by piece of sand stone supposed to be 1/4 post on East side Sec 16, but on Examination of the stone it was but a small fragment (if it was over a part of the original stone) which could have been easily moved by wagon wheels in the soft earth. I left this subject to correction. From the stake driven by this stone I ran North 0° 35' E. at 280' draw at 2656' drove stake as temporary N. E. corner of Sec 16. From this temporary N. E. corner of Sec 16. I ran S 88° 45' E. at 2680 ft drove stake as temporary 1/4 post on the North line of Sec 16. Heavy Hedges indicated that the 1/4 post was placed there by the Government. This I verified by running the 1/4 lines and found a stone set as the center of Sec 16 which was established when the 1/4 posts were standing. From this temporary 1/4 post on the North line of Sec 16. I ran due west at 2652 ft N. E. corner Sec 16. Dec 11th 1901. At the South East corner of Sec 16. I corrected 9 ft. North. of the mark made as the temporary corner and set a line stone 25" x 8" x 8" marked 1111. At a point 2660 ft North of this S. E. corner I set a line stone 28" x 9" x 8" marked 1/4 for the 1/4 post on East line of Sec. 16. At a point 2660 ft. North on sec line from the 1/4 post on the East line of sec. 16. I set a line stone 24" x 14" x 6" marked 1111. At a point South 88° 45' E. of the North East corner Sec 16. 2677 ft I set a line stone 24" x 10" x 5" marked 1/4 for 1/4 post on North line sec 16. I ran straight lines between the 1/4 posts and found at the intersection of the 1/4 lines a small flag stone as the center of sec. 16. At the center of Sec 16 I set a line stone 26" x 7" x 4 1/2" marked X as the center of sec 16 I put the small flag stone beside it as witness this completed the survey on Dec 11, 1901.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

_____, Kansas, _____ 189____.

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

County Surveyor,

County, State of Kansas.

Var. 8° E.
Dated at Independence, Montgomery County Kansas
January 4th 1902.
S. L. Hibbard Co. Surveyor.