

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that S. L. Hibbard County Surveyor of Montgomery Kansas was ordered by James Bell to survey and subdivide Section 19 Township 34, Range 14 East. On January 6, 1902 the following named parties were notified that a survey of the above named section would be made the survey to begin on the 13th day of January 1902.

Peter Malone	Jesse Orr	Milton Bowercock	James D. Gamble
S. L. Hull	Thomas E. Shipley	A. D. Berry	C. H. Gilmore
May Ketch	James M. Farland	Reason Robinson	James Bell
John A. Hooker	J. R. Blair, Agt	Harriet H. Morrow	
J. B. Rose	J. D. Blake	J. B. Gilmore	

On Jan 13, 1902 I began the survey James Hendrickson and N. A. Shipley were selected as chainmen, Henry Gilmore as flagman. From a stone the north west corner of section 19 T. 34 R. 14 E. I ran South on the Range line at 1320 ft. drove stake as temporary S. E. cor. of the N. E. $\frac{1}{4}$ section 19 (or lot 1) at 2640 ft. drove stake as temporary $\frac{1}{4}$ post on West line of sec 19. From this stake I ran south at 2640 ft. drove stake which was about 18" north and 2 ft west of a small fragment of a stone which I dug up and pronounced it as part of the original corner stone. As it was well down in the hard ground. From the stake driven I ran East on R. 14 E. this was on a line of an old fence, running South through Sec 20. From this stake as temporary $\frac{1}{4}$ post on the South line of sec. 19 I ran East at 1320' found marked stone down. (Sand stone on line with a hedge running north through sec 19 at 2640 ft. drove stake as temporary South East corner of sec. 19. From this sec 19 from this stake I ran N. 1° 30' E. at 2660 ft. a stone North East corner of sec 19. I corrected S. E. cor. 1 ft south and set a lime stone for $\frac{1}{4}$ post on East line sec 19. 28" x 10" x 5" marked 4. Jan 14, 1902. At a point 1320 ft South 1° 10' E. from N. E. cor sec 19 I set a lime stone 26" x 15" x 5" marked X as S. E. cor lot 1. Sec 19, T. 34 R. 14. At a point 2640 ft S. 1° 10' E. of N. E. cor, sec 19. I set a lime stone 33" x 12" x 8" marked $\frac{1}{4}$ for $\frac{1}{4}$ post on West line sec 19. At a point 2640' South 1° 10' E. of the $\frac{1}{4}$ post on West line sec. 19 I set a lime stone 24" x 18" x 12" marked 1111 for South West cor to sec 19. At a point 1346 ft East of South West corner of sec 19, T. 34 R. 14 E. I set a lime stone 25" x 8" x 7" marked X as S. E. corner to Lot 4

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. CRANE & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

M _____, Kansas, _____ 189____.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
_____, County, State of Kansas.

Sec 19 T. 34 R. 14 At a point 2666 ft. East of S. E. cor Section 19 I set a lime stone 22" x 18" x 5" marked $\frac{1}{4}$ for the $\frac{1}{4}$ post on South line of sec 19, at a point 1320 ft East of the $\frac{1}{4}$ post on South line of sec 19 I set a lime stone 20" x 8" x 6" marked X for S. E. cor. $\frac{1}{2}$ S. E. $\frac{1}{4}$ sec. 19. At a point 1320 feet East of the last described stone I set a lime stone 30" x 12" x 6" marked 1111 for the South East corner of sec 19 T. 34 R. 14 E. I put flags on the $\frac{1}{4}$ posts and ran straight line between at the intersects. I set a sand stone 26" x 9" x 7" marked XX At a point midway between the center of sec 19 and the $\frac{1}{4}$ posts on East and West lines of sec 19 I set stones at a point 1320 ft East on $\frac{1}{4}$ line from center sec 19 I set a sand stone 21" x 10" x 4" marked X as S. E. cor $\frac{1}{2}$ N. E. $\frac{1}{4}$ sec 19. At a point 1320 ft west of center sec 19 on $\frac{1}{4}$ line I set a sand stone 18" x 7" x 7" marked X as S. E. of the $\frac{1}{2}$ of the N. E. $\frac{1}{4}$ sec 19. At a point 1323 $\frac{1}{2}$ ft north of the last described cor. I set a sand stone 29" x 9" x 3" marked X as the S. E. corner of lot 1 sec 19, T. 34 R. 14 E. In describing location of stones set South: East: West & North: are used in a general way if the true bearing is not given in the report it will be given on the map or plat. belonging to the Report.

Var 7° 55' E.

Dated at Independence Montgomery Co Kansas Jan 25th 1902
S. L. Hibbard Co. Surveyor.