

Survey No. _____, Section 24, Town 34 South, Range 13.

This is to certify that I, D. L. Hibbard, County Surveyor of Montgomery Co., Kansas, was ordered by Pearson Robinson to survey and subdivide Section 24 Township 34 Range 13 East. On the 6th day of January, 1902 the following named parties were notified that a survey of the above named Section would be made. The survey to begin on Jan 15, 1902. William Michael, D. L. Clark, Geo. T. Blackmore, J. A. Moore, C. T. Meers, J. B. Ross, J. R. Blair, J. May, Melch Joseph King, Pearson Robinson, J. C. Shipley, Jesse Orr, Jonas Gilmore, Atlantic Trust Co. On Jan 15, 1902 I began the survey. Jesse Orr, N. A. Shipley, were chosen as chainmen and Henry Gilmore as flagman. From the North East corner of Section 24 T. 34 R. 13 E. I ran S 89° E at 2602 ft. a stone marked 7/8 from this stone on north bank of draw I ran S 89° E at 50 ft creek at 200 ft. creek at 2646 ft. a stone the N. E. cor to Sec. 24 I find the location of the 4 post as now standing on the north line of Sec 24 to be 22 ft. East of the center of the north line but on examination of the Government field notes, I found a witness tree and the distance given from the stone corresponded to that given by field notes. And as heavy hedges on each side indicated the original location. From the North West corner of section 24 I ran South at 2641 ft. the 4 post on West line of sec 24. From this 4 post I ran south at 2641 ft. a stone the south west corner of sec 24. From this stone I ran N. 89° E. at 1320 ft. drove stake at 2640 ft. a stone the 4 post on the South line of Sec 24. From this 4 post I ran N. 89° E. at 1320 ft. drove stake at 2640 ft. a stone the South East cor of Sec. 24. Thence N. 1° 10' West at 2640 ft. 4 post, at 5280 ft. a stone N. E. cor Sec. 24. Quit for the day. Jan 16, 1902. From the 7 post on East line sec 24 I offset south 10 ft and ran S 89° E at 1300 ft. drove stake at 2625 ft. a stone 10' north of line run, this stone was probably set for the center of the section, I ran the line to west line of sec 24 came out 11 ft. south which would make one foot south of the 7 post after setting back 10' north to true line. I then went to the 4 post on the south line of Sec. 24 I ran North 1° E. to the 4 post on the north line of sec 24 found the center stone correct. At a point 1301 ft. West of the North East corner of sec. 24 I set a line stone 28x18x5 marked x as the North West corner of the E 1/2 of the N. E. 1/4 of Sec 24. T. 34. R. 13. At a point 1320 ft. west on sec line from the South East corner of sec 24 I set a line stone 18x18x5 marked x as S. W. corner of the E 1/2 of the S. E. 1/4 of sec 24. T. 34. R. 13. I put flags on the N. E. corner of the E 1/2 N. E. 1/4 and the S. W. cor of the E 1/2 S. E. 1/4 Sec 24 and adjusted my transit between, at the intersection of the 4 lines I set a line stone 24x8x6, for N. E. cor E 1/2 S. E. 1/4 Sec. 24 T. 34. R. 13. This completed the survey.

Var 8° E.

Dated at Independence Montgomery Co Jan 28, 1902
D. L. Hibbard, Co Surveyor.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

_____, Kansas, 189____.

M _____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.