

This is to certify that J. S. Hubbard County Surveyor of Montgomery County Kansas was ordered by D. R. Cope to Survey and Subdivide Section 29, Township 32, Range 13, East, January 18, 1902. The following named parties were notified that a survey of the above named section would be made. The survey to begin on the 20 day of January, 1902. Owing to a severe snow and wind storm that day the survey was postponed until Feb. 12, 1902. On Feb. 12, 1902 I began the survey. The 11th of being cold and snow on the ground. J. T. Green and H. D. Hackmaster were selected as chainmen. There being no stone on the section I went to the 1/4 post between sections 4 and 5 Township 32 R. 13 E. I ran North on the section line one and 1/2 miles drove a stake as temporary S.E. corner of Sec 29. T. 32 R. 13 E. From this stake as temporary South East corner of Sec 29, I ran N 1/4 at 70 ft. broke at 565 South Bank same break at 2640 ft. drove stake as temporary 1/4 post on East line of Sec 29. From this temporary 1/4 post I ran N 1/4 at 660 ft. stake at 1320 ft. stake at 2651 ft. drove stake as temporary N.E. corner of Sec 29. To establish this line I corner I went East to a stone on the North line of Sec 28, and ran west 3960 ft. and drove a stake as the permanent N.E. corner of Sec 29. The stones from which I started have been in place for 25 years as stated by the old settlers and were located when the section corners were standing. From the permanent N.E. corner of Sec. 29 I ran S 89° 30' E. at 1100 ft. a creek at 1720 ft. a creek at 2640 ft. drove stake as temporary 1/4 post on the north line of sec. 29. From this temporary 1/4 post on north line of sec 29, I ran S 89° 30' E. at 1320 ft. drove stake at 2647 ft. drove nail near center of public Road as temporary N.W. corner of sec 29. From this temporary N.W. corner of sec 29, I ran S 1° E. at 1320 ft. drove stake at 2640 ft. drove stake as temporary 1/4 post on West line of Sec 29. From this temporary 1/4 post on the west line of sec 29 I ran S 1° E. at 1320 ft. drove stake at 2640 ft. drove stake as temporary S.W. corner of Sec 29 and quit for the day. Feb 13, 1902 Survey of Sec 29 continued. From temporary South West corner of sec. 29 I ran N 89° 30' E. at 2640 ft. drove stake as temporary 1/4 post on South line of section 29. Here I offset South 20 ft. and ran N 89° 30' E. at 1320 ft. drove stake at 2000 ft. creek at 2652 ft. came out 9 ft. South of temporary cor offset back 20 ft. to line which was 11 ft. north of the temporary S.E. cor of sec 29. There I set a line stone 26" x 11" x 6" marked 1111 for the S.E. cor to sec 29. At a point 2640 ft. N 89° 30' E. from this S.E. corner I set a line stone 29" x 9" x 9" marked 1/4 for the 1/4 post on the East line of sec 29. At a point 5280 ft. S 89° 30' E. from the 1/4 post on the east line of sec 29, I set a line stone 27" x 9" x 8" marked 1111 for the N.E. corner of section 29. At a point 5280 ft. S 89° 30' E. from the N.E. corner of Sec 29 I set a line stone 32" x 16" x 7" marked 1111 for the North West corner of section 29. But for the day as it is raining & muddy. Feb. 14, 1902. Ground covered with snow I adjourned to meet again Feb. 14, 1902 the following named parties were notified that a survey of Sec 29, T. 32 R. 13 E. would be made on Feb 25th 1902 the following named parties were also notified before survey was begun.

NOTICE—Surveyor's Permanent Record, State of Kansas.
[Copyright, 1891, by R. A. BAILEY, Topeka, Kansas.]

Kansas, _____ 189 _____

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189 _____, I will begin a survey on Section _____ Town _____ South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

County Surveyor,
County, State of Kansas.

A. L. Partridge, J. G. Swalley, William Jackson, H. A. Gastenau, R. B. Burns, Jasper Beluearanger, Clementine Lee, L. A. Sell, H. D. Henderson, H. F. Smith, E. M. Koger, John Cummings, J. Klem, O. F. Joiner, Cornelius Hues, D. R. Cope. On Feb 25 I began the survey. J. T. Green & H. D. Hackmaster were chainmen. R. Worn to do their duty. I set flags on the now established N.E. and N.W. corner of sec 29. T. 32 R. 13 E. At a point midway between their corners (2644 ft. to each corner) I set a line stone (26" x 15" x 8") marked 1/4 for the 1/4 post on the North line of sec 29. At a point midway between the 1/4 post and the N.W. corner of sec 29, I set a line stone 24" x 12" x 6" marked X as the N.W. cor. of the N.E. 1/4 of the N.W. 1/4 of Sec 29. At a point 5280 ft. S 1° E. from the North West corner of Sec 29. At a point 1320 ft. N 1° W. from S.W. corner of sec 29 set a line stone 23" x 12" x 8" marked 1/4 for the 1/4 post on West line sec 29. At a point 1320 ft. S 1° E. from the N.W. corner of sec 29 set a sand stone 18" x 12" x 6" marked X as S.W. cor N 1/2 N.W. 1/4 Sec 29. Feb 26, 1902 Survey of sec 29 continued. I set flags 12 ft. South of the S.W. cor & S.E. corners of Sec 29 on each of edge trees adjusted to transit between at a point 2646 ft. East of S.W. cor Sec 29. I set a line stone 22" x 12" x 6" marked 1/4 for the 1/4 post on the South line of sec 29. At a point 1323 ft. East of the 1/4 post on the South line of sec 29, I set a line stone 26" x 8" x 6" marked X as the S.W. cor S.E. 1/4 of the S.E. 1/4 of sec 29. T. 32 R. 13 E. At 2646 ft. S.E. cor Sec 29. I then put flags on the North & South 1/4 posts along E & W 1/4 post lines straight lines between. At the intersection of the 1/4 lines, I set a sand stone 13" x 13" x 11" marked XX, as the center of section 29. At a point on the 1/4 line, 1320 ft. south of the 1/4 Post on the North line of sec. 29 I set a sand stone 16" x 11" x 9" marked X as the S.W. corner of the N.W. 1/4 of sec 29. At a point on the 1/4 line 1320 ft. South of the center of sec 29. I set a sand stone 16" x 10" x 6" for the N.E. cor of the S.E. 1/4 of the S.W. 1/4 of sec 29. At a point 1322 1/2 ft. East of the center of sec 29 I set a sand stone 18" x 12" x 4" marked X as the S.E. cor, S.W. 1/4, N.E. 1/4 Sec 29. At a point on the Sec line 660 ft. N 89° 30' E. from the 1/4 post on the East line of sec 29, I set a sand stone 24" x 6" x 6" marked X as N.E. corner S.E. 1/4 S.E. 1/4 Sec 29. T. 32 R. 13 E. This completed the survey on Feb 26, 1902.

Var 7° 55' E.
Dated at Independence Montgomery County Kansas March 8, 1902.
J. S. Hubbard Co Surveyor