

Survey No. _____, Section 12, Town 35 South, Range 13

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that S. L. Hibbard County Surveyor of Montgomery County Kansas was ordered to Survey and Subdivide Section Twelve (12) Township 35, Range 13 East. and to establish the corners and such other corners of the above described Sec 12, as necessary to locate their lands which are the South 1/2 of the South West 1/4 of the North East 1/4 of Sec 12, Township 35 R. 13 E. On the 28 day of February 1902, the following named parties were notified that a survey of the above described section would be made the survey to begin on the 10th day of March 1902. Copy of Notice of Survey. You are hereby notified that I will be at the Residence of W. C. Meeker on the 10th day of March 1902 at 1 o'clock P. M. for the purpose of surveying the lands of J. and W. C. Meeker and others lying in Section 12, Township 35, Range 13 East you will therefore be prepared to pay your proportionate part of the expense of said survey in accordance with sections 7 & 11, Chapter 89 of the laws of 1891, Dated at Independence Kansas this 28 day of February 1902. S. L. Hibbard Surveyor of Montgomery County Kansas. Parties notified J. C. Mellor, Hattie D. Ross, F. Reynolds, Mark Baye, Mrs. Joseph Genhart, O. C. Boarding, W. H. Ridgeway, John D. Foot, J. J. Brooks, J. E. Stone, H. Edwards, D. H. Plowman, Millie H. Cox, Thomas Steel, Geo. F. Braden, W. C. Meeker, W. S. Brown, W. L. Dodden, C. B. Skinner, W. S. Upham, On March 10th in P. M. I began the survey C. Smith & W. S. Brooks were selected as Chainmen and H. Hildebrand as Flagman. I went to the 1/4 post on the north line of Section 12 Township 35 Range 13 East a stone the government corner. From this 1/4 post I ran south 88° 40' west at 2570 ft East Bank of Cheyene Creek, at 2640 ft. drove stake, I examined the trees for witness trees as shown by Government field notes, As an Iron Bridge had been constructed across the creek at this point I found only one tree that corresponded to the 4 given by the field notes. The others were probably cut down, I located a temporary corner for the north west corner of Sec 12 and ran S. 0° 40' E. at 10 ft water of creek at 1016 ft. center of D. M. & A. Rail-Road At 2640 I drove stake as temporary 1/4 post on West line of Sec 12. From this temporary 1/4 post I ran S. 0° 40' E. at 2600 ft drove stake as temporary South West corner of Sec 12. From this temporary S.W. corner I ran N. 88° 40' E. at 2644 1/2 ft. a stone the 1/4 post on the South line Sec 12. T. 35 R. 13 E. I quit for the day March 11, 1902. The rain of last night and the morning prevented Survey of Sec. 12 until afternoon. Alfred Hopper was sworn as Chainman in place of C. Smith, assisted by W. S. Brooks. From the 1/4 post on the South line of Sec. 12 T. 35 R. 13 E. I ran East at 1320 ft drove stake as temporary corner S. E. corner S. E. 1/4 Sec 12, at 2640 ft. drove stake as temporary S. E. Corner of Sec 12 this temporary corner is 20 ft. East of an old Established fence running South, to the territory line. From this temporary S. E. corner of Sec 12 I ran N. 30° West at 1300 ft. drove stake in Coffeyville & Caney Road. From this last stake I ran N. 0° 30' W. at 1314 ft. drove stake as the temporary 1/4 post on the East line of Sec. 12. From this temporary 1/4 post on East line Sec 12 I ran North on Sec line at 660 ft. drove stake as temporary N. E. corner of the S. 1/2, S. E. 1/4, N. E. 1/4 Sec. 12. At 1314 ft. drove stake as temporary S. E. corner N. E. 1/4 N. E. 1/4 Sec. 12. From this last named stake I ran North on Sec line at 200 ft. center D. M. & A. RR at 765 ft. ravine or draw, at 1314 ft. drove stake as

NOTICE—Surveyor's Permanent Record, State of Kansas.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

} GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas.
} Blank Books and Legal Blanks of Every Description.

....., Kansas, 189.....

M

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section, Town South, Range, in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish
.....
.....
.....
.....
.....
.....
.....
.....
..... County Surveyor,
..... County, State of Kansas.

South West Corner of section 12. T. 35. R. 13. Set a sand stone 18" x 11" x 10" marked 1111 for the corner to sec 11, 12, 13 & 14. At the north west corner of section 12. I set a sand stone 28" x 10" x 6" marked 1111 this stone is 11 ft. west of the stake driven at the temporary North West Cor. and 10 ft. north about 15 ft. from the north edge of the water^{2d} near the west side of the Iron Bridge. No witness trees were used to locate this point but the Elm given in field notes. At a point 262 2/2 ft. N. 0° 45' W. from the South West Corner of section 12 set a sand stone 30" x 13" x 8" marked 1/2 for the 1/2 post on the west line of sec 12. this 1/2 post is at a point midway between the N.W. Corner & the South West Corner of sec 12. Found a stone at the S.E. Corner of the south west 1/4 of the south east 1/4 of sec 12. which was 1310 ft. East of the 1/2 post on the south line of sec 12. March 13, 1902. Survey of section 12 Township, 35. R. 13. E. Continued At a point 2620 ft. East of the 1/2 post on the south line of section 12 set a sand stone 26" x 8" x 4" marked 1111 for the South East Corner of sec 12. This stone is 3 ft. 7 1/4 inches south of the stake driven for temporary South East Corner of sec 12 & 20 ft. west. Then went to the North East Corner of sec 12. Set a lime stone 2 ft. North 3/4 of 8 1/2 ft. East of the temporary N.E. Corner of sec 12 for temporary North East Corner of sec 12 & 20 ft. west. Then went to the North East Corner of sec 12. Set a sand stone 26" x 10" x 8" marked 1/2 for the 1/2 post on the east line of sec 12. size of stone 32" x 14" x 6" marked 1111. for N.E. Corner of sec 12. At a point midway between the N.E. & south East Corner of sec 12. set a sand stone 26" x 10" x 8" marked 1/2 for the 1/2 post on the east line of sec 12. At a point 656 ft. north of 1/2 post on sec line on East line sec 12. set a sand stone 25" x 12" x 6" marked X. At a point 1314 ft. North on sec line from South East Corner of sec 12. set a sand stone 25" x 12" x 10" marked X as the South East Corner of the N.E. 1/4 of the S.E. 1/4 of sec 12. T. 35. R. 13. E. I put flags on the 1/2 posts & ran straight lines between at the intersection set a sand stone 25" x 12" x 10" marked X as the center of sec 12. at a point on the 1/2 line 656 ft. north of the center of sec 12. set a sand stone 22" x 14" x 5" marked X as the N.W. Corner of the 1/4 lines: set a sand stone 25" x 11" x 10" marked XX as the center of sec 12. at a point on the 1/2 line 656 ft. north of the center of sec 12. set a sand stone 22" x 14" x 5" marked X as the N.W. Corner of the 1/4 lines: set a sand stone 25" x 11" x 10" marked XX as the center of sec 12. At a point 1275 1/2 ft. East of the 1/2 post on the North line of sec 12 set a sand stone 18" x 9" x 6" marked X as the S.E. Corner of the south 1/2 of the south west 1/4 of the north East 1/4 of sec 12. At a point 648 ft. East of the 1/2 post on the north line of sec 12 set a sand stone 18" x 6" x 4" marked X as the S.E. Corner of the West 1/2 of the N.W. Corner of the N.E. 1/4 of the N.E. 1/4 of sec 12. At a point 648 ft. East of the 1/2 post on the north line of sec 12 set a sand stone 24" x 14" x 9" marked X. Also set a sand stone at the N.E. Corner of the S.E. 1/2 of the S.W. 1/4 of the N.E. 1/4 of sec 12. T. 35. R. 13. E. This completed the Survey of sec 12, T. 35. R. 13. E. on March 14, 1902. Var. 7° 55' E.

March 14, 1902. Var. 7° 55' 18"

S. L. Hibbard County Surveyor

Dated at Independence Kansas Montgomery County, March 22nd 1902
 E. L. Hibbard - Co Surveyor.

S. L. Hibbard - Co Surveyor.