

Survey No. , Section 5 , Town 35 South. Range 17

Survey No. , Section 2 , Town 34 South, Range 16.

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, L. L. Hibbard County Surveyor of Montgomery County Kansas, was ordered by Joseph M. Neal to Survey & Subdivide Section 2 township 34, Range 16, East. On March 24, 1902 the following named parties were notified that a survey of the above named section would be made the survey to begin on the 1st day of April, 1902

|                |                   |                  |              |
|----------------|-------------------|------------------|--------------|
| E. Vandine     | A. L. Giesham     | Arma Slater      | Geo Foster   |
| Jack Hitts     | William A. Housel | Henry Miller     | Emma D. Gutz |
| Joseph M. Neal | Abijah Harding    | Robert B. Bonner |              |

On April 1, 1902 I began the survey T. V. Clay and H. Rusk were selected as chainmen, and were duly sworn. I went to the South west corner of Sec. 2, T. 34 R. 16 E. and ran North 0° 30' W. at 950 ft. top bluff at 1290 ft. creek "Foster branch" at 5320 ft. drove stake as temporary corner to S. L. & S. L. & Sec. 2, T. 34 R. 16, at 2640 ft. drove stake as temporary 4 post on the west line of sec. 2. From this temporary 4 post on the West line of sec. 2. I ran 70° 30' W. at 1320 ft. drove stake at 2629 ft. a stone N. E. corner of sec. 2. From the South West corner of Sec. 2, T. 34 R. 16, I ran 71° 30' East at 1980 ft. stake at 2170 ft. West bank of Foster creek at 2640 ft. drove a stake as the temporary 4 post on the South line of Sec. 2, T. 34 R. 16 E. From this temporary 4 post on the South line of Sec. 2, I ran 71° 30' E at 835 ft. West bank Verdigris River at 885 ft. water edge. Measured River by wire, 47 ft. across at 1320 ft. drove stake in edge of timber on East bank of River at 2676 ft. came out 37 ft. north of a stone the South East corner of Sec. 2. From this stone the South East corner of sec. 2. I ran North 0° 30' W. at 812 ft. South bank of the Verdigris River runs S. L. here I offset East 340 ft. [to clear the water and timber in the river as the line runs in the river]. I then ran North 0° 30' W. at 800 ft. the line was 100' East of River bank at 2640 ft. drove stake and offset back west 340 ft. to sec. line, here I drove a stake as a temporary 4 post on the east line of Sec. 2, T. 34 R. 16. From this stake I checked to the bank of the River south on the section line which was 590 ft. I also measured west on the 4 lines to the East bank of the river 440 ft. From this temporary 4 post on the East line of Sec. 2, T. 34 R. 16 I ran 70° 30' W. at 1150 ft. South bank of the Verdigris River at 1190' near water edge, measured River by wire 137 ft. wide. Drove stake and quit for the day, April 2, 1902 from the stake driven on north bank of Verdigris River on East line of Sec. 2, T. 34 R. 16 E. I ran 70° 30' W. at 1286 ft. came out 5 ft. west of the Government corner as N. E. corner of Sec. 2. I then went to the South West corner of Sec. 2, T. 34 R. 16 E. and measured north on Sec. line 440 ft. and set a stone, a lime stone 22" x 12" x 4", at a point 1317 1/4 ft. north on Sec. line from South West corner of Sec. 2. I set a line stone 48" x 9" x 4" marked x as the N. E. cor. of the S. L. & S. L. & Sec. 2, at a point 2634 1/2 ft. 70° 30' W. from South West corner of Sec. 2. I set a Flag stone 28" x 18" x 3" marked 4 for the 4 post on the west line of Sec. 2. Drove an Iron Rod beside it. Corrected the temporary 4 post on the south line of Sec. 2, 18 1/2 ft. south and 18 ft. east and set a Flag stone 30" x 12" x 4" marked 4 this stone is 2658 ft. east of the south west corner of sec. 2, T. 34 R. 16 E. At a point 1993 1/2 ft. East of the south west corner of sec. 2. I set a sand stone 24" x 9" x 8" marked x. From this last mentioned stone I ran North 0° 30' W. at 440 ft. set a Flag stone 30" x 8" x 4" marked x. This stone is 26 3/4 rods north of the south West corner of the East 1/2 of the south East 1/4 of the south west 1/4 of sec. 2, T. 34 R. 16 E. I put flags on the 4 posts and ran straight lines between and established the center of sec. 2. Thursday April 3, 1902 survey of Sec. 2, T. 34 R. 16 Continued. For the 4 post on the East line of Sec. 2 I set a lime stone 24" x 15" x 6" marked 7 this stone was corrected 2' 9" East of temporary corner. For the center of Sec. 2 I set a Flag stone 26" x 9" x 4" marked x, at a point midway between the 4 post on the south line of sec. 2 and the center I set a Flag stone 36" x 9" x 3" marked x as N. E. Cor. S. E. 1/4 S. L. & S. L. & Sec. 2. At a point midway between the center and the 4 post on the west line of sec. 2, T. 34 R. 16 I set a Flag stone 28" x 10" x 3 1/2" marked x as the S. E. cor. S. L. & S. L. & Sec. 2. At a point 1317 1/4 ft. 70° 30' west from 4 post on west line sec. 2, I set a sand stone 24" x 11" x 4 1/2" marked x. This completed the survey on April 3, 1902. Var 7° 55' E.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.  
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.)

Kansas, 189.....

You are hereby notified that, at ..... o'clock A. M., on the ..... day of ..... 189....., I will begin a survey on Section ..... Town ..... South, Range ..... in which you are interested, and shall continue the same from day to day until completed. Commencing at the ..... corner of said Section, I shall permanently establish

County Surveyor,  
County, State of Kansas.

midway between the 4 post on the south line of sec. 2 and the center I set a Flag stone 36" x 9" x 3" marked x as N. E. Cor. S. E. 1/4 S. L. & S. L. & Sec. 2. At a point midway between the center and the 4 post on the west line of sec. 2, T. 34 R. 16 I set a Flag stone 28" x 10" x 3 1/2" marked x as the S. E. cor. S. L. & S. L. & Sec. 2. At a point 1317 1/4 ft. 70° 30' west from 4 post on west line sec. 2, I set a sand stone 24" x 11" x 4 1/2" marked x. This completed the survey on April 3, 1902. Var 7° 55' E.

Dated at Independence Montgomery Co Kansas

April 26, 1902

L. L. Hibbard Co Surveyor.

|      |        |
|------|--------|
| 870  | 1993.5 |
| 312  | 664.5  |
| 147  | 2658.0 |
| 1329 |        |
| 2658 |        |