

Survey No. Section 5 Town 35 South Range 17
Survey No. Section 14 Town 34 South Range 16

This is to certify that I, S. L. Hibbard, County Surveyor of Montgomery County Kansas, was ordered by Att. M. Koyl to survey & subdivide Section 4, Township 34 R. 16 East. On the 12th day of April 1902 the following named parties were notified that a survey of the above named Section would be made, the survey to begin on April 22nd 1902.

S. L. Stiles, Doc, Van Meter, apt: W. B. Goddard: W. B. Dana: Burr Gates: A. B. Graham: Geo M Smith: James W. Engles: Joseph Smith: A. J. Connelly: J. L. Dewlen: A. P. Groten: Silas Walvert: E. J. Meares, apt: Geo. Foster: Matt Griffin: Art M. Koyl: Geo T. Guernsey: James Bremerman: O. Austin and Washington Brittriker was present and an owner of Land adjoining Sec. 4, T. 34, R. 16. On April 22nd 1902 I began the survey J. M. Goddard and D. F. Blue were selected as chain carriers and were duly sworn. I went to the north west corner of Sec 4, T. 34, R. 16 E. I found a stone the section corner. I ran S 0° 45' E, at 1359 ft. I found a stone in center of Road as S. W. corner Lot 4, T. 34, R. 16 E. at 2052 ft. north edge bridge at 2679 ft. drove stake as temporary 1/4 post on west line Sec. 4. From this temporary 1/4 post on west line Sec 4, I ran S 0° 45' E. at 2640 ft. drove stake as temporary S. W. Cor. sec 4 - P. M. Apr 22nd 1902. From temporary S. W. Cor sec 4, T. 34, R. 16 E. I ran N. 89° 30' E, at 1680 ft. creek at 2623 ft. temporary 1/4 post on South line sec 4. From temporary 1/4 post on South line sec 4, I ran N. 89° 30' E. at 312 ft. creek or draw at 940 ft. creek, at 1311 ft. stake, at 2611 ft. I found part of the old Government corner stone. From this south East corner of Sec 4, I ran north 0° 30' W. at 1320 ft. drove stake at 1710 ft. creek. From this drove stake at 1710 ft. I ran N. Branch Foster creek, at 2050 ft. I ran at 2633 ft. a stone marked 49 corner or 1/4 post on East line sec 4. From this stone I ran N 0° 30' W. at 1320 ft. drove stake at 2661 ft. a stone the north east corner Sec. 4-34-16 quit for the day - Apr. 23, 1902 to locate the South west corner of Sec 4-34-16. I went to the South west corner of Sec 9, T. 34, R. 16 one mile and measured north on the section line between section 8 & 9 at 5280 ft. came out 4 feet north of temporary S. W. corner of sec 4. I divided 1/2 distance and put temporary cor. 2 ft north. I then went to the south west corner of Sec 5, T. 34, R. 16 E. and measured East, at 5280 ft. Came out 6 ft west of temporary S. W. Cor of sec 4, as the South line of Sec 4 was short I set the corner at the end of the last measurement, here I set a line stone 25" x 12" x 10" marked IIII. for the corner to sec 4-5, 8 & 9. At a point 2640 ft N. 0° 30' W. from S. W. corner Sec 4, I set a line stone 28" x 12" x 10" marked 4 for the 1/4 post on west line sec. 4, at a point 1320 ft. north 0° 30' W. from the 1/4 post on the west line of Sec 4 I set a line stone 30" x 15" x 10" marked X as S. W. corner of Lot 4, of Sec 4-34-16. At a point 2620 ft. N. 89° 45' E. from south west corner of sec 4, I set a line stone 25" x 8" x 7" marked 7 for the 1/4 post on South line of sec 4. At a point 1310 ft east of 1/4 post on South line sec 4, I set a line stone 20" x 12" x 8" marked 4, as N. W. Cor. N. E. 1/4, N. E. 1/4 Sec 9-34-16. At the South East corner of Sec 4, I set a line stone 24" x 9" x 6" marked IIII I put the parts of the old government stone which was broken beside the stone planted, as S. E. corner of Sec 4. At a point 2634 ft north and on the East line of sec. 4 I set a line stone 24" x 9" x 6" marked 4 for the 1/4 post on East line sec 4 put the old Government stone beside it at a point 1327 ft. north and on the East line sec 4 I set a line stone 24" x 8" x 7" marked X as the S. E. corner of Lot 1, Sec. 4. I found a small sand stone the original corner, I set this line stone in place of it. At a point 1316 1/2 ft north on Sec line from S. E. corner of Sec 4, I set a triangular stone 10" x 12" x 12" x 12" marked X as the South East corner of the N. E. 1/4 of the South East quarter of Sec 4-34-16. Thursday Apr. 1902. From the 1/4 post on the East line of Sec. 4-34-16 I ran East on Random line at 680 ft. draw at 2625 ft temporary center Sec 4. From this stake temporary center sec 4, I ran East on Random line at 980 ft. deep draw at 1316 ft stake at 2635 ft. came out 3 1/2 ft. South of the 1/4 post on the east line before correction. From 680 ft. 1/4 line, I ran north at 1320 ft. stake temporary S. E. cor. Lot 3, sec 4, at 2672 ft. 1/4 post on north line sec 4, corrected center 21 inches north of intersection of 1/4 lines and set a line stone 26" x 12" x 6" marked XX as center Sec 4. At a point 1315 ft east on 1/4 line from center Sec. 4 I set a line stone 26" x 10" x 2 1/2" as S. W. cor. S. E. 1/4 N. E. 1/4 sec. 4. At a point 1316 ft. on the 1/4 line north of the 1/4 post on the south line sec 4, I set a line stone 18" x 10" x 10" marked X as N. W. cor. S. E. 1/4 Sec 4. At a point 1320 ft. north of the center Sec 4 on 1/4 line I set a line stone 24" x 14" x 4" marked X as S. E. cor Lot 3, sec 4-34-16. Where stones were placed in place of old stone because they were too small & Parties interested require large stones. I have completed the survey. Var 7° 55' E.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.)

_____, Kansas, _____, 189____.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

_____, County Surveyor,
_____, County, State of Kansas.

line of sec 4. From the 1/4 post on the south line of sec. 4, I ran north at 2630' E. & N. 1/4 line before correction. From 680 ft. 1/4 line, I ran north at 1320' stake temporary S. E. cor. Lot 3, sec 4, at 2672 ft. 1/4 post on north line sec 4, corrected center 21 inches north of intersection of 1/4 lines and set a line stone 26" x 12" x 6" marked XX as center Sec 4. At a point 1315 ft east on 1/4 line from center Sec. 4 I set a line stone 26" x 10" x 2 1/2" as S. W. cor. S. E. 1/4 N. E. 1/4 sec. 4. At a point 1316 ft. on the 1/4 line north of the 1/4 post on the south line sec 4, I set a line stone 18" x 10" x 10" marked X as N. W. cor. S. E. 1/4 Sec 4. At a point 1320 ft. north of the center Sec 4 on 1/4 line I set a line stone 24" x 14" x 4" marked X as S. E. cor Lot 3, sec 4-34-16. Where stones were placed in place of old stone because they were too small & Parties interested require large stones. I have completed the survey. Var 7° 55' E.

Dated at Independence Montgomery Co Kansas this 3 day of May 1902.
S. L. Hibbard