

This is to certify that S. D. Hibbard County Surveyor of Montgomery County Kansas was ordered by T. F. Burke to survey and subdivide section 29, township 31, Range 15, East 15. On April 21, 1902 the following named persons were notified that a survey of the above named section would be made (also of a survey of Sec. 28, 32-15) On April 29, 1902 Jos Chandler, Rosella Lattin, T. F. Burke, Chas. F. McElary, L. Harmon, H. H. Coleman, P. D. Swartzel, A. J. H. D. Richcreek, R. M. Richcreek, G. J. Lumsy, A. D. Slocum, A. J. Goodell Foster, Clara Richardson, S. D. Perkins, Agust Schicke, Katherine Schicke, Mary J. Gray, H. H. Cox, Andrew W. Griffin, R. S. Parkhurst, R. S. Heady, A. J. Harriet A. Devore, G. B. Caldwell. On April 29, 1902 I began the survey, H. B. Newmaster and T. M. Burke were selected as chainmen. I went to the south east corner of sec 29, T. 31 R. 15 E. I found the corner standing a stone bearing the marks of the section corner. I ran north at 1320' drove stake at 1980' ft. drove stake, at 2640' drove stake as temporary 4 post on east line of sec. 29. From this temporary 4 post I ran north at 1980' ft. drove stake at 2640' ft. drove stake as temporary North East corner of sec 29, T. 31 R. 15 E. From this temporary N.E. corner of sec 29 I ran west at 2640' ft. drove stake as temporary 4 post on the north line of sec 29. I quit for dinner, P. M. From the temporary 4 post on the north line sec 29, I ran west at 1320' ft. drove stake at 2640' ft. drove stake as temporary N. W. corner of sec. 29, I then went west to a stone the 4 post on north line of section 30, T. 31 R. 15 E. and Ran East at 2640' ft. drove stake which was 4 ft. west of the stake as temporary N. W. corner of sec. 29. Corrected temporary N. W. corner 2 ft. west and established this point as true cor. to sections, 29, 30, 19 and 20. From this true corner, I ran south between sections 29 & 30 at 2640' ft. drove stake as temporary 4 post on West line of sec. 29. From this temporary 4 post on the west line of sec 29, I ran south, 600 ft. ravine (550 ft. across) At 1071 ft. top of bluff 30 ft. high at 1260' creek at 1475' top of bluff, at 2400' ft. top bluff at 2653' ft. Came out 9 ft. west of the Government corner south west corner of sec 29. Correction for 4 post on West line of sec. 29. would be 6 1/2 ft. south 4 1/2 ft. East of temporary 4 post. From the Government stone the south West corner of sec. 29. I ran East at 150 ft. top bluff at 600 ft. Edge of Draw at 800 ft. East side Draw at 2640' ft. a stone the 4 post on south line of sec. 29. From this 4 post on the south line of sec 29, I ran east at 1320' ft. drove stake, at 2646 1/2 ft. South East corner of section 29. I quit for the day, Apr. 30, 1902. Survey of Sec 29, T. 31 R. 15 E. continued. At the north west corner of sec. 29 I set a lime stone 26" x 15" x 5" marked 1111. As the corner to sections 19, 20, 30 & 29. At a point 2627 ft. south of the north West corner of sec. 29, I set a lime stone 24" x 12" x 6" marked 4 for the 4 post on West line sec 29. Corrected temporary north East corner of sec. 29. One foot west and set a lime stone 22" x 8" x 8" as corner to sections 20, 21, 28 & 29. This stone I marked 1111. At a point 2641 ft. west of the north east corner of sec 29 I set a lime stone circular in form 18 inches in diameter 4 1/2 inches in thickness marked 4 for the 4 post on North line of sec 29. At a point 1320 1/2 ft. west of the 4 post on the north line of sec 29, I set a lime stone 22" x 15" x 4" marked X as the N. W. cor. 6 1/2 N. W. 4 sec 29. At a point 1320 ft. north of the south East corner of sec 29, I set a lime stone 24" x 14" x 4" marked X as the N. E. corner of the S. E. 1/4 of the south East 4 sec. 29. At a point 1980 ft. north of the south East corner of sec. 29 I set a lime stone 24" x 11" x 5" as the N. W. cor. of the S. E. 1/4 of the N. W. 4 of the South west 4 of sec 28, T. 31 R. 15 E. At a point 2640 ft. north of the South East corner of sec 29. I set a lime stone 22" x 14" x 6" marked 4 for the 4 post on the East line of sec. 29. At a point 660 ft. south of the north East corner of sec. 29, I set a lime stone 20" x 9" x 5" marked X as the south west corner of the N. 1/2 of the N. 1/2 of sec 28, T. 31 R. 15 E. I then put flags on the 4 posts and ran straight lines between at the intersection of the 4 lines, I set a lime stone 22" x 10" x 8" marked X as the

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

M

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

center corner of sec 29. Put glass around the center corner as witness to the corner. At a point midway between the center of section 29 and the 4 post on the West line I set a lime stone 18" x 16" x 3" marked X as the south west corner of the East 1/2 of the North West 1/4 of sec 29. At a point midway between the 4 post on the South line of sec 29 and the South East corner I set a lime stone 18" x 14" x 3" marked X as the South West corner of the South E. 1/4 of the S. E. 1/4 of sec 29, T. 31 R. 15 E. At a point midway between the center of sec 29 and the 4 post on the East line of sec. 29, I set a lime stone 24" x 12" x 4" marked X as the N. W. corner of the N. E. 1/4 of the S. E. 1/4 sec 29. I also set a lime stone 1320 ft. south of the last named stone, 18" x 12" x 4" marked X as the S. W. cor. N. E. 1/4 S. E. 1/4 sec 29. This completed the survey of sec 29, T. 31 R. 15 E.

Var 7° 55' E.

Dated at Independence Montgomery County Kansas. May 16, 1902.

S. D. Hibbard, County Surveyor