

Survey No.

Section

5

120

Survey No.

Section

28

Town

31

South, Range

15.

Geo. W. Crane &amp; Co., Topeka, Kas.

This is to certify that S. D. Hibbard County Surveyor of Montgomery County, Kansas, was ordered by T. F. Burke to survey and subdivide Sections 28 & 29 Township 31 Range 15, East. On April 21, 1902. The following named parties were notified that a survey of the above named sections would be made. The survey to begin on April 29, 1902. Joe Chandler, Rosella M. Lattin, T. F. Burke, J. Harmon, H. H. Coleman, P. D. Swatgel, A. J. H. Richerick, Robert M. Richerick, E. T. Guernsey, A. D. Locum, A. J. Goodell Foster, Clara Richardson, S. D. Perkins, August Schicke, Katherine Schicke, Mary T. Gray, H. H. Cox, Andrew N. Griffin, R. D. Parkherst, R. D. Steady, A. J. Harriet A. Devore, E. C. Baldwin. As Section 29, T. 31, R. 15, was surveyed, first the survey was continued on Dec 28, on May 1st, 1902. Henry Newmaster and T. M. Burkewere chosen as chainmen and Jolly as Flagman who were duly sworn. From the South west corner of Section 28, T. 31, R. 15, E. drew N. 89° 30' E. at 950 ft. top of bluff at 1600 ft. break or draw. At 2640 ft. drove stake as temporary 1/4 post on south line of Dec 28, at 2960' drove stake. From this stake drew N. 89° 30' E. at 1340 ft. center north and south Road drove stake as temporary S. E. Corner to Dec 28. From this temporary South East corner of sec. 28, drew north at 2640 ft. a stone the 1/4 post on the East line of Dec 28. From this temporary South East corner of sec. 28, drew N. 40° E. at 2645 ft. drove stake as temporary North East Corner of Dec. 28. Duit for dinner. From this temporary N. E. Corner of sec. 28, drew S. 89° 15' W. at 1320 ft. made mark on plank of bridge for temporary N. E. corner of N. E. 1/4 Sec 28. At 2640 ft. drove stake as temporary 1/4 post on North line of sec. 28. From this temporary 1/4 post on the north line of sec. 28, drew S. 89° 15' W. at 2622 ft. came out at the Section corner, the north west corner Dec 28. Correction for temporary 1/4 post on north line of Dec 28 would be 9 feet East here we drove a stake as true point for 1/4 post on north line of Dec. 28, T. 31, R. 15, E. From the 1/4 post a stone on the west line of Dec 28, drew N. 89° 15' E. at 1335 ft. top of bluff, at 1500 ft. center Ravine at 1670 ft. top east side Ravine bluff, at 2265 ft. top bluff of second Ravine, 2435' top bluff east side of the Ravine at 2640 ft. drove stake as temporary center of Dec 28. From this temporary center of Dec 28, T. 31, R. 15, E. drew N. 89° 15' E. at 1280' top of bluff at 1320' drove stake, at 2640 ft. came out 4 1/2 ft. South of the 1/4 post on the East line of Dec 28. Correction for center of Dec 28 would be 2 1/4 ft. North. From the corrected temporary 1/4 post on the South line of Dec. 28. (which was 5 ft. 10 ft. East of center of Dec 28) drew N. 1° W. at 1320 ft. drove stake at 1980 ft. drove stake as corner to the Griffin tract 2640' came out 3 ft. East of corrected 1/4 post. quit for the day. May 2-1902 Survey of Dec 28 continued. at the N. E. Corner of Dec 28, set a line stone 26" x 12" x 8" marked IIII for corners to sections 27, 28, 29 and 30. From the temporary South east corner of Dec 28, set a line stone 24" x 17" x 6" marked IIII for corners to sections 27, 28, 33 and 34. Corrected temporary 1/4 post on the South line Dec 28. drew N. 1° W. at 1320 ft. drove stake at 1980 ft. drove stake as corner to the Griffin tract 2640' came out 3 ft. East of corrected 1/4 post. quit for the day. May 2-1902 Survey of Dec 28 continued. at the N. E. Corner of Dec 28, set a line stone 26" x 12" x 8" marked X as the S. E. corner of the N. E. 1/4 of the South East 1/4 of sec. 28. T. 31, R. 15, E. Corrected temporary 1/4 post on north line of sec. 28, 9 feet East of center of Dec 28. set a line stone 24" x 12" x 6" marked 7 for the 1/4 post on the North line of Dec 28. At the center of Section 28, set a line stone 28" x 16" x 7" marked XX as the center corner. At a point 660 ft. South on the 1/4 line from the center of Dec 28, set a line stone 34" x 20" x 8" marked X as the South east corner of the North 1/2 of the North 1/2 of the S. E. 1/4 of Dec 28. At a point on the 1/4 line midway between the center and the 1/4 post on the East line of Dec 28, set a line stone 27" x 10" x 4" marked X as the North west corner of the E. 1/2 of the S. E. 1/4 of Dec 28. At a point midway between the center and the 1/4 post on the north line of sec 28, set a line stone 28" x 16" x 8" marked X as the S. W. cor. of the N. E. 1/4 of the N. E. 1/4 Dec 28. T. 31, R. 15, E. At a point 660 ft. North on the 1/4 line from this last named cor. set a line stone 25" x 14" x 6" marked X as the S. E. cor. N. 1/2, N. 1/2, N. E. 1/4 Dec 28.

## NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane &amp; Co., Printers and Binders, Topeka, Kas.

(Copyright, 1894, by B. A. Bailey, Topeka, Kansas.)

Blank Books and Legal Blanks of Every Description.

Kansas, 189.....

M

You are hereby notified that, at ..... o'clock A. M., on the ..... day of ..... 189....., I will begin a survey on Section ..... Town ..... South, Range ..... in which you are interested, and shall continue the same from day to day until completed. Commencing at the ..... corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

North on the 1/4 line from this last named cor. set a line stone 25" x 14" x 6" marked X as the S. E. cor. N. 1/2, N. 1/2, N. E. 1/4 Dec 28.  
This completed the survey on May 3-1902

Car 7° 55' E. Dated at Independence Montgomery Co, Kansas. May 31, 1902.

S. D. Hibbard Co Surveyor