

This is to certify that J. S. Hibbard County Surveyor of Montgomery County, Kansas was ordered by A. P. McBride to Survey & Subdivide Section Three 3 Township 32 Range 15 East. On April 7th 1902 the following named parties were notified that a Survey of the above named section would be made. The Survey to begin on April 15th 1902. On account of a Heavy Rain the survey was postponed. On April 24th 1902 the following named parties were notified that a Survey of the above named section would be made the Survey to begin May 6th 1902.

J. J. Jones, Mary Vanclaver, H. B. Bayless, S. T. Guernsey, Daniel Ringle, Ben Murphy, A. D. Humphrey, A. P. McBride, Henry Hanson, Geo Hewett, Jacob Batches, S. D. Staley, Helen Beatche, S. D. Parks, Annie Cleavenger, Ellie Nealt, James Beatche.

On May 6th 1902 I began the Survey S. D. Staley and A. Smart were selected as chainmen who were duly sworn.

I went to the South east corner of section 3-7-32-R-15-E. a stone^{2nd} Ran South 89° 45' W. at 640 ft. drove stake at 1320' drove stake at 1580 ft. a draw at 2648 ft. drove stake as temporary 1/4 post on the South line of sec. 3. From this stake as temporary 1/4 post on South line of sec. 3. I ran due west at 2639 ft. a stone the South west corner of sec. 3. Correction of temporary 1/4 post on South line sec. 3. would be 4 1/2 ft. East here drove stake as true point for the 1/4 post on the South line of sec. 3. From this stake ran north 0° 45' W. at 480 ft. creek. at 580 ft. creek at 600 ft. creek at 2310 ft. drove stake as temporary N. E. corner of McBride tract offset west 6 ft. on account of ledge. At 2640 ft. drove stake 6 ft. east as temporary center cor. to sec. 3. From this temporary center corner of section 3-7-32-R-15-E. Ran 70° 45' West at 2697 1/2 feet I came out 27 feet west of the 1/4 post on north line sec. 3. Correction for center corners would be for north & south line 13 1/2 ft. east. I put flags on the 1/4 posts on the east & west lines and Ran a straight line between by adjusting my transit between the flags at the intersection of the 1/4 lines which was 8 ft. north of temporary center on north^{2nd} and South 1/4 line. Here I established true point for center corners. In digging down we found the center corners stone well worn. I set a sand stone 18" x 10" x 7" marked X and put the old stone beside it for the center of sec. 3-7-32-15-E. And quit for the day. May 7th 1902 Survey of sec. 3 continued. From the 1/4 post a stone on the east line of sec. 3. I measured west on the 1/4 line at 660 ft. drove stake as center of north^{2nd} and South street in Radical City at 1320 drove stake. At a point 495 ft. west on the 1/4 line from the last named stake I drove a stake as temporary S. W. corner to Hanson tract at 1320 ft. center sec 3 I went to the North east corner of sec. 3-7-32-15-E. I ran west at 1320 ft. drove stake, I measured 495 ft. west from this stake I drove stake at N. E. corner of Hanson tract at 1320 ft. the 1/4 post on north line of sec. 3. At a point on South line of sec. 3. 660 ft. west of the South east corner. I set a sand stone 24" x 16" x 5" marked X, as the S. W. corner, S. 1/2, S. E. 1/4 Sec. 3. At a point 40 Rods East of the South east corner of sec. 3. I set a sand stone on South line of sec. 2- 24" x 18" x 5" marked X. At a point 60 Rods north of the South east corner of sec. 3. I set a sand stone 26" x 18" x 5" marked X, as the N. E. corner of 15 acre tract. At a point 330 ft. north of last named cor. on East line sec. 3. I set a sand stone 18" x 12" x 5" marked X. At a point 60 rods north of last named corner I set a sand stone 22" x 16" x 4" marked X. this stone is in center East^{2nd} and west Road at 20 Rods north of this stone 1/4 post on

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Baillet, Topeka, Kansas.]

_____, Kansas, _____, 189____.

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
_____, County, State of Kansas.

of sec. 3. T. 32 R. 15-E. I set a sand stone 24" x 15" x 9" marked X as the North west corner of lot 1, sec. 3. At a point 495 ft. west of this last named stone I set a sand stone 24" x 12" x 9" as the N. E. corner of the 30 acre tract. At a point 40 rods west on the 1/4 line from the 1/4 post on the east line of sec. 3. I set a sand stone 20" x 9" x 5" marked X in street of Radical City. At a point 40 Rods West & 60 Rods north of South East corner of sec. 3. I set a sand stone marked X, 24" x 12" x 4" as N. E. cor. Mary Vanclaver tract. At a point 40 Rods west^{2nd} & 80 Rods north of S. E. corner of sec. 3. I set a fine stone 26" x 12" x 5" marked X as N. E. cor. of near land. At a point 40 Rods west & 93 Rods north of S. E. cor. sec. 3. I set a sand stone 20" x 14" x 3" as S. W. corner of Shellenbeger tract at a point 12 rods north of last named corner I set a fine stone 22" x 14" x 3" marked X as N. E. cor. of Shellenbeger tract. Also set stone 14 Rods East of Shellenbeger N. E. & S. W. corner as N. E. & S. E. corner to his lot. At a point 46 1/2 ft. north of Shellenbeger's N. E. corner. I set a sand stone 14" x 10" x 8" as the corner of Batches tract. At a point 330 ft. South of N. E. corner N. E. 1/4 Sec. 3. I set a sand stone 28" x 10" x 5" marked X. At a point 46 1/2 ft. south of N. E. cor. N. E. 1/4 Sec. 3. I set a sand stone 18" x 9" x 9" marked X as S. W. cor. of a lot. At a point 94 ft & 8 in South of last named stone I set a sand stone 17" x 12" x 3" marked X, as S. W. corner of Staley tract. At a point 302 1/2 ft. South of last named cor. I set a sand stone 18" x 12" x 5" marked. At a point 101 ft. South of the last named cor. I set a sand stone 24" x 16" x 3" marked X as S. W. cor. of Batches tract. At a point 86 1/2 ft. north of last named cor. I set a sand stone 18" x 7" x 3" marked X Batches N. E. cor. At a point 2150 ft. North^{2nd} & 40 Rods west of S. E. cor. sec. 3. I set a sand stone 18" x 12" x 4" marked X as the corner between Cleavenger^{2nd} & Staley. I also set a sand stone 39 Rods & 3 ft East^{2nd} & 20 Rods & 4 1/2 ft. South of the North west corner of the North East 1/4 of the South East 1/4 of sec. 3 T. 32 R. 15-E. This stone is on the main street in Radical City but near the west side of the street. I also drove iron pins to the corners of the Batches tract, as follows: 93 R. 7 & 40 Rods N. from the South East corner sec. 3. Thence west 178 1/2 ft. thence north 24 1/2 ft. thence East 178 1/2 ft. Thence south on center street of Radical City 244 1/2 ft. to Beginning.

This completed the Survey of sec. 3- T. 32 R. 15-E. East.

K. S. C.

Dated at Independence Montgomery County Kansas June 5- 1902

J. S. Hibbard County Surveyor

322
662
60
644

825
1375
2640