

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that J. D. Hibbard County Surveyor of Montgomery County Kansas, was ordered by J. D. Etter to Survey and Subdivide section One (1) Township 32, Range 15 East. On April 28th 1902 The following named parties were notified that a survey of the above named section would be made the survey to begin on May 8th 1902. J. D. Griffith; William Jones; Sophia Festner; Francis D. Graham; R. L. Madden; J. H. Bates; Eli Alexander; Eugene Foster; D. T. Hitten; Laura Dunkin; Robert Daniel; L. H. Bowers; Samuel Etter; May E. Henderson; Matilda J. De Mott; William M. Jeter; Christian Bohre; D. P. Greer; Geo B Smith; William H. Roer; Fred Halber; On acct of an unfinished survey a mile west of sec 1 T. 32 R. 15 E. I adjourned the survey of sec 1, T. 32 R. 15 E. until May 9th 1902. On May 9th 1902 I began the survey - A. J. Litta and I Litta were selected as Chainmen and were duly sworn. I went to the South East corner of sec 1, T. 32 R. 15 E. We found a part of the sec corner with plain marks on it, the top had been broken off as it was in the public Road. Having thus determined the true point for the south East corner of sec 1, T. 32 R. 15 E. I ran north on the Range line at 1322 ft. I found a stone marked as South East Corner N 1/2 of the South East 1/4 of sec 1, at 2640 ft. drove stake as temporary 1/4 post on the East line of sec 1. From this temporary 1/4 post on the East line of sec 1, I ran north on the Range line at 1320 ft. drove stake at 2640 ft. drove stake as temporary North East Corner of sec 1. This distance north was determined by adjusting my transit on the East and West line, or Township line. Here I set a sand stone 31"x9"x5" marked IIII for corner to sec 1, 6, 31 & 36. From the North East corner of sec 1, T. 32 R. 15 E. I ran west at 2640 ft. drove stake as temporary 1/4 post on North line sec 1. From this temporary 1/4 post on North line sec 1, I ran west at 2645 ft. set a sand stone 16"x12"x10" marked IIII as the corner to sections 1, 2, 35 & 36. Quit for dinner. A. M. May 9th 1902, Survey of sec 1, T. 32 R. 15 continued. From the North West Corner sec 1, I ran south 0° 50' E at 1320 ft. drove stake at 2660 ft. drove stake as temporary 1/4 post on the South line of sec 1. From this stake temporary 1/4 post on West line sec 1, I ran south 0° 50' E at 1320 ft. drove stake at 2640 ft. stone South West Corner of sec 1. From South West corner sec 1, I ran East at 1325 ft. drove stake as temporary 1/4 post on South line sec 1. From the temporary 1/4 post on the South line sec 1, I ran East at 2652 ft. came out 6 1/4 ft. South of the corner stone. Correction for 1/4 post on South line of sec 1 would be 6 ft. East and 3 3/4 ft. north. Here I set a sand stone 36"x12"x6" marked 1/4 for 1/4 post on South line of sec 1. At a point 2640 ft. north on Sec line from the South West corner of sec 1, I set a sand stone 25"x12"x6" marked 1/4 for the 1/4 post on West line of sec 1. At a point 1325 ft. north of the 1/4 post on the West line of sec 1, I set a sand stone 18"x12"x6" marked X as the South West corner of Lot 4. At a point 2640 ft. north of the South East corner sec 1, I set a sand stone 30"x12"x8" marked 1/4 for the 1/4 post on the East line of sec 1, T. 32 R. 15 E. At a point 1320 ft. north of the 1/4 post on the East line of sec 1, I set a sand stone 24"x14"x7" marked X as the South East corner of Lot 1 of sec 1. Quit for the day May 10th 1902 Survey of sec 1, T. 32 R. 15 continued. I put flags on the 1/4 posts a gas pipe 40 ft high with flag on the South 1/4 post, Enable me to run a straight line between the 1/4 posts and at the intersection of the 1/4 lines, I set a sand stone 20"x12"x8" marked XX, as the center of sec 1. At a point 661 1/2 ft. East on the 1/4 line from the center of sec 1, I set a sand stone 30"x9"x8" marked X as the N. E. corner of the East 1/2 of the N. E. 1/4 of the South East 1/4 of sec 1. At a point 1320 ft. south of last named corner a sand stone 20"x10"x4" marked X, as the N. E. cor. E 1/2 of the South East 1/4 of the S. E. 1/4 sec 1. At a point midway between the center of sec 1 & the 1/4 post on the West line of sec 1, I set a sand stone 24"x14"x5" marked X as the North West corner of the N. E. 1/4 of the South West 1/4 of sec 1. At a point 1322 1/2 ft. north on 1/4 line from the center of sec 1, I set a sand stone 22"x6"x6" marked X as the South West

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

M

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

Corner Lot 2. of sec 1, T. 32 R. 15 E. this finished the survey.
Var 8' E.

Dated at Independence Montgomery Co. Kansas June 5th 1902
J. D. Hibbard. Co Surveyor