Survey No. ....., Section 5, Town 35 South, Range 17

Survey No. ....., Section 31, Town 33. South, Range 14.

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I S.L. Hibbard, County Surveyor of Montgomery County, Kansas was ordered by M.E. Kelso to survey and subdivide section 31, Township 33. R. 14. East. On May 12" 1902 the following named parties were notified that a survey of the above named section would be made the survey to begin on May 20" 1902, E.M. Needles: Geo P. Dalby: Frank Rabb: Goodell Foster: J.F. Morris: A.J. Sullivan: A. Mendenhall: L.H. Stull: M.E. Kelso: W.B. Jennings: C.A. Stull: J.H. Huston: Westerly Savings Bank: W.H. Allen: G.T. Guernsey: & Westerly Savings Bank - On May 20" 1902 I began the Survey. F.L. Paull and G.W. Tiley were selected as chainmen and were duly sworn From a stone the north East corner of Sec. 31-33-14. I ran S. 89° 45' West. At 435 ft. Creek, at 1463 ft. Creek, at 2640 ft drove stake temporary 1/4 post on north line of Sec 31. At. 2923 ft. Draw & Bridge at 3203 ft, came out 17 1/2 ft south of the Government Corner. I located the government corner by stumps of witness trees. We found the stone broken the top off but the bottom was still in the ground firmly bedded. This was the true point for the north, west corner of Sec 31. From this N.W. Corner of Sec. 31 I ran South on the Range line at 1320 ft drove stake at 2637 ft. came out 13 ft East of a stone marked 1/4 supposed to be Gov. stone. I was so located that if could not be found except by measurement as the ground was covered with stone. I continued South on the Random line from the point 13 ft. east of the 1/4 post. From this last mentioned point I ran south 1° East at 1320 ft. drove stake at 2641 ft. I came out 13 ft east of the Government stone which I found standing as the South west Corner of Sec 31, T 33 R 14 E. and quit for the day - May 21" 1902 Survey of Sec 31 T 33 R 14 E continued. From the South west corner of Sec 31. I ran N. 89° 30' E, at 260 ft west Bank of a Pond 6 feet South 100 ft. East 200' Thence offset back to line 100 ft. at 2745 ft. East from S.W. Cor. Sec. 31, I came out 2 ft north of a stone marked 1/4 this was a small sand stone and this point was in dispute but I located true point by witness tree stumps which we found and found the stone in the right place, but on top of the ground. From this true point for 1/4 post on south line of sec 31. I ran (N. 89° 30' E) at 1320 ft. stake at 2640 ft. Drove stake as temporary S.E. Cor, Sec 31. From this temporary S.E. Cor. of Sec 31, I ran N. 1° 30' W. at 1320 stake, at 2640 ft. drove stake as temporary 1/4 post on East line of Sec. 31. From this temporary 1/4 post on East line of sec 31. I ran N 1° 30' W. at 925 ft. Creek: at 2620 ft. Came out 10 ft East of N.E. Corner of Sec. 31. Correction for 1/4 post on East line would be 10 ft south and 5 ft west. Quit for the day - May 22" 1902, Survey of Sec. 31, Continued. At the north West Corner of Sec 31, Where the old part of the Government stone stood, I set a Lime stone 24" x 14" x 9" marked 1111 with a part of the old stone beside it, for the north west Corner of sec 31. I put flags on the N.E Cor & N.W. Cor. and adjusted my transit between. at a point 2640 ft. west on the Section line from the North East Corner of sec 31. I set a Lime stone 18" x 24" x 5" Marked 1/4 for the 1/4 post on the North line of sec 31. Quit for dinner P.M. I checked from a stone 80 rods south of the temporary S.E. Cor. of sec 31. and found the distance to be correct. I set a lime stone 24" x 10" x 2 1/2" marked 1111 for S.E. Cor of Sec 31. At a point 2630 ft N. 1° 35' W. from the South East Corner of Sec 31. I set a Lime stone 27" x 16" x 3" Marked 1/4 for the 1/4 post on East line of Sec 31. At a point 80 Rods west on the Section line, from the South East Corner of Sec 31, I set a Lime stone 28" x 16" x 6" marked X as the South west Corner of the East 1/2 of the South East 1/4 of Sec 31. At a point 2747 ft. East on Township line from the South west Corner of Sec. 31. I set in place of the Gov. stone a Lime stone 26" x 16" x 6" marked 1/4 for the 1/4 post on south line of Sec 31. This stone is located where the government put it but not according to the field notes by measurement. From the 1/4 post on south line of Sec. 31. I measured North on 1/4 line, 1320 ft. drove stake, at 2640 ft. Drove stake as temporary center of Sec. 31. and quit for the day -

NOTICE—Surveyor's Permanent Record, State of Kansas.

GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

....., Kansas, ... 189....

M.....

You are hereby notified that, at ..... o'clock A. M., on the ..... day of ....., 189....., I will begin a survey on Section ....., Town ..... South, Range ....., in which you are interested, and shall continue the same from day to day until completed. Commencing at the ..... corner of said Section, I shall permanently establish

.....

.....

.....

.....

..... County Surveyor,

..... County, State of Kansas.

May 23" 1902 Survey of Sec 31. Continued. At a point on the Range line 1318 1/2 ft. South of the north West corner of Sec 31. I set a sand stone 20" x 8" x 6" marked X as the South East Corner of the N.E. 1/4 of the N.E. 1/4 Sec 36. T. 33. R. 13. E. At a point 2637 ft. south and where the old Government Cor. stood I set a sand stone 24" x 16" x 6", marked 1/4 for the 1/4 post on the west line I put the old stone beside it. At a point 80 Rods south of the 1/4 post on the west line of Sec 31. I set a sand stone 25" x 14" x 6" marked X as the N.W. Cor, S 1/2, S.W. 1/4 Sec 31. From the 1/4 post on the West line of Sec 31. I ran S. 89° 30' E. at 2700 ft. drove stake temporary center sec 31. At a point 1316 1/2 ft. North of 1/4 post on South line sec 31. I set a sand stone 28" x 10" x 8" marked X as N.E. Cor. of the S 1/2 of the South west 1/4 of Sec 31 At the Intersection of the 1/4 lines I set a sand stone 24" x 9" x 7" marked XX as the center of sec 31. At a point midway between the center of Sec 31 & the 1/4 post on the east line of Sec 31. I set a sand stone 22" x 18" x 7" marked X as the N.E. corner of the N 1/2 of the south East 1/4 of Sec. 31, this completed the survey of section 31. T. 33. R. 14. E on May 23" 1902

Var. 7° 55' E.

Dated at Independence Montgomery County. June 16" 1902.

S.L. Hibbard County Surveyor.