

Survey No. _____, Section 29, Town 34 South, Range 15.

This is to certify that I, S. D. Hibbard County Surveyor of Montgomery Co. Kansas, was ordered by G. P. Wheeler to survey & subdivide sections 29, Township 34, Range 15 East. On July 29, 1902 the following named parties were notified that a survey of the above named sections would be made. The survey to begin on August 6, 1902. H. H. Roger: T. Hood: W. F. Dunbar: J. C. Hester: G. P. Wheeler: W. H. Tacker: J. W. Devel: S. D. Taylor: Samuel T. McBrown: W. H. Britten: C. Clark: W. T. Goe: L. Davis: H. Anderson. On August 6, 1902 I began the Survey George Hicks and A. J. Wheeler were selected as chainmen and F. M. Roger as Flagman who were duly sworn. Went to the South west corner of Section 29, T. 34, R. 15 E. A stone marked, I ran North 1° 15' West at 1320' drove nail at 1940 ft. Drove & bridge at 2600 ft. drove nail as temporary 1/4 post on West line of section 29. A Heavy Hedge run East. From this temporary 1/4 post on West line of Sec 29. I ran North 0° 45' minute West at 1320' drove nail at 2640 ft. drove stake as temporary N. E. corner of Sec 29. stopped for dinner. P. M. Aug 6, 1902. From the temporary North west corner of section 29-34-15 I ran due east at 1650 ft. drove stake as temporary corner to the 100 acre tract at 2640 ft. drove stake as temporary 1/4 post on the North line of section 29. From this temporary 1/4 post on the North line of Sec 29. I ran North 89° 15' East, at 2640 ft. drove stake as temporary North East corner of Sec 29. From this temporary N. E. corner of Sec 29. I ran South 1° 45' East, at 2640 ft. drove stake at the end of Hedge as temporary 1/4 post on the East line of Section 29. From this temporary 1/4 post on the East line of section 29. I ran South 0° 45' East, at 543 ft. the North end of an Iron bridge across Fawn Creek, at 1320 feet drove stake at 2603 ft. drove stake in center of the cross road as temporary South East corner of Section 29. From this temporary S. E. corner of Sec 29 I ran due West at 960 ft. East Bank of Fawn Creek at 1070 ft. West Bank of Creek at 2640 ft. drove stake as temporary 1/4 post on the South line of section 29. From this temporary 1/4 post I ran west at 2420 center public Road at 2632 ft. a stone the South West corner of section 29. Quit for the day - Aug 7, 1902, survey of Sec 29 continued. At a point 2611 ft. N. 1° 30' W from the south west corner of section 29, T. 34 R. 15 E. I set a lime stone 24" x 13" x 6" marked 1/4 for the 1/4 post on the West line of section 29. This stone is at the west end of a Heavy Hedge running East on the 1/4 line and was planted 30 years ago, when Government 1/4 post was standing, at a point 2640 ft North 1° W. from this 1/4 post I set a lime stone 18" x 15" x 7 1/2" marked 1111 for the corner to Sections 19, 20, 29 & 30. At a point 1650 ft. due east of the North west corner of Sec 29. I set a lime stone 22" x 12" x 6" marked X as the North East corner of a Hundred acre tract off the west side of the North west 1/4 of Sec 29. At 2640 ft. East of the North West corner of Sec 29. I set a lime stone 23" x 12" x 8" marked 1/4 for the 1/4 post on the north line of Sec 29. at a point 2640 feet N. 89° 15' East of this last named 1/4 post I set a lime stone 24" x 13" x 6" marked 1111. for the corner to Sections 20, 21, 28 & 29. At a point 2640 ft. South 1° 45' East from the North East corner of Sec 29. I set a lime stone 28" x 10" x 6" marked 1/4 for the 1/4 post on the east line of Sec 29. A Heavy Hedge runs west from this

NOTICE—Surveyor's Permanent Record, State of Kansas.

GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

., Kansas, 189

M

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section, Town South, Range, in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

also offset East 15 ft. from the $\frac{1}{4}$ post on the north & south $\frac{1}{4}$ line put flags at the points and ran a straight line between them at the intersection of said lines I drove a stake and measured west on the $\frac{1}{4}$ line 15 feet from this point I ran South 15 feet and set a line stone 18" x 12" x 6" marked XX as the center corner of Sec 29. I measured the distance from the $\frac{1}{4}$ post to the center of from the South line and found it to be 2603 ft. at a point on the $\frac{1}{4}$ line 1301 $\frac{1}{2}$ ft. south from the center of Sec 29. I set a line stone 26" x 9" x 6" marked X as the N.W. corner of the South $\frac{1}{2}$ of the South East $\frac{1}{4}$ of Sec 29. At a point 1650 ft. East on the $\frac{1}{4}$ line from the $\frac{1}{4}$ post on the west line of Sec 29. I set a line stone 22" x 10" x 4" marked X as the South East Corner of the 100 acre tract off the west side of the North West $\frac{1}{4}$ of Sec 29. Township 34 R. 15 E. I find the lines irregular but the stones are planted about where the Government put them.

This completed the Survey of section 29-34-15 on August 8-1902 Independence Montgomery Co. Aug. 9-1902

Var 7° 55' E.

Var 7'-5-5'-E.

S. L. Hubbard, County Surveyor.