

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that S. L. Hibbard County Surveyor of Montgomery County Kansas was ordered by D. S. Hight to survey^{and} subdivide section two township thirty one 31, Range 13 East. On September 13th 1902 the following named parties were notified that a survey of the above named section would be made on Sept. 23rd 1902. Survey to begin at 9 o'clock A. M. E. D. Hight, E. J. Means Aft. Joe Dexter, J. B. Pickler, D. S. Hight, John Marlow, Albert Hight, L. N. Dunn, William Oliver, Am. Frost Aft. I also notified the surveyor of Elk County J. F. Chapman to notify the parties adjoining Montgomery Co. line west of sec 2 - T. 31, R. 13 E. On September 23, 1902. It was raining and continued to do so. The parties were notified that a survey of sec 2-31-13 would be made the survey to begin at 9 o'clock on Oct 1st 1902. On October 1st 1902, I met the deputy county surveyor of Elk Co. G. F. Osborn, at the north west corner of sec 2, T. 31, R. 13 E. we found the north west corner of sec 2 standing. From this corner we ran S. 0° 30' E. on a random line between sec 2 & 3 at 1332 ft. drove a stake as temporary 4 post on west line of section 2-31-13. From this temporary south west corner of lot 4 of sec 2, at 2652 ft. drove a stake as temporary 4 post on west line of section 2-31-13. From this temporary 4 post on the west line of sec 2, I ran south 0° 30' E. at 2675 feet, drove a stake as a temporary south west corner of section 2-31-13. As we found no corner here, we went to the 4 post on the south line of sec 1, T. 31, R. 13 E. and ran west on the section line G. F. Osborn and A. H. Craig were chainmen^{and} were duly sworn at 2640 ft. I drove a stake as a temporary south east corner of section two 2 township thirty one 31 Range Thirteen 13 East. From this temporary south east corner of sec 2, I ran west S. 89° 24' at 1960 ft. A creek at 2640 ft. drove a stake as temporary 4 post on the south line of section 2, T. 31, R. 13 E. From this temporary 4 post, a stake I ran S. 89° 24' at 1320 ft. drove a stake as temporary S. W. Cor. Sec 2 - T. 31, R. 13 E. This stake was on the line of wire fence supposed to be on the line between Montgomery and Elk Counties. To ascertain the exact location of the true point for the south west corner of sec 2 I went a mile west to the south west corner of section 3. I found the corner standing^{and} marked. I ran east from this stone at 79° 56'. The distance given by the Government field notes I drove a stake this stake is 20 feet west of the run made from the 4 post on the south line of sec 1, west as the distance given by the Gov. field notes for the south line of sec 2 is 79° 15' and as section 3 was full^{and} 20 ft. over distance given by Gov. field notes. I located the south west corner of sec 2, giving the south line 5252 ft. It was raining at this time^{and} rained for 3 days. I adjourned the survey until October 8th 1902. On October 8th 1902 I continued the survey of section two 2 township 31 Range Thirteen 13 East. J. R. Craig^{and} S. M. Kelek were selected as chainmen^{and} were duly sworn. At a point 2647 ft. west of the 4 post on the south line of section 1, Township 31 Range 13 East. I set a sand stone 20" x 15" x 8" marked 1111 for the corners to sections 12, 11 & 12. From the South East corner of section two 2 T. 31, R. 13 E. I ran north 0° 55' west to a flag on the north east corner of sec 2 which was standing at 2640 ft. drove stake as temporary 4 post on East line of sec 2. From this temporary 4 post on the East line of sec 2, I ran N. 0° 55' West at 2700 feet north east corner Sec 2 - 31 - 13 on County line to Equalize the distance as the Government field notes, the line between sections 14 & 2 as 5292 ft. I divided the excess which was 48 ft. at a point 2664 ft. north of the South East corner of sec 2. I set a sand stone 32" x 10" x 6" marked 4 for the 4 post on the east line of sec 2. At a point 1332 feet north 0° 55' of the 4 post on the East line of sec 2. I set a sand stone 21" x 10" x 5" marked X as the North East Corner of the S. E. 1/4 of the N. E. 1/4 of sec 2. At a point 5252 ft. west from S. E. corner of sec 2 I set a sand stone 20" x 12" x 8" marked 1111 for corners to sec 2, 3, 10 & 11. At a point 1313 ft. East on Sec. line from the South west corner of sec 2. I set a sand stone 26" x 12" x 4" marked X as the South East corner of the S. W. 1/4 of the S. E. 1/4 of sec 2. At a point 2626 ft. East on the section line from the South West Corner of sec 2. I set a sand stone 30" x 12" x 5" marked 4 for the 4 post on the south line of sec 2. From this 4 post on the south line of sec 2, I ran N. 1° 10' at 100' draw at 1330 feet, drove stake^{and} quit for the day Oct 9th 1902, survey of sec 2-31-13 continued. From temporary stake driven as temporary N. E. Cor. of S. E. 1/4 of the N. E. 1/4 of sec 2-31-13, I ran N. 1° 10' at 800' draw on Ravine at 1330 ft. came out 8 feet east of the 4 post stone on the north line of sec 2-31-13. I went to the South West corner of sec 2, T. 31, R. 13 E. I ran a random line N. 1° 30' W. I came out 36 3/4 ft. west of the N. W. corner of sec 2 to correct my line I ran S. 1° 10' E. at 1342 ft. S. 1° 10' E. I set a sand stone 18" x 10" x 6" marked X as S. W. Corner lot 4, sec. 2, T. 31, R. 13 E. on County line. At a point 2672 ft. S. 1° 10' E. from the North West Corner of sec 2, I set a sand stone 26" x 13" x 9" marked 4 for the 4 post on the West line of sec 2, at 5332 ft. Southwest corner of sec 2-31-13. I put flags on the East West 4 post of sec 2, at the intersection of the 4 lines the north & south temp center to be corrected 4 ft. west. Here I set a sand stone 54" x 11" x 11" marked XX, as the center corner of sec 2-31-13. At a point midway between the center of sec 2^{and} the 4 post on the East line of sec 2 I set a sand stone 18" x 12" x 9" marked X, as the South West corner of the South E. 1/4 of the N. E. 1/4 of sec 2. At a point 1332 ft. north of the center of sec 2 on the 4 line I set a sand stone 26" x 12" x 9" marked X as the N. W. Corner S. W. 1/4 of sec 2-31-13. This stone is 1342 feet south of the 4 post on the north line of sec 2. From this stone the N. W. Corner of the South West 1/4 of the N. E. 1/4 of sec 2. I ran East at 2640 ft. stone at a point midway between these two stones I set a sand stone 20" x 9" x 5" marked X as the north west corner of the Southeast 1/4 of the N. E. 1/4 of sec 2-31-13. At a point 1316 ft. East on the 4 line from the 4 post on the west line of sec 2, I set a sand stone 18" x 10" x 6" marked X as the S. W. Corner of the S. E. 1/4 of the N. E. 1/4 of sec 2. I set a sand stone on the County line 1320' west of the 4 post on the north line sec 2-31-13. I also set a sand stone 1330 ft. North of the S. W. Cor. S. E. 1/4 N. E. 1/4 sec 2. As the N. W. Corner of the S. E. 1/4 of the N. W. 1/4 of sec 2-31-13 This stone is 20" x 9" x 7" marked X. This completed the survey on the 9th day of October 1902.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. CRANE & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.
(Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.)

_____ Kansas, _____ 189____.

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
_____, County, State of Kansas.

Var 7° 55' E. Dated at Independence Montgomery Co. Kansas this 24th day of October 1902
S. L. Hibbard
Co. Surveyor