Survey No. ....., Section 35, Town 33, South, Range 15.

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I S. L. Hibbard County Surveyor of Montgomery County Kansas was ordered by A. H. Shulthis & others to survey and subdivided section Thirty five (35) Township Thirty Three (33) Range Fifteen (15) East. On October 11th 1902. This notice was sent to the following named Parties "You are hereby notified that I will be at the Residence of G. H. Ross on the 21st day of October 1902, at 9 o'clock A. M. for the purpose of surveying the Lands of A. H. Shulthis and others lying in section 35 Township 32. Range 15. You will therefore be prepared to pay your proportionate part of the Expence of said Survey, in accordance with sections 7 & 11 Chapter 89 of the laws of 1891. Dated at Independence Kansas this 11th day of October 1902 S. L. Hibbard Surveyor of Montgomery Co." A. G. Empfield: H. H. Whitesitt: Philip Attendorf: J. H. Bear: Elizabeth Gillman: J. E. Mensch: John Loyd: William Goodwin: A. L. Kaid: A. M. West: U. E. Smith: A. E. Carpenter: Chas Kinegart: A. R. Waterman: Geo H. Ross: Gilbert Smythe: G. T. Guernsey: A. H. Shulthis: A. T. Ward: J. H. Elam: On October 21st 1902, I began the survey of Sec 35. T 33 R. 15. E. Nic Altendorf and John Altendorf were chosen as chainmen & G. H. Ross as Flagman, who were duly sworn: I then went to the South East Corner of Section 35. T 33. R. 15. I found the Corner standing (a stone) From this south East Corner I ran West at 1320 ft. drove stake as temporary 1/4 post at 1480 ft ran at 2640 ft I drove a stake: as temporary 1/4 post on South line of Sec. 35. From this temporary 1/4 post on the South line of Sec. 35 I ran West at 1320 ft drove stake as temporary Cor S.E. Cor, S. W 1/4 of S W 1/4 of Sec 35 at 2640 ft. I drove stake as temporary south West Corner of sec 35; to be sure that I was not to far West, I went to the South West Corner of Section 34. T 33. R. 15. and ran East at 2280 ft. the stake driven as temporary South West Corner of Sec 35. From this temporary South West Corner of Sec 35. I ran north at 1320 ft. drove stake as temporary N. W. Corner to S. W 1/4 S W 1/4 Sec 35, at 2640 ft, drove stake as temporary 1/4 post on the West line of Section 35. From this temporary 1/4 post on the west line of sec 35 I ran North at 1000 ft. draw, at 1320 I stake, at 2640 ft drove stake as temporary N. W. corner of sec 35. Quit for dinner. From a stone the north east Corner of Sec 35 T. 33. R. 15. E. I ran S 89° 30' West at 1320 ft. drove stake as N. W. Corner E. N. E. 1/4 Sec 35, at 2333 ft, draw at 2640 ft. drove stake as temp 1/4 post on the north line of Sec. 35. From this temporary 1/4 post on the north line of Sec 35. I Ran S. 89° 30' W. at 1320 ft. drove stake as temporary N. E. Cor. W 1/2 N W 1/4 Sec 35 at 2650 ft Came out 8 ft. south of temporary N. W. Cor. Sec 35 for Correction Set a Lime Stone 31" x 12" x 5" marked IIII for the Corner of Sections 26 - 27. 34 & 35. I also put glass broken around the stone as witness. I put Flags on the N. E & N. W. Corners of Sec 35 and adjusted my transit between them. At a point 132 2/2 ft. east on the section line from the N. W. Corner of sec 35. I set a sand stone 18" x 13" x 8" marked X with glass around the stone as witness to true point for N. E. Corner of the W 1/2 N. W. 1/4 of sec. 35. T. 33. R. 15. E at a point 2645 ft. East on section line from N. W. Corner of Sec 35, which is the middle point on the north line of the section. I set a sand stone 24" x 12" x 8" marked 1/4 for the 1/4 post on the north line Sec 35. I witnessed this 1/4 Post with Iron bars and glass At a point midway between the N. E. Corner and the 1/4 post on the North line of Sec 35. I set a sand stone 24" x 14" x 9" as N. W. Cor of the East 1/2 of the N. E. 1/4 of Sec 35. T. 33. R. 15. E. Witnessed by Iron glass & Flagstone, Quit for the day. October 22" 1902. Survey of Section 35, Continued at the South West Corner of Sec 35. T. 33. R. 15 E. I set a sand stone 21" x 18" x 10" marked IIII for Corners to sections 34. 35, 2 & 3. At a point 1320 feet north of the South west Corner of Sec. 35. I set a sand stone 27" x 12" x 7" marked X as the North West corner of the South West 1/4 of the South West 1/4 of Sec 35. At a point 2640 ft north of the South west Corner of Sec. 35. or at the middle point on the west line of sec. 35. I set a sand stone 22" x 15" x 6" marked 1/4, for the 1/4 post on the West line of section 35. T. 33. R. 15 E. October 22" P.M. Put flags on the S. W. Corner and the South East Corner of Sec 35 adjusted my transit between at a point 2640 ft east of the South West Corner of Sec. 35. I set a sand stone 24" x 8" x 8" marked 1/4 for the 1/4 post on the South line of Sec. 35. At a point midway between the 1/4 post on the South line of sec. 35 and the South West corner of said Sec 35. I set a Sand stone 18" x 15" x 7" marked X as the South East Corner of the South West 1/4 of the South West 1/4 of Sec 35. T. 33 R. 15 E. At a point midway between the 1/4 post on the South line of Sec. 35 and the South East Corner of Sec. 35, I set a sand stone 30" x 12" x 6" Marked X as the south west corner of the South East 1/4 of the South East 1/4 of sec 35. T. 33 R. 15 E. From this last discribed corner I ran north at 5-5-5 ft. draw at 1320 ft. drove stake as temporary N. W. Corner of the South East 1/4 of the South east 1/4 of Sec 35 at 2640 ft drove stake as temporary S. W. Cor of the E 1/2 N. E 1/4 Sec. 35 Quit for the day. October. 23" 1902. Survey of Section 35 Continued. I put Flags on the 1/4 posts and ran straight lines between at the intersection of the 1/4 lines I set a sand stone 32" x 12" x 7" marked X as the center Corner of Sec 35. T. 33 R 15 E. At a point 1320 ft, north on the 1/4 line, from the S. E Corner of the S. W 1/4 of the S. W 1/4 of Sec. 35 I set a sand stone 18" x 15" x 12" marked X as the N. E. Corner of the S. W 1/4 of the S W 1/4 of sec 35. At a point 1320 ft north on the 1/4 line also on the 1/4 line running east west I set a sand stone 27" x 16" x 9" marked X as the South East Corner of the South West 1/4 of the N. W 1/4 of Sec 35. At a point 1320 ft. north of last discribed Corner I set a sand stone 22" x 12" x 8" marked X, as the south west Corner of the N. E. 1/4 of the N. W 1/4 of Sec. 35. At a point midway between the Center of sec 35 on the 1/4 line and the 1/4 post on the east line of Sec 35, which I found standing I set a sand stone 26" x 18" x 9" marked X as the south west corner of the east 1/2 of the N. E. 1/4 of sec 35. I put flags on the south west Corner of the South east 1/4 of the south East 1/4 and the N. W. Corner of the E 1/2 of the N. E. 1/4 of Sec 35 T. 33. R. 15 E. I adjusted my Transit between. at the N. W. Corner of the South East 1/4 of the South East 1/4 of sec. 35, I set a sand stone 28" x 12" x 7" marked X, at a point 1320 feet West and 1322 ft north of the 1/4 post on the east line of Sec 35. I set a sand stone 27" x 11" x 7" marked X as the South East Corner of the W W. 1/4 of the N. E. 1/4 of Sec 35 T. 33. R. 15 E. I found the stones on the East line of sec 35, standing.

This completed the survey on Oct. 23" 1902.

Var 7° 3-5' E.

Dated at Independence Montgomery County Kansas, this 15" day of November 1902.

S. L. Hibbard.

County Surveyor

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

....., Kansas, ... 189....

M.....

You are hereby notified that, at ..... o'clock A. M., on the ..... day of ....., 189....., I will begin a survey on Section ....., Town ..... South, Range ....., in which you are interested, and shall continue the same from day to day until completed. Commencing at the ..... corner of said Section, I shall permanently establish

.....

.....

.....

.....

....., County Surveyor,

..... County, State of Kansas.