

Survey No. _____, Section 36, Town 34 South, Range 13.

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that S. D. Hibbard County Surveyor of Montgomery County Kansas was ordered by Ed Cochran to survey and subdivide section 36, Township 34 Range 13 East. On November 15th 1902 the following named parties were notified that a survey of the above named section would be made the survey to begin on November 24th 1902. J. B. Ross; Ed Cochran; Carissa C. Carter; H. C. Abel; J. E. Bennett; Henry F. Ayer; William Martin; J. E. Stone; W. J. Pettibone; Andrew J. Reeves; H. H. Dickerson; N. N. Osborn; Jas. A. Otto; Thomas Steel; David Vance. The notice was as follows: "You are hereby notified that I will be at the Residence of Ed Cochran on the 24th day of November 1902, at One o'clock P.M. for the purpose of surveying the lands of Ed Cochran and others lying in section 36 Twp. 34, Range 13. You will therefore be prepared to pay your proportionate part of the expenses of said survey, in accordance with sections 7411. Chapter 89. of the laws of 1891." Dated at Independence Kansas this 15th day of November, 1902, S. D. Hibbard surveyor of Montgomery County. On November 24th 1902 P.M. I began the survey. John Nolleck and Amos King were selected as Chainmen Edgar Arnold as Flagman. I went to the north West corner of the section 36 T. 34 R. 13 E. I found the corner a stone marked standing. The chainmen & Flagman were duly sworn. From this stone the north West corner of section 36 T. 34 R. 13 E. I drew N. 89° 30' E. at 2640 ft. drove stake as temporary 1/4 post between sections 25 and 36. From this temporary 1/4 post I drew N. 89° 30' E. at 1200 ft. draw, at 1320 I drove stake as temporary N. E. Cor. 1/2 of the N. East 1/4 of Sec. 36 at 2640 ft. drove stake as temporary North East Corner Sec. 36 T. 34 R. 13 on Range line. From this temporary North East corner of Sec 36 I drew South 1° 10' E. at 1320 ft. drove a stake as temporary S. E. corner N. E. 1/4 Sec. 31-34 R. 14 E. at 2640 ft. Drove a stake as temporary 1/4 post on the east line of Sec 36. From this temporary 1/4 post on the east line of Sec. 36 I drew S. 1° 10' E. at 1320 ft. drove a stake as temporary N. E. corner 1/2 of Sec. 31 T. 34 R. 14 E. at 2640 ft. drove a stake as temporary South East corner of sec 36-34-13, and quit for the day - November 25th 1902. Survey of Sec. 36-34-13 continued. I found by the Government Field notes that there were witness trees to the corner between Ranges Thirteen 13 and Fourteen 14 and Township Thirty Four 34th Township Thirty Five 35th. I found the Elm stump S. 27° E. 62 links distant. And an Oak stump N. 37° E. 70 links distance. The Hickory tree and stump was gone on acct of a slide by the creek. I located the corner by the witness trees and set a sand stone 30"x12"x8" marked 1111 with an Iron Rod driven beside it. Broken glass in hole. From this permanent S. E. corner of Sec 36-34-13. I drew S. 88° 30' W. at 880 ft. draw, at 1320 I drove stake as temporary S. E. corner of Sec 36 T. 34 R. 13 E. at 1950 ft. a draw, at 2640 ft. drove a stake as temporary 1/4 post on the South line of Sec. 36. From this temporary 1/4 post on the South line Sec 36, I drew S. 88° 30' west at 445 ft. a Draw, at 2385 ft. a Draw, at 2640 ft. found the south West corner of Sec 36 a marked stone. From this stone the South West corner of Sec 36. I drew N. 1° 10' W. at 2640 ft. a stone marked 1/4 the 1/4 post on the west line Sec 36-34-13. At a point 1320 feet N. 1° 10' W. from South West corner of sec 36, I set a sand stone 21"x10"x9" marked x as the north West corner of the South 1/2 of the South West 1/4 of Sec 36. At a point 2640 ft. S. 88° 30' West from the south East corner of Sec 36 I set a sand stone 25"x10"x10" marked 1/4 for the 1/4 post on the South line of Sec 36. At the North East corner of Sec 36. I set a sand stone 24"x9"x8" marked 1111 as the corner to sections 30, 31, 25 and 36. At a point 1321 ft. South 1° 10' E. from North East corner of sec 36 I set a sand stone 24"x12"x8" marked x as the south West corner of the N. E. 1/4, N. E. 1/4 Sec 31. T. 34 R. 14 E. At a point 2642 feet south on Section line from the North East corner of sec 36. I set a sand stone. I set a sand stone 24"x13"x6" marked 1/4 for the 1/4 post on the East line of Sec 36 and quit for the day November, 26th 1902. Survey of Sec 36. Township 34, Range 13 E. continued - At a point midway between the 1/4

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 189.

M.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189., I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

post on the East line of Sec 36 and the South East corner of Sec 36. I set a sand stone 24"x10"x8" marked x as the north West corner of the South 1/2 of the South West 1/4 of Sec 31. T. 34 R. 14 E. At a point 2640 feet N. 88° 32' E. From the North West corner of Sec 36. I set a sand stone 24"x9"x8" marked 1/4 for the 1/4 post on the North line of Sec 36. At a point 1320 ft. East on the section line from the 1/4 post on the North line of Sec 36. I set a sand stone 24"x12"x8" marked x as the North West corner of the E 1/2 of the North East 1/4 of Sec 36. At the South West corner of the East 1/2 of the North East 1/4 of Sec 36. I set a sand stone 30"x10"x8" marked x. I put flags on the 1/4 post and ran straight line between at the intersection of the 1/4 lines. I set a sand stone 24"x8"x6" marked xx as the center corner of Sec 36 T. 34 R. 13 E. At the North East corner of the S 1/2 of the South West 1/4 of Sec 36. I set a sand stone 26"x10"x4" marked x.

This completed the survey on November 26th 1902

Var 7° 55' E.

Dated at Independence Montgomery Co Kansas, Dec 13th 1902.

S. D. Hibbard, County Surveyor.