

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, L. L. Hubbard, County Surveyor of Montgomery County, Kansas, was ordered by H. L. Banks to survey and subdivide section 17, Township 33, Range 15 East, On November 23, 1902. This notice was sent to the following named parties, "You are hereby notified that I will be at the residence of H. L. Banks on the 3rd day of December, 1902 at 9 o'clock A. M. for the purpose of surveying the lands of H. L. Banks & others lying in Sec 17, Township 33, Range 15 East. You will therefore be prepared to pay your proportionate part of the expense of said survey, in accordance with Sections 7 and 11, Chapter 89, of the laws of 1897. Dated at Independence, Kansas, this 23rd day of November, 1902. L. L. Hubbard Surveyor of Montgomery County." Names taken: A. D. Mott: Samuel H. Connor: Geo. L. Banks: Enos B. Shaw: H. M. Prosser: Harriet M. Eugin: Thomas Callahan: Mrs. L. C. Booth: J. D. Atkinson: H. B. Atkinson: J. Bolt: E. Erhart: C. Metzger: A. D. Atkinson: Samuel Schonburg: W. D. Prather: Forest Erhart: C. H. Manning. On December 3, 1902 I began the survey. C. H. Carpenter and H. B. Erhart were selected as chainmen, and H. B. Atkinson as flagman, who were duly sworn, as there were no corner stones standing on Sec 17. I went a mile west of the north west corner of Sec 17 to the north west corner of section 18, Township 33, R. 15. E. and found this corner standing. I ran East on the north line of Sec 18, 5254 ft. drove a stake as the temporary north west corner of Sec 17. T. 33, R. 15. E. From this temporary N. W. corner of Sec 17, I ran N. 89° E. at 1318 1/2 ft. drove stake as temporary N. E. corner of the west 1/2 of the N. W. 1/4, Sec 17. at 2637 ft. drove stake as temporary 1/4 post on the north line of Sec 17. From this temporary 1/4 post, I ran East, N. 89° E. at 340 ft. draw at 1318 1/2 ft. stake temporary N. W. corner of the east 1/2 of the north east 1/4 of Sec 17. at 2637 ft. drove stake in center of cross roads as temporary N. E. corner of Sec 17. From this temporary north east corner of Sec 17, I ran South 20° E. at 1320 ft. drove stake as temporary 1/4 post on East line of Sec 17. From this temporary 1/4 post on East line of Sec 17, I ran S. 30° E. at 828 ft. center S. F. R. R. at 1320 ft. drove stake as temporary South East corner of Sec 17. This I did by taking bearing East & west on Sec line correction for 1/4 post on East line Sec 17 would be 5 ft. south of temporary 1/4 post. From the temporary South East corner of Sec 17, I ran S. 89° 30' west at 210 ft. draw at 675 ft. Draw at 1320 ft. drove stake as temporary S. E. cor. East 1/2 S. E. 1/4 Sec 17. at 1970 ft. center S. F. R. R. at 2640 ft. drove stake 1/4 post. From this temporary 1/4 post I ran West at 1900 ft. drove stake 1/4 quit for the day. December 4, 1902 survey of Sec 17, T. 33, R. 15. E. Continued. From the temporary North West corner Sec 17, I ran South 20° East at 2640 ft. drove stake as temporary 1/4 post on West line Sec 17. From this temporary 1/4 post on the West line, Sec 17, I ran S. 20° E. at 116 ft. draw at 1320 ft. stake temporary S. E. cor. N. W. 1/4 S. E. 1/4 Sec 17. at 2640 ft. drove stake as true point for south west corner of Sec 17. Here I set a line stone 23" x 17" x 9" marked 1111 for corner to sects 17, 18, 19 & 20. I measured from the stake driven on South line Sec 17, 1900 ft. west of the 1/4 post on the South line of Sec 17. I found the distance to be 2652 ft. to the South West corner, making an excess of 12 ft. over a mile to be divided on South line Sec 17. I set a line stone at the point where the temporary N. W. corner of Sec 17 was established as true corner. I set a line stone 30" x 14" x 11" marked 1111 for corner to sects 7, 8, 17 & 18. At the north East corner of Sec 17, I set a line stone 21" x 14" x 12" marked 1111 for corner to sects 8, 9, 16 & 17. Distance between the N. W. & north east corner of Sec 17 is 5274 feet. At a point 5290 ft S. 30° E. from the N. E. corner of Sec 17, I set a line stone 24" x 10" x 7" marked 1111 for corner to sects 16, 17, 20 & 21. At a point 1322 1/2 ft. north on Sec line from South East corner of Sec 17, I set a line stone 16" x 8" x 6" marked X as the N. E. corner of the S. E. 1/4 S. E. 1/4 of Sec 17. At a point 2645 ft. north on Sec line from S. E. corner of Sec 17, I set a line stone 25" x 12" x 7" marked 4 for the 1/4 post on the East line of Sec 17. Flags were put at the section corners and the stones were on a straight line between the section corners. At a point 1310 1/2 ft. East on Sec line from north west corner of Sec 17, I set a line stone 21" x 10" x 6" marked X as the N. E. corner of the N. W. 1/4 of the N. W. 1/4 of Sec 17. At a point 2637 ft. East on north line of Sec 17, I set a line stone 28" x 8" x 6" marked 4 for the 1/4 post on the north line of Sec 17. At a point midway between the 1/4 post on the north line of Sec 17 and the north East corner of Sec 17, I set a line stone 22" x 8" x 6" marked X, as the north west corner of the East 1/2 of the north east 1/4 of Sec 17. I quit for the day. December 5, 1902. Survey of Sec 17, T. 33, R. 15. E. Continued. As the corners on the South line of Sec 17 being established 5292 ft. apart I have 12 ft. to divide among land owners on the line at a point 1323 feet on the Sec line from the South West corner of Sec 17, I set a line stone 1/2 wagon spindle as the S. E. corner of the S. W. 1/4 of the S. W. 1/4 of Sec 17. At a point midway between the S. E. cor. & S. E. cor. Sec 17, which is 2646 ft. each way, I set a line stone 22" x 16" x 5" marked 4 for the 1/4 post on the South line of Sec 17. Flags were placed at the corners of the sects if their stones are in a straight line. At a point 1320 ft. North of the South West corner, I set a line stone 21" x 15" x 8" marked X, also put glass around the stone as witness as the north West corner of the S. W. 1/4 of the S. W. 1/4 of Sec 17. At a point 2640 ft. North on Sec line from the South West corner of Sec 17, I set a line stone 24" x 9" x 8" marked 4 for the 1/4 post on the West line of Sec 17. I put flags on all the subdivision corners around the out side of the section. I adjusted my transit between these flags, I established the interior corners for the center of Sec 17, I set a line stone 30" x 6" x 5" marked X, at the intersection of the 1/2 lines. At the N. W. corner of the South East 1/4 of the South East 1/4 I set a line stone 26" x 10" x 5" marked X as the N. E. corner of the S. W. 1/4 of the S. W. 1/4 of Sec 17. I set a line stone 28" x 12" x 14" marked X with glass 1/2 wagon spindle as witness. At the N. E. corner of the N. W. 1/4 of the South West 1/4 of Sec 17, I set a line stone 26" x 8" x 7" marked X as the S. E. cor. S. E. 1/4 Sec 17. I set a line stone 24" x 10" x 5" marked X and wagon spindle as witness.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. HALEY, Topeka, Kansas.)

Kansas, 189

M

You are hereby notified that, at . . . o'clock A. M., on the . . . day of . . . , 189 . . . , I will begin a survey on Section . . . , Town . . . , South, Range . . . , in which you are interested, and shall continue the same from day to day until completed. Commencing at the . . . corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

Sec line from N. W. cor. Sec 17, I set a line stone 28" x 8" x 6" marked 4 for the 1/4 post on the north line of Sec 17. At a point midway between the 1/4 post on the north line of Sec 17 and the north East corner of Sec 17, I set a line stone 22" x 8" x 6" marked X, as the north west corner of the East 1/2 of the north east 1/4 of Sec 17. I quit for the day. December 5, 1902. Survey of Sec 17, T. 33, R. 15. E. Continued. As the corners on the South line of Sec 17 being established 5292 ft. apart I have 12 ft. to divide among land owners on the line at a point 1323 feet on the Sec line from the South West corner of Sec 17, I set a line stone 1/2 wagon spindle as the S. E. corner of the S. W. 1/4 of the S. W. 1/4 of Sec 17. At a point midway between the S. E. cor. & S. E. cor. Sec 17, which is 2646 ft. each way, I set a line stone 22" x 16" x 5" marked 4 for the 1/4 post on the South line of Sec 17. Flags were placed at the corners of the sects if their stones are in a straight line. At a point 1320 ft. North of the South West corner, I set a line stone 21" x 15" x 8" marked X, also put glass around the stone as witness as the north West corner of the S. W. 1/4 of the S. W. 1/4 of Sec 17. At a point 2640 ft. North on Sec line from the South West corner of Sec 17, I set a line stone 24" x 9" x 8" marked 4 for the 1/4 post on the West line of Sec 17. I put flags on all the subdivision corners around the out side of the section. I adjusted my transit between these flags, I established the interior corners for the center of Sec 17, I set a line stone 30" x 6" x 5" marked X, at the intersection of the 1/2 lines. At the N. W. corner of the South East 1/4 of the South East 1/4 I set a line stone 26" x 10" x 5" marked X as the N. E. corner of the S. W. 1/4 of the S. W. 1/4 of Sec 17. I set a line stone 28" x 12" x 14" marked X with glass 1/2 wagon spindle as witness. At the N. E. corner of the N. W. 1/4 of the South West 1/4 of Sec 17, I set a line stone 26" x 8" x 7" marked X as the S. E. cor. S. E. 1/4 Sec 17. I set a line stone 24" x 10" x 5" marked X and wagon spindle as witness.

This completed the survey & subdivision of Sec. 17-33-15 E.

Var 7° 33' E

Dated at Independence Montgomery Co. Kansas. Dec. 20, 1902.

L. L. Hubbard Co Surveyor.