

Geo. W. Crane & Co., Topeka, Kan.

This is to certify that S. L. Hibbard County Surveyor of Montgomery Co. Kansas was ordered by D. A. Clinch to survey and subdivide section 34. Township 34 Range 16 East. On January 17th 1903 the following named parties were notified that a survey of sec 34 would be made, survey to begin on January 26th 1903 the following notice was served on the parties named below. You are hereby notified that you will be at the south east corner of section 34, Town 34 Range 16, on the 26th day of January 1903, at 10 o'clock A. M. for the purpose of surveying the lands of D. A. Clinch, Mrs. Barnett & others lying in section 34. T. 34 Range 16. Parties notified in the D. A. Clinch survey of sec 34 T. 34 Range 16 E. D. A. Clinch, Thomas Burnett for Barnett, O. A. Lee, Mrs. Dehofield, Mrs. Boswell, Nannie Dewark, C. F. Hall, J. R. Jones, H. H. Tyler. You will therefore be prepared to pay your proportionate part of the expense of said survey, in accordance with sections 7th and 11th chapter 89 of the laws of 1891. Dated at Independence Kansas this 17th day of January 1903, S. L. Hibbard surveyor of Montgomery County. On January 26th 1903, I began the survey. T. J. Earle was selected as chairman and duly sworn, assisted by S. L. Hibbard. We began at the south east corner of sec 34 T. 34 Range 16 E. a stone and measured west on the Township line at 1320 ft. drove stake as temporary south west corner of the south east 1/4 of the south east 1/4 of sec 34 T. 34 R. 16 E. at 1820 ft. drove stake at 2640 ft. drove stake as temporary 1/4 post on the south line of sec 34. From this temporary 1/4 post on the south line of sec 34 I ran west on Township line at 310 ft. East end of bridge across Onion Creek at 2640 ft. drove stake as temporary south west corner of sec 34. I then went to the south west corner of sec 33. T. 34 R. 16 E. a mile west of this temporary sec 33. I found a corner stone standing and measured east at 5200 ft. I drove a stake as temporary south east cor. of sec 33. There was 23 ft. between the two stakes the two sections over run 23 ft. this is to be divided between the two sections giving them 11 1/2 feet, 11 1/2 feet for each section. Quit for noon. Jan 26 P. M. From the north east corner of section 34 (a stone) Township 34 Range 16 E. I ran N. 89° 40' West at 2010 ft. a. Draw at 2640 ft. a stone the 1/4 post on the north line of sec 34. From this stone the 1/4 post I ran N. 89° 40' West at 1310 ft. a stone at 2300 ft. a draw at 2640 ft. a stone the north west corner of sec 34. T. 34 R. 16 E. From this stone the north west corner of section 34. I ran south 0° 30' West at 210 ft. draw at 2110 ft. north bank of Onion Creek at 2640 ft. found a stone in the hedge the 1/4 post on the West line of sec 34. From this 1/4 post I ran south 0° 30' west at 2636 ft. Township line. Quit for the day. Raining & muddy. Jan 27-1903. One o'clock P. M. From the 1/4 post (a stone) on the east line of sec 34. T. 34 R. 16 E. and at the 1/4 post on the west line of sec 34. I ran straight line between and drove temp stake as the center of sec 34. At the south west corner of sec 34 I set a line stone 30 x 24 x 5 marked 1111 for the corner to sec 33, 34, and drove an iron bar beside it as a witness. At a point 2645 3/4 ft. East on Township line from the south west corner of section 34. I set a line stone 30 x 18 x 5 marked 1/4 for the 1/4 post on the south line of sec 34. Bearing of the south line of sec 34 is N. 89° 30' West. Jan 28th 1903. Survey of sec 34. T. 34 R. 16 E. Continued. At a point 1322'-10" West of the south east corner of sec 34 I set a line stone 24 x 18 x 4 marked x as the south east corner of the south east 1/4 of sec 34. T. 34 R. 16 E. This stone is midway between the south east corner of the 1/4 post on the south line of sec 34. I then put flags on the 1/4 posts and ran straight line between at the intersection of the 1/4 line I set a line stone 30 x 18 x 5 marked xx as the center of sec 34. At a point midway between the 1/4 post on the East line of sec 34 and the center I set a line stone 24 x 12 x 3 marked x as the N. E. corner of the north east 1/4 of the S. E. 1/4 of sec 34. T. 34 R. 16 E. I also drove an iron pipe

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.)

..... Kansas, 189.....

M.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

..... County Surveyor,
..... County, State of Kansas.

1 1/2" diameter & 3" long as S. E. corner N. E. 1/4, S. E. 1/4, sec 34. At a point 53 rods and 3 ft. north of 1/4 post on East line of sec 34 I drove stake at a point 20 rods north of this stake drove iron pipe as N. E. corner of B. Blatterner land at a point 41 rods west I drove and iron pipe 2 feet south of true corner on sect. off Cam. at a point 20 rods south of true N. E. cor. Blatterner land drove stake on Rail Road dump near center of dump. This completed the survey of sec 34. T. 34 R. 16 E. I also measured south from S. E. cor. of sec 34 between sec 2 & 3. T. 34 R. 16 E. I ran S. 1° 10' E. 14 1/2' stake O. D. R. line at 2326 ft. center Mo Pacific R.R. at 2630 ft. stone 1/4 post. From this 1/4 post I ran west Parallel with north line sec 3. at 80 1/2 ft. drove stake as S. E. cor. E. 1/2 N. E. 1/4 sec 3. T. 34 R. 16 E. This completed the survey on Jan 29th 1903.

Var 8° E. Dated at Independence Feb. 18th 1903

S. L. Hibbard Co Surveyor.