

Survey No. _____, Section 14, Town 33 South, Range 13

This is to certify that I, S. L. Hibbard County Surveyor of Montgomery Co. Kansas, was ordered by C. C. Brooks and others to survey Sections Thirteen (13) and Fourteen (14) Township 33, Range 13 East. Having completed the survey of Sec 13 I began the survey and subdivision of Sec 14. From the South West Corner of Sec 13, I ran West (Chainmen N. E. Foster and J. W. Foster who were duly sworn) Parties notified on March 23rd 1903 that a survey of Sections 13 and 14 would be made the survey to begin on March 31st 1903. A. J. Romig, James Helmes, H. E. Sadler, A. J. Newlan, B. H. Gummaree, C. C. Brooks, Thomas J. Warner, Thomas P. Elliott. April 2nd 1903 I began the survey, I ran West on Sec line at 650 ft draw at 2627 ft. found the old Government ¹/₄ post lying down in draw but in proper place. From this ¹/₄ post I ran West on Random line at 1200 ft draw at 1313 drove stake as temporary cor to 80 acre tract at 1820 ft. draw at 2627 ft. came out 10 ft South of a stone, South West corner of Sec 14, on County line. From this stone (small stone marked) the South West Corner of Sec 14, I ran north on Random line at 1200 ft bottom hill at 1730 draw at 2640 drove stake temporary ¹/₄ post on West line Sec 14. Quit for Dinner. P. M. From temporary ¹/₄ post on West line of Sec 14 I ran north on Random line at 71° West at 940 ft. C. Kins breek 2640 ft. stone North West Corner Sec 14. From North West Cor Sec 14, I ran N. 89° E. at 1310 ft. drove stake at 2620 ¹/₂ ft found Gov ¹/₄ post in pile stone, stone down 8 ft north of stake driven as temporary ¹/₄ post on North line sec 14. From this stake I ran N. 89° E. 710 ft. drew at 1310 drove stake at 2300 ft. Ravine line runs in branch 150 ft. at 2610 ft. came out 15 feet north of the North East Corner, corrected ¹/₄ Corner 11 ¹/₂ ft. South and 5 ft West of temp Cor here I set a sand stone 26" x 16" x 6" marked X as the North West Corner of the N. E. ¹/₄ of the North East ¹/₄ of Sec 14 T. 33, R. 13, East this stone is 1305 ft West of the North East Corner of Section 14. For ¹/₄ post on North line of Sec 14 set a sand stone 24" x 16" x 6" marked ¹/₄, 2620 ft. East of North West Corner Sec 14. For ¹/₄ post on West line of Sec 14, I set a sand stone 24" x 14" x 7" marked ¹/₄. Quit for the day. April 3rd 1903. From the ¹/₄ post on East line Sec 14 I ran S. 89° W. at 1310 ft. drove stake at 2618 ft drove stake as temporary center corner of Sec 14. From this temporary center of Sec 14, I ran South 89° W. at 1323 drove stake at 2620 ft. came out 22 ft South of ¹/₄ post on West line sec 14. From temporary center Sec 14 I backsighted to a Flag on ¹/₄ post on North line sec 14 I ran South. Came out to ¹/₄ post on South line Sec 14 as the ¹/₄ post was down and not a large stone I set a sand stone 22" x 18" x 8" marked ¹/₄ put old Government

stone beside it as witness, for ¹/₄ post on South line of Sec 14, for the center of Sec 14 I set a sand stone 18" x 12" x 8" marked XX, for center Sec 14, at S. E. Corner of N. ¹/₄ of the South West ¹/₄ Sec 14 I set a sand stone 28" x 15" x 6" marked L. At the South West Corner of Sec 14 where old stone set I set a sand stone 22" x 16" x 8" marked IIII I put the old stone beside it as witness. This stone is where the old stone stood, which was too small to be permanent. At a point midway between the center of Sec 14 and the ¹/₄ post on East line of Sec 14 I set a sand stone 24" x 12" x 8" marked X as N. E. corner of East ¹/₂ S. E. ¹/₄ Sec 14. At a point 1314 ft west of the South East Corner of Sec 14 I set a sand stone 26" x 12" x 8" marked X as S. W. Cor. East ¹/₂ South East ¹/₄ Sec 14 - 33 - 13 - this completed the survey.

NOTICE—Surveyor's Permanent Record, State of Kansas. Geo. W. CRANE & Co., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description. [Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

_____, Kansas, 189____.

M. _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor, _____ County, State of Kansas.

Var, 7° 55' 6"
Dated at Independence Montgomery County Kansas May 1st 1903.
S. L. Hibbard, County Surveyor