Survey No. ....., Section 3, Town 35 South, Range 14

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I. S.L. Hibbard County Surveyor of Montgomery County Kansas was ordered by Daniel Pollett to Survey and Subdivide Section Three (3) and ten (0) Township 35 Range 14 East. On May 5th 1903. The following named parties were notified that a Survey of the above named Sections was to be made the Survey to begin on the 13 day of May 1903, J. C. Noble, J. R. Kellums; D. H. Dougan; S. M. Williams; Chas L. Keller; G. T. Guernsey, G. E. Frederick; Daniel Pollett; H. Martin; G. H. Gunwalt; J. C. Eddy; H. B. Broome; F. A. Bronson; J. N. Foreman; J. H. Roper; Elizabeth Bryant A. B. Hamilton; H. H. Smith; Joseph Perry;

Notice, You are hereby notified that I will be at the North East Corner of Section 3 Township 35 Range 14 East on the 13 day of May 1903, at 10 o'clock A.M. for the purpose of Surveying the lands of D. Pollett and others lying in Sections 3 and 10 Township 35, Range 14 East. You will therefore be prepared to pay your proportionate part of the expense of said Survey in accordance with sections 7 & 11 Chapter 89 of Laws of 1891. Dated at Independence Kansas this 5th day of May 1903. S.L. Hibbard County Surveyor; On May 13th, 1903 at 10 o'clock A.M. I was at the North East Corner of Sections 3, Township 35 Range 14 East, Frank Fragier and Geo Pollett were selected as Chain Carriers and were duly sworn, - I found the North East Corner of Sec 3 gone. In order to restablish this corner: I went to a stone 80 rods north of the North East cor of Sec 3, T 35, Range 14 E. this stone was located April 10, 1894 and recorded on page 29 in Record Book of Permanent Surveys at that time the Corner Stone for the north East corner of Sec 3, T 35 R. 14 was standing. Here I located the point for the Corner of Sec 3 - 1323 ft South of the North West Corner of the S ½ of the South West ¼ of sec 34 T 34 R 14 E. From this point located as the North East Corner of Sec 3, T 35 R. 14 E. I ran South 0° 40' E, at 160 ft. North End of Bridge across Cheyenne creek at 15-21 ft, drove Stake as temporary S.E. Cor, lot 1, Sec 3, on Osage Diminished Reserve line. From this temporary Corner on Osage Diminished Reserve line I ran S. 1° E, at 1048 ft drove stake as temporary ¼ post on East line of Sec 3. From this temporary ¼ post on East line Sec 3, I ran South 1° E. at 200 ft, Branch at 350 ft. Same branch at 500 ft, Same branch at 1266 ft. found stone standing ⅛ post Set by some survey before this time. At 1555 ft, Branch at 2592 ft a stone, South East Corner Sec 3. T 35 R 14 E. From S.E. Corner Sec 3 T. 35 R. 14 E. I ran S 89° 30' W at 875 ft. Branch at 1005 ft, Same branch at 957 ft, Same branch, at 1185 ft, Same branch at 1332½ ft, Stone set by Surveyor as S.W. Cor SE ¼ of the SE ¼ of Sec 3. From this last mentioned Corner I ran S. 89° 30' W, at 1120 ft, Creek at 1180, Creek at 1329 ft ¼ post Government Corner. Which I found but had top broken off - From this ¼ post on South line of Sec 3 I ran West at 825 ft, Creek runs S.E. at 900 ft, Creek runs N.W. at 1050, Creek runs S.W. line runs in Creek 150 ft, at 2630 ft drove stake as temporary South west corner of Sec 3, From this temporary South west Cor Sec 3 T 35 R 14 E, I ran North 1° W, at 1324 ft drove stake at west end of Heavy Hedge run East & West at 2626 ft a stone ¼ post on West line of Sec 3 this stone is about 13 ft east of true point for the ¼ post, but I concluded this was the place of the original stone. From this stone I ran N 1° W at 1014 ft, drove stake on Osage diminished Reserve line, from this stake on O.D.R. Line I ran N 1° W at 1090 ft Cheyenne Creek 20 ft wide at 1235 ft. Center D.M. & A.R.R. at 1508 ft. a stone the north west corner of Sec 3 T 35 R 14. E. - From this stone the North west corner of Sec 3 I ran East on Township line at 350 ft. I ran at 1810 ft. Center D. M. & A. Railroad Bearing of Center line of Rail Road N. 83 30' E at 2643½ ft found parts of Government ¼ post a thin lime stone broken in several parts, this stone was standing two years ago bearing Government marks. As I had occasion to measure from this ¼ post as recorded in survey of Sec 33. T 34 R 14 E. From this ¼ post I ran East at 1180 I offset North 165 ft on account of Creek at 1210 West bank Cheyenne Creek at 1650 Creek at 1950 Creek, at 2640 came out 15 ft north of Cor to Secs 2 & 3, 34 & 35, Quit the day May 14, 1903 Survey of Sec 3-35-14 Continued. For the North East corner of sec 3 T 35 R 14 I set a lime stone 16" x 10" x 3" marked 1111, I ran Bar at a Course 152 3 ft. S 1° E - From NE cor, sec 3, I set a lime stone 24" x 12" x 4" marked X as S.E. corner lot 1 of sec 3, this stone is on Osage Diminished Reserve line, I ran Lod driven beside stone at 1048 ft ¼ 1° E Distance to a lime stone 24" x 12" x 6" marked ¼ for ¼ post on East line of Sec 3. From this drove stake at 1326 ft stake, at 2650 ft stake as temp center Sec 3. From temporary center of Sec 3 I ran S 89° W, at 2620 ft came to 118 ft South of the ¼ post. From this mile located as true point as ¼ post on North line of Sec I ran South 0° 45' East at 650 ft Cheyenne Creek at 1574½ O.D.R. at 2595½ ft, E & W Random, ¼ line Established temp Center from this temporary center Sec 3 I ran S at 24 20 ft Creek at 2358 ft came out 12⅓ East of ¼ post on South line Section 3. As the Government ¼ post was broken in two I set a Sand stone in its place 24" x 12" x 8" marked ¼ for ¼ post on South line Sec 3 T. 33 R 14 E at a distance 2630 ft N of the last mentioned corner I set a lime stone 30" x 10" x 5" marked 1111 as S.W. Cor Sec 3 T 35 R 14 E, Drove Iron Rod beside stone At a point 1322 ft West of last mentioned corner I set a lime stone 24" x 15" x 4" marked X as N.W. Corner of S ½ S W ¼ sec 3, I set a bar beside it. At a point 1304 ft N of the last mentioned corner I set a lime stone 20" x 12" x 2½ M ¼, the stone was small much worn by wagon wheels. I put old Cor beside ¼ post and drove Iron Rod as witness. At a point as NE. corner S ½ S W ¼ Sec 3 I set a Stone 12" x 12" x 10" marked X at the Center of Section 3, I set a Sand stone 22" x 11" x 3" marked X X. this stone is 2.50 36½ ft South of ¼ post on North line of sec 3, T 35 R 14 I drove an Iron Rod beside Center Stone as witness. From the North East corner of the S ½ of the S W ¼ of Sec 3. I ran East at 1329½ ft Stone N.E. cor S W ¼, S E ¼, Sec 3 this Stone is marked top broken off set by some Surveyor but no record made of it this is a Sand stone made mark on it. From the stone I ran East at 1330 ft. Stone on East line sec 3 as N.E. cor S E ¼ S E ¼ Sec 3 from the last mentioned post I set a stone 665 ft west of it, sand stone 18" x 8" x 8" marked X as S.W. corner of the E ½ of the N E ¼ of the S E ¼ of Sec 3, I also set a stone 18" x 12" x 8" marked X as N.W. corner of the E ½ N E ¼ S E ¼ sec 3, I adjourned to meet again to finish the survey at the time Sec 10 T 35 Range 14 was to be surveyed. The parties notified on June 9th 1903 to complete survey of Sec 3 Township 35 Range 14 E. as adjourned were the same as before mentioned and the Survey of Sec 3 T 35, R 14 East was completed on June 20, 1903 at a point 1014 ft. north of the ¼ post on west line Sec 3 I set a lime stone 30" x 11" x 7" marked X this stone is on the Osage diminished Reserve line at the point where the ¼ post was located on the north line of Sec 3, I set a lime stone 24" x 12" x 7" marked ¼ I put parts of the old ¼ post about the Corner this completed the Survey of Sec 3 T. 35 R 14 on June 20th 1903. Section line Irregular & short North & South Old Stones Lold shortage in most cases.

Var 7° 55' E.

S. L. Hibbard County Surveyor.

NOTICE—Surveyor's Permanent Record, State of Kansas.

GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

....., Kansas, ... 189....

M.....

You are hereby notified that, at ..... o'clock A. M., on the ..... day of ....., 189....., I will begin a survey on Section ....., Town ..... South, Range ....., in which you are interested, and shall continue the same from day to day until completed. Commencing at the ..... corner of said Section, I shall permanently establish

.....

.....

.....

.....

.....

....., County Surveyor,

..... County, State of Kansas.