

Survey No. _____, Section 10, Town 35 South, Range 14

This is to certify that D. L. Hibbard County Surveyor of Montgomery Co. Kansas, was ordered by Daniel Collett to Survey and subdivide Sections 3 & 10 Township 35, Range 14, East on May 5th the parties interested were notified in Section 3 and a survey was made being on May 13th 1903 establishing the corners to Section 3 T. 35 R. 14 E. Except two as shown by this Record, the survey was adjourned on May 15th 1903 to be completed on renotification of the interested parties. On June 9th 1903 the following named parties were notified that a survey would be made subdividing Section 10 Township 35, Range 14, East. D. L. Hibbard; D. Pollett; E. H. Ginnwalt; E. D. Russell; John Kelly; J. R. Miller; Nathaniel Bradley; D. B. Dabney; Sumner Lucas; J. M. Williams; John T. Tamm; The survey to begin on June 18th 1903 at 9 o'clock A. M. On June 18, 1903 I began the survey. D. H. Collett & J. H. Jones were selected as Chaimmen & gave duty sworn. From the North East corner of Section 10 Township 35 R. 14 E. I ran South 1st 20' East at 1330 ft. I found a stone said to be the South East corner of the NE 1/4 of the NE 1/4 of Sec 10. At 2640 ft drove stake as temporary 1/4 post on East line of Sec 10. From this stake I ran S 1st 20' E. at 3985 ft. drove stake near center public road at 5280 ft. I set a line stone 20' x 10' x 22" marked 1111, which drove rod beside as witness to the South East corner of Sec 10. T. 35 R. 14 E. Quit for dinner. From South East cor of section 10 I ran west at 2663 ft 1/4 post on South line of Sec 10, stone in hedge. From this 1/4 post I ran west at 1320 ft. drove stake at 2650 ft. drove stake as temporary South West corner of Sec 10. From this temporary South West cor of Sec 10 T. 35 R. 14 E. I ran N 1st 40' E. at 1320 ft. drove stake at 2405 ft. draw at 2640 ft. stake temp 1/4 post on West line Sec 10. From this temporary 1/4 post I ran N 1st 40' E. at 1320 ft. drove stake at 2622 ft. stone NE cor Sec 10 T. 35 R. 14 E. Corrected temporary 1/4 post on West line Sec 10 nine 9 ft south as true point for the 1/4 post. I ran East at 625 ft draw at 2646 Hedge 1/4 line running North & South drove stake as temporary center of Sec 10. From temporary center of Sec 10 I ran East at 2643 ft temp 1/4 post on East line Sec 10 & quit for the day. Friday June 19th 1903 Survey of Sec 10, continued. Put flag on NE corner also a flag on South East cor Sec 10 ran straight line between for 1/4 post on East line Sec 10. I set a sand stone 18" x 14" x 6" marked 4, bearing of East line Sec 10 is S 1st 30' East. At a point 3980 ft South of the North East corner of Sec 10 I set a sand stone 18" x 13" x 6" marked X drove shon rod and put broken brockery about stone as a witness to this corner. This stone is on a line with the stone in the center of the public Road running East & West. At the South West corner of Sec 10, I set a sand stone 24" x 8" x 5" marked 1111, for the sec corner this stone is 2627 ft. west of the 1/4 post on the South line of Sec 10. At a point 1316 1/2 ft north of this last named corner on the SW cor Sec 10 I set a sand stone 20" x 7" x 3" marked X as NW corner SW 1/4 SW 1/4 Sec 10. I set a sand stone 22" x 12" x 7" marked 4, for the 1/4 post on West line of Sec 10. At a point 1316 1/2 ft south of NW cor Sec 10 I set a sand stone 22" x 12" x 4" for NW corner S 1/2 NW 1/4 of Sec 10, put glass around stone as witness for center Sec 10 I set a sand stone 22" x 5" x 4" marked X. From temporary NE cor S 1/2 NW 1/4, Sec 10, I ran East to 1/4 line stake. From this stake I ran East to East line Sec 10 came out 9 1/2 ft north of stone S. E. cor NE 1/4. The NE 1/4 Sec 10, corrected and set sand stone at NE corner S 1/2 NW 1/4 of Sec 10, 20" x 12" x 8" marked X. I found a stone 1313 ft. East of this stone also one at 2644 ft. as South East corner NE 1/4 NE 1/4 of Sec 10. This completed the survey of Sec 10, T. 35 R. 14 E. From the adjourned survey of section 3 T. 35 R. 14 E. and at points where stakes had been driven on May 15th 1903. I set stone in place of the stakes, at a point 1014 feet north of the 1/4 post on west line of Section three 3 Township 35 R. 14 E. I set a line stone 30" x 11" x 7" marked X. This stone is the South West corner of 1/4 of Sec 3, on the Deage

NOTICE—Surveyor's Permanent Record, State of Kansas. } GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas. }
[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.] Blank Books and Legal Blanks of Every Description.

_____, Kansas, _____ 189____.

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
_____, County, State of Kansas.

Diminished Reserve line. For the 1/4 post on the north line of Sec 3, I set a line stone 24" x 12" x 7" marked 1/4, this completed the survey of sections 3 & 10, T. 35 R. 14 E. on June 19th 1903, lines irregular and some lines short Var 7° 55' E., Dated at Independence Montgomery Co. Kansas July 18th 1903-
D. L. Hibbard Co Surveyor.

1349
1332 5
2661 5 10
220
2640
1330
1310