

Survey No. , Section 11 , Town 35 South, Range 14

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that H. F. Keller, Deputy Surveyor of Montgomery County Kansas was ordered by D. A. Dabney to survey and subdivide Section 11 Township 35 South Range 14 E. The following parties were notified on Feb 20, 1904, that a survey of the above named Section would be made on Feb 29, 1904. Parties notified - D. A. Dabney, Jno Gaskill, O. C. Boarding, J. C. Fields, H. S. Overpeck, M. E. Price, J. F. Hester, Moses Miller, H. F. Kilburn, Jno A. Miller, & Sam Williams. On Feb 29, 1904, I proceeded to survey and subdivide the section as shown by this plat.

A. D. Jordan and Russ Gaskill were selected as chairmen and duly sworn. I began at a government cor. stone at the corner of Sections 3, 3, 10+11 from which I ran south  $89^{\circ}37' E$  at 2640' drove stake for temporary  $\frac{1}{4}$  sec cor. stone missing. At 5286' drove stake for temporary cor. to Sec's 1-2, 11+12, found no stone here. I proceeded on same line E at 2640' drove stake for temporary quarter cor. line, north line of Sec 12 lat 5280' intersect  $N + S$  line found no cor. stone set for cor. to 1, 6, 7 & 12 but a broken stone lying on ground. The pieces of stone fit together answered description given in Gov't field notes. I then went to stake driven for temporary cor. to sections 1, 2, 11+12 and ran south at 1320' drove stake for temporary S.E. cor. of N.E.  $\frac{1}{4}$  of N.E.  $\frac{1}{4}$  of Sec 11 at 2640' drove stake for  $\frac{1}{4}$  sec cor. at 3960' found an old stone set at S.E. cor. of N.E.  $\frac{1}{4}$  of S.E.  $\frac{1}{4}$  Sec 11 in center of highway. At 5280' drove stake for temporary S.E. cor. to Sec 11, continue same line south and at 1330' found old stone set on line. This line last named, ran parallel with and 25' to west of an old hedge from temporary S.E. cor. of Sec 11 to old stone 1330' to south of it. I then went to stake driven for temporary cor. to Sections 11, 12, 13+14 and set a sand stone 30" x 11" x 5" marked X for permanent cor. to Sections 11, 12, 13+14. I then went to stake at temporary  $\frac{1}{4}$  sec. cor. on E line of Sec 11 and set a sand stone 32 x 12 x 9 marked X for permanent  $\frac{1}{4}$  sec. cor. I then went to the stake at temporary S.E. cor. of N.E.  $\frac{1}{4}$  of N.E.  $\frac{1}{4}$  and set a sand stone 18 x 14 x 6 marked X for permanent cor. I then went to stake at temporary cor. to sections 1, 2, 11+12 and set a sand stone 30 x 14 x 7 marked X for permanent cor. I then went to an old stone cor. to Sections 10, 11, 14+15 and ran E on true line at 2640' drove stake for temporary  $\frac{1}{4}$  sec. cor. at 5294' reached cor. to Sections 11, 12, 13+14. Returned to stake driven for temporary  $\frac{1}{4}$  sec. cor. on S line of Sec 11 and corrected East 7' and set sand stone marked X. I then started at last named cor. ( $\frac{1}{4}$  sec. cor. on S line Sec 11) and ran N. on random. At 1320' drove stake at 2640' drove stake, 3960' drove stake, 5280' intersect E + S. line on N. of Sec 11, 12' to E of stake at  $\frac{1}{4}$  sec. cor. and corrected back. I then went to an old stone at  $\frac{1}{4}$  sec. cor. on west line of Sec 11, and ran E. on random to  $\frac{1}{4}$  sec. cor. on E line of Sec 11 and corrected back. At intersection of line connecting  $\frac{1}{4}$  section lines I set a sand stone 24" x 9 x 6 for permanent sec. center to Sec 11. On true line 1320' S of Sec. center I set a sand stone 27" x 12" x 10" marked X for permanent N.W. cor. of S.E.  $\frac{1}{4}$  of S.E.  $\frac{1}{4}$  Sec 11. I then went to stake on true line 1320' S E of Sec. center and set a sand stone 33 x 11 x 5 for permanent S.E. cor. of S.W.  $\frac{1}{4}$  of N.E.  $\frac{1}{4}$ . I then went to stake on true line and 1320' N of Sec. center and set a sand stone 26" x 10" x 9" for N.W. cor. of S.W.  $\frac{1}{4}$  of N.E.  $\frac{1}{4}$ . I went to corrected stake on N line of Sec 11 and set a sand stone 18" x 6" x 6" and drove iron pin below for permanent  $\frac{1}{4}$  sec. cor. I then went to stone set at N.E. cor. of S.E.  $\frac{1}{4}$  of N.E.  $\frac{1}{4}$  and ran west to stone at N.W. cor. of S.W.  $\frac{1}{4}$  of N.E.  $\frac{1}{4}$  and corrected back and at 1320' set a sand stone 28" x 14" x 7" for N.E. cor. of S.W.  $\frac{1}{4}$  of N.E.  $\frac{1}{4}$ .

NOTICE—Surveyor's Permanent Record, State of Kansas.

GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Blank Books and Legal Blanks of Every Description.

Kansas,

189.

M  
You are hereby notified that, at o'clock A. M., on the day of , 189 , I will begin a survey on Section , Town , Range , in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,  
County, State of Kansas.

H. F. Keller Deputy Surveyor

Montgomery County Kansas.