

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that D. H. F. Keller, Deputy Surveyor of Montgomery County, Kansas, was ordered by J. D. Bray to survey and subdivide Sec 14 Township 33 S. Range 16 E. The following parties were notified on April 16, 1904, that a survey of the above named Section would be made commencing on April 28, 1904. Parties notified: - Carrie Reles (Mestole) E. Brooke, A. D. Bray, J. C. Baker, H. N. Price, H. M. Minnick, H. E. Braden, C. A. Jutz, H. H. Forsythe and Lavina Thompson. On April 28, 1904 I proceeded to survey and subdivide the section as shown by this plat. M. C. Heckert and F. D. Thompson were selected as chammens and duly sworn. I began at a sand stone 8" x 8" at the Gov't corner to Sections 23, 24, 25 & 26 and ran north 0.22' N. At 5280' drove stake for temporary cor to sections 13, 14, 23 & 24. I then went to 1/4 sec. cor. on south line of Sec 13 and ran (as recorded in permanent survey of Sec 13) North 89° 35' N. 2640' and corrected temporary cor to sec's 13, 14, 23 & 24 and set a line stone 28" x 12" x 6" marked 1 on E and 111 on S for permanent corner to Secs 13, 14, 23 & 24. From the established cor to sections 13, 14, 23 & 24 I ran north on random. At 1320' a point E of an old stone. 2640' drove stake for temporary 1/4 sec. cor. on E. line of Sec 14. At 5280' drove stake for temporary cor. to Sec's 11, 12, 13 & 14. I then went to the cor of Sec's 10, 11, 14 & 15 and ran true line (as recorded in permanent survey of Sec 11) East and at 5248' I set a line stone 22" x 15" x 8" marked 1 on E face and 111 on S. for permanent cor to Sec's 11, 12, 13 & 14. Except the last named cor. I found all stones on N. line of Sec 14, set as recorded in the permanent survey of Sec. 11. From the established cor to Sec's 11, 12, 13 & 14 I ran South on true line. At 2640' reached a point N of stake set for temporary 1/4 sec. corner. Corrected over and set a line stone 20" x 12" x 4" marked X for permanent 1/4 sec. cor. on E line of Sec 14. I then went to cor. to Sec's 13, 14, 23 & 24 and ran S. 89° 40' N. on random. At 2640' drove stake for temporary 1/4 sec. cor. on line of Sec 14. At 5280' drove stake for temporary cor to Sec's 14, 15, 22 & 23. I then went to cor to Sec's 15, 16, 22 & 23 and measured east to stake at temporary cor. to Sec's 14, 15, 23 & 24. Corrected this corner by moving E. 5' making it proportionate distance between the cor to Sec's 15, 16, 22 & 23 and the cor to Sec's 14, 15, 23 & 24 where I set a line stone 20" x 16" x 6" marked 11 on E face and 111 on S. corrected the temporary 1/4 sec. cor. on S line of Sec 14 by moving E. 2.5' and set a limestone 11" x 10" x 5" below plow depth for permanent 1/4 sec. cor. on S line of Sec 14. I then went to established cor to Sec's 14, 15, 22 & 23 and ran N 70° 5' N. on true line. At 1320' I set a limestone 24" x 12" x 4" marked X for permanent S. E. cor. of N 1/2 of Sec 14. At 2640' I set a triangular line stone 24" in height marked X for permanent 1/4 sec. cor. on N. line of Sec 14. At the intersection of right lines connecting 1/4 sec. corners of Sec 14, I set a line stone marked X for permanent section center of Sec 14. I then went to 1/4 sec. cor. on N line of Sec 14 and ran East on true line. At 330' I set a limestone 16" x 12" x 3" for permanent S. E. cor. of ten (10) Acres off west end of S 1/2 of N 1/4 Sec 14. From the last named corner I ran N 70° 5' N. and parallel with N line of Sec 14 and at 1050' I set a line stone 24" x 8" x 4" marked X for a witness. The true corner in Verdigris River. I then went to center of Sec 14 and ran S. on true line to 1/4 sec. cor. on S line of Sec 14 and at a point equidistant from the last named corners I set a line stone 22" x 12" x 3" marked X for the permanent S. E. cor. of N 1/2 of S 1/4 of Sec 14. I then went to center of Sec 14 and ran N on true line. At 1320' found an old sand stone set for N. E. cor. of S 1/2 of N 1/4 Sec 14. This completed the survey on May 4, 1904.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.....

M.....
You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

went to center of Sec 14 and ran N on true line. At 1320' found an old sand stone set for N. E. cor. of S 1/2 of N 1/4 Sec 14. This completed the survey on May 4, 1904.

Done at Independence Montgomery Co. Kans, May 21, 1904.

H. F. Keller, Deputy Surveyor of Montgomery Co. Kans