

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, S. L. Hibbard County Surveyor of Montgomery Co Kansas was ordered by M. D. Bond and H. L. Long to survey and establish the line from the N.E. corner of Sec 5 T 35 R 17 E to the North East corner of said section also to survey and subdivide lots 1, 2 & 3 of Sec 5 T 35 R 17 E as shown by the plat of this survey. On the 14th day of May 1904, the following named parties were notified. M. D. Bond; Elgie Boyman; A. B. Holland; Virginia L. Wright; F. A. Fleeter; H. L. Long; Catherine Stephenson; Sealy Brown; P. Magnus. That a survey of the above described land would be made the survey to begin on May 24th 1904. May 24th 1904 I began the survey. H. L. Harned and S. Morgan were selected as chainmen and Bert H. Grier as Flagman who were duly sworn. I began at a pine stone at the intersection of the section line on the west line of Sec 5 T 35 R 17 E and the Osage Diminished reserve line ran N 1° W. 1108 ft. made a mark on the Iron Bridge across Pumpkin Creek as temporary corner of the N.W. cor of Sec 5. Here I found marks made on the Iron as true corner to Sec 5 which were made on the survey of Sec 6 T 35 R 17 E as Recorded. From this now located corner of Sec 5 I offset South 150 feet on acct of line in Pumpkin Creek drove stake, from this stake I ran S 87° 15' E as per field notes 200 ft offset north 100 feet. Thence S 87° 15' E across slough 100 feet. Thence north 50 feet to Sec line. Thence South 87° 15' E at 1634 feet drove stake as temporary 1/4 post between sections 32 & 33 on a line north of an old stone which is directly South on the Osage Diminished Reserve line. I then went to the 1/4 post on the East line of Sec 32 T 34 R 17 E and ran South at 173 feet Pumpkin Creek line runs angling across creek 107 feet wide I ran South along a stone fence at 1834 ft Pumpkin Creek line runs in creek at 1800 ft. I offset west 100 feet and ran South at 2640 ft. Offset East 100 ft and drove stake as temporary S.E. cor to Sec 32, and quit for the day. May 25th 1904 On acct. of rain I postponed this survey until May 31st 1904. May 31st 1904 Survey continued I went to the North West corner of Sec 32 T 34 R 17 E, a stone. I ran South 87° 15' E at 1591 ft. the distance given by government field notes to the treaty line. I drove a stake. From this stake I ran South 0° 45' E. at 3962 Pumpkin Creek 157 feet wide by measurement. At 5280 feet drove stake near corner of old fence as true point for the 50th mile Post on the Treaty line and on the Township line between Townships 34 & 35, R. 17 E. here I set a line stone 16" x 16" x 6" marked 50th M and quit for the day. June 1st 1904 Survey continued From the stone the 50th mile Post I ran N 88° 45' E on township line at 1054 feet. Stake temporary 1/4 post on South line Sec 32. From this stake I ran N 88° 45' E at 1320 stake at 1800 feet. Draw 125 feet wide at 2300 ft offset north on acct of creek 70 feet Thence N 88° 45' E at 2640' offset back 70 feet and came out 4 1/2 feet South of temporary corner set by N & South ran on East line of Sec 32. Here at this point I set a line stone 16" x 10" x 5" marked 111. also set an Iron rod beside it as witness to corner to sections 32, 33, 4 & 5 on Township line. It witness tree water oak 14" in Diameter 4 feet each: a Hickory 4" in Diameter 2 feet west. both trees marked 3 notches. I set for the 1/4 post on the South line of Sec 32 a line stone 18" x 10" x 4" marked 7 this stone is 1020 ft N 88° 45' E of 50 mile Post. From this 1/4 Post on the north line of Sec 5 I ran South at 1046 ft an old stone on Osage diminished Reserve line. Here I put a flag and ran west to a flag at the intersection of the west line of Sec 5 and the Osage Diminished Reserve line a stone at 1020 feet intersection of the Osage Diminished Reserve line and Treaty line. I set a line stone 24" x 17" x 4 1/2" marked X at a point 408 1/2 feet west on O.D.R. line. Set a line stone 12" x 9" x 4" M X and Iron Rod as S.W. cor E 1/2, E 1/2 lot 3, Sec 5; measured South from 50 mile stone to O.D.R. stone 1027 feet. At a point 408 1/2 ft. N 87° 15' W. from 50 mile stone I set a line stone on township line 24" x 10" x 4" M X at N.W. cor E 1/2, E 1/2 lot 3 Sec 5 this completed Survey June 1st 1904

NOTICE—Surveyor's Permanent Record, State of Kansas.
[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

_____, Kansas, 189____.

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
_____, County, State of Kansas.

wide at 2300 ft offset north on acct of creek 70 feet Thence N 88° 45' E at 2640' offset back 70 feet and came out 4 1/2 feet South of temporary corner set by N & South ran on East line of Sec 32. Here at this point I set a line stone 16" x 10" x 5" marked 111. also set an Iron rod beside it as witness to corner to sections 32, 33, 4 & 5 on Township line. It witness tree water oak 14" in Diameter 4 feet each: a Hickory 4" in Diameter 2 feet west. both trees marked 3 notches. I set for the 1/4 post on the South line of Sec 32 a line stone 18" x 10" x 4" marked 7 this stone is 1020 ft N 88° 45' E of 50 mile Post. From this 1/4 Post on the north line of Sec 5 I ran South at 1046 ft an old stone on Osage diminished Reserve line. Here I put a flag and ran west to a flag at the intersection of the west line of Sec 5 and the Osage Diminished Reserve line a stone at 1020 feet intersection of the Osage Diminished Reserve line and Treaty line. I set a line stone 24" x 17" x 4 1/2" marked X at a point 408 1/2 feet west on O.D.R. line. Set a line stone 12" x 9" x 4" M X and Iron Rod as S.W. cor E 1/2, E 1/2 lot 3, Sec 5; measured South from 50 mile stone to O.D.R. stone 1027 feet. At a point 408 1/2 ft. N 87° 15' W. from 50 mile stone I set a line stone on township line 24" x 10" x 4" M X at N.W. cor E 1/2, E 1/2 lot 3 Sec 5 this completed Survey June 1st 1904

Reserve line. Here I put a flag and ran west to a flag at the intersection of the west line of Sec 5 and the Osage Diminished Reserve line a stone at 1020 feet intersection of the Osage Diminished Reserve line and Treaty line. I set a line stone 24" x 17" x 4 1/2" marked X at a point 408 1/2 feet west on O.D.R. line. Set a line stone 12" x 9" x 4" M X and Iron Rod as S.W. cor E 1/2, E 1/2 lot 3, Sec 5; measured South from 50 mile stone to O.D.R. stone 1027 feet. At a point 408 1/2 ft. N 87° 15' W. from 50 mile stone I set a line stone on township line 24" x 10" x 4" M X at N.W. cor E 1/2, E 1/2 lot 3 Sec 5 this completed Survey June 1st 1904

S. L. Hibbard Co Surveyor

Independence June 9th 1904.