

This is to certify that d. H. F. Keller, Deputy Surveyor of Montgomery County, Kansas, was ordered by J. C. Page & A. E. Page to survey and subdivide Section 6, Township 33, Range 16. The following parties were notified on June 1, 1905 that a survey of the above named section would be made beginning on June 8, 1905. Parties notified - A. E. Page, J. C. Page, Jas. Lillard, Western States Portland Cement Co., Independence Park and Improvement Co., J. F. Evans, H. T. Goe, Ferene Kolander, Gilbert W. Denniston, Hiram Newton, A. F. Johnson, Mary S. W. Gaughlin, E. H. Talbert, C. E. Schank, D. Painter, James Bolton, C. L. Bloom, J. C. Ross. On June 8, 1905, I proceeded to survey and subdivide said Sec 6-33-16 as shown by this plat. Ed Main and Stephen Hamilton were selected as chainmen & duly sworn. Harry Fowler acted as flagman & found the corner to Townships 32 & 33 Range 15 & 16 and the corner to Sections 5, 6, 7 & 8, Township 33, Range 16 standing. I also found the Gov't 1/4 post on north line of Sec 6-33-16 lying in the corner of two old hedges and dug up a piece of it buried in the ground where the corner stone lay. I began at the corner of Townships 32 & 33 Range 15 & 16 and ran south on a random. At 2640 I drove stake for temporary 1/4 post on N. line of Sec 6-33-16. At 3280 I drove stake for temporary E. corner to Secs 1, 6, 7 & 12. I then went to cor. of Secs 5, 6, 7 & 8 (a limestone) and ran N. on random. At 1320 I marked a rock for temporary S. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16. At 2640 I drove iron pin for temporary 1/4 post on S. line of Sec 6. At 3760 I drove stake for temporary S. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16. At 5280 I reached temporary S. E. cor. of Sec 6-33-16. E. & W. random intersecting N. & S. random at stake. I then produced random on N. line of Sec 6-33-16 (by back & foreights) south to cor. to Secs 13, 18, 19 & 24 falling 65 ft. N. of Gov't cor. which I found standing as recorded by witness trees. I then corrected temporary cor. to Secs 1, 6, 7 & 12 - 33-16 by moving E. 2.1' and drove iron pin for the location of permanent S. E. cor. of Sec 6-33-16. I went to 1/4 post on N. line of Sec 6 and corrected E. 1.05' and drove iron pin for location of permanent 1/4 post on N. line of Sec 6. I corrected the temporary S. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16 by moving it E. 11 1/4'. The S. line of Sec 6 fall short of Gov't distance 15' and drove stake for permanent corner. I then corrected temporary 1/4 post on S. line Sec 6 by moving E. 7 1/2' and drove iron pin for location of permanent 1/4 post on S. line Sec 6. I corrected temp. S. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6 by moving E. 3 3/4' marking a rock for location of permanent cor. I then started from N. E. cor. Sec 6-33-16 and ran E. on offset 10' to S. at 1890' Rock. I then at 2549' reached N. & S. hedge 12 1/2' to S. of where I found Gov't 1/4 post lying in cor. of hedge. At 3130' I drove stake in N. & S. hedge. At 3872' I drove stake for temporary N. E. cor. of Gov't 1/4 Sec 6-33-16. At 5792' I drove stake for temporary N. E. cor. of Sec 6-33-16. Quit for the day. I then went to 1/4 post on E. line Sec 31-32-16 and measured S. 2627' to stake for temporary N. E. cor. Sec 6-33-16. I next went to S. E. cor. Sec 6-33-16 and ran N. on random. At 1318' I drove stake on old sandstone set and marked 1/4 on N. face. At 2640 I drove stake for temporary 1/4 post on E. line Sec 6-33-16. At 2641' found old limestone, unmarked, lying in fence about 6 ft. to N. at 3611' Rock. I then at 4006' a point 12' to N. of an old limestone set in ground. At 4398' I offset 25' to N. & continued N. at 5356' intersected E. & W. random on N. of Sec 6 at 47' to N. of temporary N. E. cor. of Sec 6. I then corrected temp. N. E. cor. of Sec 6 by moving South 13' and drove stake for location of permanent N. E. cor. Sec 6-33-16. This left the E. line of Sec 6, 3-34' long, which was 31.4' more than Gov't length. I apportioned this excess as follows: To the first 1/4 mi. on S. of E. line Sec 6 I added 7' to the next 1/4 mi. I added 7' to the next 1/4 mi. 7' and to fractional north part (1/4 nearly mi) I added 8'. I corrected random on E. line Sec 6 to true line at 1327' N. of S. E. cor. Sec 6. I drove stake for permanent N. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16. At 2655' I drove stake for location of permanent 1/4 post on E. line Sec 6. At 3983 1/2' I drove stake for permanent N. E. cor. of S. E. 1/4 of N. E. 1/4 Sec 6. I then went to stake at 1/4 post on E. line of Sec 6-33-16 and ran N. on random to N. line Sec 6 fall S. of 1/4 post on N. line I corrected bearing & ran E. on true line. I then went to 1/4 post stake on N. line Sec 6 and ran South on offset random & corrected back. At intersection of straight line connecting quarter posts of Sec 6-33-16 I set a sandstone 15" x 14" x 6" marked X for permanent center to Sec 6-33-16. From center of Sec 6 to Quarter post on N. line of Sec 6 the distance is 2603 1/2' to 1/4 post on E. line 2642 3/4' to 1/4 post on S. line 2649' to 1/4 post on N. line Sec 6 2677 1/2'. On true line 1327' N. of center of Sec 6 I set a sandstone 18" x 8" x 8" marked X for permanent N. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16. On true line 1321 1/2' E. of center of Sec 6 I set a sandstone

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1897, by B. A. Bailey, Topeka, Kansas.]

Kansas, 189.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

14" x 10" x 7" marked X for permanent N. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16. From the central point on boundary lines of S. E. 1/4, Sec 6-33-16, I ran straight line to opposite central point and at their intersection I set a sandstone 17" x 14" x 4" marked X for permanent N. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16. For the 1/4 post on N. line Sec 6 I reset the line stone 18" x 10" x 3" marked 1/4 which I found in the corner of old hedge for permanent 1/4 post on N. line Sec 6-33-16. On true N. line Sec 6 and at 1321 1/2' E. of 1/4 post I set a limestone 24" x 10" x 3" marked X with 7/8" iron pin 3 1/2" long driven beside for permanent N. E. cor. of N. E. 1/4 of N. E. 1/4 (or Gov't) Sec 6-33-16. At N. E. cor. of Sec 6-33-16 I set a limestone 27" x 18" x 8" marked X on E. face & 11111 on S. face for permanent N. E. cor. of Sec 6-33-16. (This stone is about 17' S. of a hedge running E. and S. 31' N. of N. rail of R.R. spur to cement plant) At N. E. cor. of S. E. 1/4 of N. E. 1/4 Sec 6-33-16 I set a limestone 19" x 17" x 4" marked X for permanent cor. (This stone is 23' S. of an old set limestone) For the 1/4 post on E. line of Sec 6-33-16 I set a limestone 20" x 10" x 2 1/2" marked X for permanent 1/4 post at N. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6-33-16. I set a sandstone 15" x 9" x 9" marked X for permanent corner. (This stone is 9' N. and 4' E. of a sandstone marked X which was set by Co. Surveyor A. G. Savage) At S. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6 I drove a cast iron pin 12" x 2" x 2" in middle of road for permanent corner from which a Cottonwood tree 8" diam bears S. 10° W. 21' dist. For the 1/4 post on S. line Sec 6 I set an iron pump cylinder with 3/8" iron rod 4 ft. long driven down through it. At S. E. cor. of S. E. 1/4 of S. E. 1/4 Sec 6 I set a sandstone 17" x 10" x 4" marked X with iron pin driven beside for permanent corner. At 1/4 post on N. line Sec 6-33-16 I set a limestone 16" x 12" x 6" marked 11111 on S. face with iron rod driven beside for permanent corner. On true line 715' N. of S. E. cor. Gov't 2 Sec 6-33-16 I set a sandstone 20" x 13" x 10" marked X with iron pin driven beside for permanent corner. On true N. line of Sec 6 at 715' ft. west of N. E. cor. of Gov't 2 - Sec 6-33-16 I set a sandstone 24" x 12" x 3" marked X for N. E. cor. of a tract of land 43 1/2' wide from off E. side of Gov't 2 - Sec 6-33-16. On true N. line of Sec 6 at 715' ft. west of N. E. cor. of Gov't 2 - Sec 6-33-16 I set a sandstone 24" x 12" x 3" marked X for N. E. cor. of a tract of land 43 1/2' wide from off the East side of Gov't 2 - Sec 6-33-16

This completed the survey of Sec 6-33-16
Dated at Independence Montgomery Co. Kansas June 24, 1905

H. F. Keller Deputy Surveyor of Montgomery Co. Kansas.