

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, H. F. Keller Deputy Surveyor of Montgomery County, Kansas, was ordered by A. B. Broome to survey and subdivide section 4 Township 35 Range 14 East. The following parties were notified on May 14, 1905 that a survey of the above named section would be made, beginning on May 25, 1905. Parties notified: H. B. Broome, A. H. Broome, Henry Bradley, H. A. Truskett, Mrs. H. F. Fymwalt, The Deming Investment Co. and M. G. Rockwood. On May 25, 1905, I proceeded to survey and subdivide the section as shown by this plat. H. F. Keller & H. F. Keller were selected as chainmen & duly sworn. Clyde Broome acted as flagman. I found the quarter posts on the East, West & North lines of Sec 4-35-14 standing as recorded in permanent surveys of the surrounding sections. I set a flag at 1/4 post on N line of Sec 4-35-14 and then went to the 1/4 corner on E line and ran West on true line connecting E & N quarter corners. At 1320' drove stake for temporary S.W. cor of Lot 8. At 2620' drove stake on E bank of Cheyenne creek, at 2640' would be in the stream. Extended flag line across the creek and quit for noon. When started at 1/4 cor on North line of Sec 4-35-14 and ran South on random. From point where this random intersected E & N line through center of Sec 4 we measured South on random. At 1320' drove stake for temporary S.E. cor of N 1/2 of S.W. 1/4 sec 4. At 2614' 1/4 intersected E & N line on South of Sec 4 at 14 1/2' East of the Gov't 1/4 corner. At this 1/4 cor we found a stone which answered description of Gov't field notes except the marks could not be seen. Also found here the witness tree as given in Gov't field notes. I then corrected over on true line and set a limestone 18" x 10" x 4" marked 1/4 and buried old stone beside for permanent 1/4 post on South line of Sec 4-35-14. On true line 1307' 1/8 north of 1/4 corner on South line sec 4 I set a sandstone 14" x 11" x 8" marked X for the S.E. cor of N 1/2 of S.W. 1/4 sec 4-35-14. I then went to center of Sec 4 and corrected temporary center by moving it West on true E & N line 7' 1/4 and drove stake for location of permanent center of Sec 4. I then measured to stake driven 2620' N of 1/4 post on E line of Sec 4 and found the distance to be 41' 3" thus making distance from 1/4 post on E line to center 2661' 3". I then went to stake driven on E & N line at temp cor of Lot 8 and corrected it N 10' 2/3 ft and drove stake for location of permanent S.W. cor of Lot 8 sec 4-35-14. From the S.W. cor of Lot 8 sec 5-35-14 I ran East on random and intersected N & S line on E of Sec 4-35-14 at 1 1/2 ft S of E cor of Lot 1 sec 4. I then returned to about the location of 17th mile stone on Osage Diminished Reservation line and found the Gov't 17th mile stone lying flat near a fence with proper marks on it. I then located the point of the 17th mile stone on O.D.R. line by means of the stump of the witness tree given in Gov't field notes. I then located the line by Gov't bearing N 89° 38' and produced the line both E & W through Sec 4-35-14. I then went to the 1/4 cor on N line of Sec 4 and ran E on true line and at 1320' 1/8 ft drove stake 2641 1/2 ft. N.E. cor stone, sec 4-35-14. I returned to last named stake driven on N line of Sec 4 and ran South on random intersecting E & N line through center of Sec 4 at 4 7/8 ft E. of S.W. cor Lot 8, Sec 4. I then corrected over and where true N & S line crossed O.D.R. line I set a sandstone 20" x 11" x 6" marked X for permanent N.W. cor of Lot 8 sec 4-35-14, from which an Elm 3 ft diameter bears N. W. 21 ft. dist. At the S.W. cor of Lot 8 I set an irregular limestone 20" x 8" x 5" marked X for permanent S.W. cor of Lot 8 Sec 4-35-14. At the center of Sec 4-35-14 I set a sandstone 30" x 10" x 10" marked X for permanent cor from which an oak 8" diameter bears S.W. 3 1/2 ft. I then N & S. Quarter line intersected O.D.R. line I set a sandstone 20" x 10" x 4" marked X for permanent S.E. cor of Lot 3 Sec 4-35-14 from which an Oak 10" diameter bears N 20 ft. dist.

NOTICE—Surveyor's Permanent Record, State of Kansas. Geo. W. Crane & Co., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description. [Copyright, 1891, by E. A. Bailey, Topeka, Kansas.]

....., Kansas, 189.....

M.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

..... County Surveyor, County, State of Kansas.

At the point where west line of Sec 4 intersected O.D.R. line I set a limestone 18" x 10" x 4" marked X with crockey and iron pin beside for permanent S.W. cor of Lot 4 Sec 4-35-14. At a point on N line of Sec 4 midway between 1/4 post and S.W. cor of Sec 4 I set a sandstone 30" x 14" x 4" marked X with iron pin driven beside for permanent S.W. cor of N 1/2 of S.W. 1/4 Sec 4-35-14. From the S.W. cor of N 1/2 of S.W. 1/4 Sec 4-35-14 I ran north on N line of Sec 4 and at 660 ft. I set a sandstone 20" x 14" x 4" marked X for permanent N.W. cor of 5 acre tract. I then ran East 330 ft. and set a sandstone 12" x 8" x 7" marked X for N.E. cor of 5 acre tract. I then ran South 660 ft. to S line of N 1/2 of S.W. 1/4 Sec 4 and set an irregular sandstone 22" x 11" x 3" marked X for S.E. corner of 5 acre tract. This completed the survey.

Dated at Independence Montgomery County Kans, this 6th day of July 1905.
 Va 7° 55' E.
 H. F. Keller, Deputy County Surveyor.