



This is to Certify that S. L. Hibbard County Surveyor of Montgomery County, Kansas, was ordered by Thomas Harrison on January 16th 1893, to survey and establish the County Road running from the Quarter post on the East line of Section 12, T. 34 R. 16, N. 12 to the Verdugo River, also to subdivide and locate corners necessary in such survey and to establish any corners that may be demanded by legal owners of lands in the above described section. On January 23rd 1893 the following named parties were notified that a survey of the above named section would be made on February 6th 1893. H. L. Hoggatt, Thomas Hooper, R. C. Graham, J. C. Tolbert, Joseph Savard, Elmer Hayes, William F. Huddellorn, Cordell Foster, Noah Kane, J. J. Jordan, Chat Ball, and J. M. W. Marshall. Thomas Harrison and H. P. Baker. On Feb 6th 1893 appeared at the place appointed at J. P. Harrison's at 12 O'clock M. in the afternoon they looked for the corners of the section, finding no corner on the East line of Section 12, & located a starting point a stone at the North East corner of Section 12 on the 7th & 8th Ranges as above. Feb 7th & went across the Verdugo River to the West side of Section 12, and ascertained that there was no corner on the section, that was the North West corner as previously shown which I found correct. On each of the corners found correct and stones. I concluded to set the survey at the corner line by a re-survey and adjourned at 3 P.M. on Feb. 7th 1893. On February 8th 1893 the above named parties were again notified with the additional names of William Hunkins and Joseph Chandler, that a survey of Section 12, T. 34 R. 16 E. would be made on Feb. 16th 1893. On Feb. 16th 1893. I began the survey 8:30 A.M. Thomas Hunkins and David Rupert were selected as chain carriers and were duly sworn. I went to the North East corner of Section 12 on the Range line 7.34 R. 16 E. here I found a stone from which I ran South on mile 5280 ft. line I found stake temporary N.E. corner Sec. 12. I then went to the North East corner on the Range line South which was at the S.E. corner of Sec. 24, T. 34 R. 16 E. I found a stone, ran North two miles down a stake as temporary S.E. corner Sec. 12, which was 12 ft. South of the temporary stake set from the run from the North East corner of Section 12. I found temporary stake at 1/4 post East side Sec. 12, 6 ft. South, West I set a line stone 22' x 6" marked 1/4. At the South East corner of Section 12 I set a line stone 18' x 6" x 4" marked 1111. In corner to Section 7.18 12 1/3. At the North East corner of Section 12 I set a line stone 16' x 15' x 5" marked 1111. In corner to Section 1.6, 7 & 12, found the N.E. corner of Section 12 I ran N. 89° W. at 1320 ft. down stake at 2640 down stake, temporary 1/4 post, North side Sec. 12, at 5285 ft. came out at permanent corner. I found stone found stump of a Quince tree a Hickory S. 73° 30' E. 35 ft. distant, then I set a post 15 ft. west on each of which ran South at 1320 ft. down stake, at 1720 ft. across edge of River measured River by wire 160 ft wide at 2640 ft. down stake at temporary 1/4 post 15 ft. west of the corner at 3960 ft. down stake at 5280 ft. came out 10 ft. west of a sand stone, at the request of the parties leaving land joining this corner and finding it nearly correct I located the S.W. corner of Sec. 12 at this place and agreed to make record of the same. Thomas Harrison for 1/4 post on West line of Section 12 would be 5 ft. South and 12 1/2 ft. East of the run made 15 ft. West of the line line, found the S.W. corner of Sec. 12 ran S. 89° E. at 1320 ft. down stake. I then went to the point located as the place for 1/4 post on North line of Sec. 12. Here I set a line stone 27' x 12' x 6" marked 1/4. I found Friday evening and being obliged to be at my office one Saturday afternoon at Independence, I adjourned the survey until Monday Feb. 20th 1893. On Monday Feb. 20th 1893 I began at the temporary stake on the North line of Sec. 12 1320 ft. East of the S.W. corner & ran S. 89° E. at 242 ft. Verdugo River 304 ft. N. side by measurement, at 1320' down stake at temporary 1/4 post North line Sec. 12. found this temporary stake I ran S. 89° E. at 1320' down stake at 2636 ft. came out 6 ft. North of S.E. corner Sec. 12, correction for 1/4 post South side Sec. 12, 3 ft. South and 2 ft. West, then I set a sand stone 22' x 12' x 6" marked 1/4, Midway between S.E. corner & 1/4 post North line, I set a line stone 16' x 7' x 8" marked X. I then went to the 1/4 post on East line Sec. 12 ran West at 1320 down stake, at 2640 down stake temporary stake Sec. 12 found this last named stake I ran N. 89° W. at 837 ft. Verdugo River, River 213 1/2 ft. wide by measurement, at 1320 ft. down stake — Tuesday Feb. 21st 1893 found the last named stake I ran N. 89° W. at 5284 ft. came out 2 1/2 ft. North of corner between S.E. corner & N.W. 1/4 Sec. 12. I set a point 1322 1/2 ft. South of the 1/4 post on the West side of Section 12. I set a sand stone 16' x 10' x 4" marked X. At a point 1319 ft. S. 89° 6' E. from S.W. corner Section 12 I set a line stone 16' x 7' x 3" marked X. From this corner I ran West at 1322 1/2 ft. I set a line stone 16' x 12' x 2 1/2" marked X. For S.E. corner of N.W. 1/4 Sec. 12. At 2645 ft. temporary corner then I set a line stone 22' x 10' x 6" marked X. I then went to the temporary located 1/4 post on the North line Sec. 12 found this 2 1/2 ft. West, then I set a sand stone 20' x 6' x 3" marked 1/4. I then ran due South at 1320 ft. down stake, at 2640 ft. down stake was temporary stake previously located, ran South on 1/4 line to South line Sec. 12 came out 2 ft. West of 1/4 post correction for Center 3 ft. South 1 ft. West at this point I set a line stone 33' x 14' x 3" marked XX. At the intersection of 1/4 lines, at a point 1321 ft. West on the 1/4 line from the 1/4 post on the East line of Section 12, I set a line stone 16' x 15' x 2 1/2" marked X. For S.E. corner of N.W. 1/4 Sec. 12. At a point 1322 1/2 ft. South of the 1/4 post on the North line of Section 12 I set a line stone 33' x 16' x 4" marked X. For S.E. corner of N.W. 1/4 Sec. 12. Feb. 22nd 1893 had to make sure that the West line of the N.W. 1/4 Sec. 12 was straight I set flag 24 ft. West of the N.W. corner & the 1/4 post on West line Sec. 12 adjusted my hand & corrected for angles 2 1/2 ft. South and set a line stone 24' x 10' x 2 1/2" marked X. Now as the distance between the S.E. corner of the N.W. 1/4 Sec. 12 and the S.W. corner of the N.W. 1/4 Sec. 12 was 2644 ft. I ran from the S.E. corner of N.W. 1/4 Sec. 12 West 1322 ft. I set a line stone 30' x 12' x 5" marked X. For N.W. corner of S.E. 1/4 N.W. 1/4 Sec. 12. At a point 661 ft. West on 1/4 line I set a sand stone 18' x 8' x 4" marked X. In the S.E. corner of the N.W. 1/4 Sec. 12, at a point 661 ft. East on Section line from the N.W. corner of Sec. 12, I set a sand stone 14' x 6' x 5" marked X. as the N.W. corner of E. 1/2 N.W. 1/4 Sec. 12, I also set a line stone 1321 ft. N. 89° W. from the North East corner of Section 12 as the N.W. corner of the East 1/2 of N.E. 1/4 Sec. 12. This completed the survey (Wednesday Evening Feb. 22nd 1893. Car. 9° E.

Noted at Independence Montgomery County Kansas -
March 4th 1893. S. L. Hibbard
County Surveyor.