

FIELD NOTES OF SURVEY NO.

Hamilton & Curl, Manufacturers Topeka, Kansas

the section at half distance in the west of the half section (By reason of part of the section being in the Osage Reserve, no quarter section corner was ever made in the west line of the section) Description and size of the corner established. Limestone 2 inches thick by 15 inches broad and 15 inches long.

E. G. Davison
Co. Surveyor

Survey No 2. April 22nd 1869 For J. E. Boye Diagram No 2.

West 1/4 of North West quarter of section 21 Dp. 31 Range 17 E.

Variations of and length of lines are as represented on the diagram.
Found position of Center corner of the section at crossing of lines connecting the opposite quarter section corners. Established corner at half distance in South line of the quarter section. Description and size of the corner Limestone 3 inches thick by 10 inches broad and 18 inches long. Established corner at half distance in north line of the quarter section. Description and size of the corner Established Limestone 3 inches thick by 12 inches broad and 18 inches long.

E. G. Davison
Co. Surveyor

Surveyor Office Oswego La Bette Co. Kansas, May 24th 1879.

I certify that the foregoing transcript of the Diagram plats and notes of Survey made by E. G. Davison County Surveyor of La Bette County Kansas April 21st and 22nd 1869 and as recorded on page 5 of Surveyors Record for La Bette County Kansas has been correctly copied from the original record on file in this office.

Geo. Thornton, County
Surveyor La Bette County Kansas

Surveyor Office Oswego La Bette County Kansas May 27th 1879
I certify that on the 26th and 27th days of May 1879 I retraced the lines of the survey made by E. G. Davison for J. E. Boye and Delaplain April 21st and 22nd 1869. The notes and diagrams of which are recorded in the Surveyors Record for this La Bette County on page 5. I found the corner established by him at half distance on the south line of the North East quarter of Section 20 Dp. 31 Range 17 E. in place and from it with the distance and variations given in his notes and diagrams I reset the other corners of his survey.

Geo. Thornton, County Surveyor

La Bette County Kansas

Exhibit "G"
C. W. Lamb sworn says— Saw the 1/4 S. corner bet. 20 & 21 Township 31 S. Range 17 E. in Dec. 1869. It was a stake and stood upon the south side of Drum Creek and to the best of knowledge it was near the stone set by E. Doeter today. I have known the corner to Secs. 16, 17, 20 & 21 in Township Thirty one, Range 17 E. since July 1869. It then stood in the same place where it has since stood until removed by A. G. Savage in the spring of 1879. The place where said rock stood has always been regarded as the original Government corner by all parties in interest.

Chas. W. Lamb

Subscribed and sworn to before me this 1st day of December 1879.

E. Doeter
(L.S.) Notary Public

Exhibit "D"

Statement of J. C. Delaplain. I first saw the 1/4 S. corner bet. 20 & 21 Township Thirty one 31 South of Range 17 E. in April 1869. It was a Stake recognized by E. G. Davidson as the Govt corner, and was then standing on the south side of Drum Creek. I can not now locate the point where the corner then stood. I think the corner then stood near the corner stone set by Mr. Doeter today. I think it stood south of the stone about 8 feet.

I have known the corner to Secs. 16, 17, 20 & 21 Township 31 R. 17 E. since April 1869. The corner stone was down at that time and was set up by the La Bette County Surveyor. He took measurements from different corners then standing at the time. He set said corner. It has always stood in the place the Surveyor then put it, and has been regarded as the corner by all parties in interest, until removed by A. G. Savage in the Spring of 1879.

J. C. Delaplain

Subscribed and sworn to before me this 1st day of Dec. 1879.

E. Doeter

(L.S.) Notary Public

Statement of Henry Moninger and J. B. Jones. We first saw the corner to Secs. 20, 21, 28 and 29 in Township 31 South Range 17 E. in the year of 1869. There was a rock standing at that time that was regarded as the Government corner to said sections and to the best of our knowledge and belief the rock is now standing in the same place it then stood. We saw a stake standing in the year of 1869, that we regarded as the 1/4 Sec. corner bet. 20 & 21. To the best of my knowledge and belief the said stake stood at that time about Two rods North East of the rock set by E. Doeter today.

Henry Moninger

J. B. Jones

Subscribed and sworn to before me this 1st day of Dec. 1879.

E. Doeter

(L.S.) Notary Public

Statement of J. E. Boye. I have known the corner to Secs. 16, 17, 20 & 21 Township Thirty one, Range 17 E. since April 1869. It was found at the time of survey made by E. G. Davidson in the place where it has since stood until removed by A. G. Savage in the Spring of 1879. The corner was lying down at the time Davidson made his survey in 1869, and was set up by him. Mr. Davidson at the time he set up said corner tested the same by measurement from the 1/4 S. corner bet. 16 & 21 and the 1/4 corner bet. 17 & 20 and the 1/4 S. corner bet. 20 & 21 which corners were standing at that time. I have been acquainted with the corner to Secs. 20, 21, 28 & 29 Township Thirty one, South Range 17 East since April 1869. and that where the stone now sets is the same place that the corner stood at that time to the best of knowledge and belief. I first saw the 1/4 S. corner between Secs. 20 & 21 T. 31 R. 17 E. in April 1869. The corner was standing at that time and was a Burr Oak Stake, squared at the top marked 1/4 S. To the best of my knowledge and belief said stake stood about 4 ft. South and 4 ft.