

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that H. F. Keller, Deputy Surveyor of Montgomery County Kansas, was ordered by J. E. Hagner and others to reestablish the line between sections 3 and 10, Township 34, South Range 15 E. The following parties were notified on June 22, 1905, that a survey of the above named section line between Secs 3 & 10 would be made beginning on June 29, 1905. Parties notified J. H. Trimble, Mrs Prentice Smyth, Mrs C. C. Smith, John E. Hagner, J. E. Hunter, Eliza H. Katon, Rosella Newman, Cordelia Hulbert, Ethel Hay, Lottie Hobson, Harvey Blacet, Walter Scott, H. E. Hudson, A. J. Broadbent, Wm Angyle, D. B. Snell, Sarah M. Parker, H. H. Frost, J. E. Menech, James Marshall, E. M. Wheeler & Ernest Burster. On June 30, 1905, (the 29th rain delayed survey) I proceeded to survey and locate the section line as shown by this plat. A. J. Broadbent and H. F. Keller were selected as chainmen and sworn, Harry Fowler acted as flagman part time and Floyd Hay the remainder.

I found no corner monuments on this line so I proceed as follows. I began at 1/4 sec. corner (stone) on South line of Sec 2-34-15 and ran west on random and at 2640' drove stake. Then began at 1/4 sec. cor on East line of Sec 3 (a sandstone marked 1/4 on E face) and ran south on random and at 2640' drove stake. Then began at the Gov't 1/4 Sec. Cor. on East line of Sec 10 and ran north on random and at 2640' drove stake. From the 1/4 sec. cor on the East line of Sec 3-34-15 to 1/4 sec. cor on East line of Sec 10-34-15 the distance is 5282 1/2 ft. I divided the excess 2 1/2 ft. and located the S.E. cor. of Sec 3-34-15 at 2641 1/4 from 1/4 cor on E line of Sec 10-34-15 and 2641 1/4 from 1/4 sec cor on E line of Sec 3-34-15 and 2639 ft. from 1/4 sec. cor on south line of Sec 2-34-15. Here I set a sandstone 18"x10"x3" marked 11 on E face and 11111 on S face, for permanent corner to Sections 2, 3, 10 & 11 T. 34 R. 15.

From this S.E. cor to Sec 3-34-15 I ran N 89° 36' E. for Gov't bearing at 2633 1/2 ft. the center between N & S old hedges. Here I drove an iron rod 1 1/4" by 30" with a sandstone 20"x15"x3" marked 1/4 beside for permanent 1/4 sec corner on S line sec 3-34-15. At 5276 ft a point between two old N & S hedges, from this point I measured N on random and at 2642 1/2 reached a hedge said to have been planted on N & S quarter line. I returned to the point 5276 ft S of S.E. cor. of Sec 3-34-15 and set a sandstone 27"x12"x8" marked 111 on E face and 11111 on south face, with piece of broken sewer pipe around it for the permanent cor to Secs 3, 4, 9 & 10. Gov't notes gave length of this line 77.90 ch.

This completed the survey.
Dated at Independence Montgomery County Kansas this 31st day of July 1905.
Va 7° 55'

H. F. Keller Deputy Surveyor of Montgomery Co Kansas

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.

M.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189., I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

_____, County Surveyor,

_____, County, State of Kansas.