

Survey No. , Section 10 , Town 32 South, Range 15

GEO. W. CRANE & CO., Topeka, Kas.

This is to certify that H. F. Keller, Deputy Surveyor of Montgomery County, Kans., was ordered by Geo. E. Nicholson to survey and subdivide Sec. 10, T. 32, R. 15, and also to survey a strip of land beginning at the S.E. cor. of S.W. 1/4 of S.E. 1/4 of sec. 10-32-15 and running thence west on south line of said sec. 10 to the S.W. cor. of the S.E. 1/4 of S.W. 1/4, Sec. 10-32-15, thence south 70 ft., thence east to a point 75 ft. south of beginning thence north 70 ft. to beginning. On the 23d day of Feb. 1906, the following parties were notified that the above mentioned survey would be made beginning on the 2d day of March 1906. Parties notified—Geo. E. Nicholson, Mrs. Murphy, Murphy heirs, A. Ringle, Harriet F. Powers, H. C. Baylies, John Frenhagen, Amanda Frenhagen, Am. H. Brost, L. F. Brost, Nancy J. Hays, A. P. Montgomery, Adda P. Bolles, H. J. Barnes, H. M. Cleverger, Ellison Peet, Mary Van Cleaver, Eliza A. Brownfield, A. P. McBride, Henry E. Hanson, Geo. E. Guernsey and T. Domes.

The 2d of March being stormy, the survey was commenced on the day following. M. L. Heckert and W. G. Shirey were chosen as chairmen being duly sworn. Frank Fowler acted as flagman one-half day and M. L. Heckert flagged, during the remainder of the time. I began at the cor. to Secs. 10, 11, 14 & 15 T. 32 R. 15, a limestone which I found standing, and ran west on random. At 1320 ft drove iron spike for temporary quarter-quarter cor. at 2640 drove stake for temporary quarter post on line of Sec. 10, at 3960 drove stake for temporary quarter-quarter cor. at 3380 ft. drove stake and searched for S. W. cor. of Sec. 10-32-15 but could find no stone. Then went to the Gov't quarter post on West line of Sec. 10-32-15 which I found standing (The stone answered the description and location given in Gov't field notes but marks were obliterated) I set my transit over this quarter post and back sighted to flag on stone standing at N.W. cor. Sec. 10-32-15, reversed telescope and ran South on true line, at 484 ft. Top edge of bluff, 1275 ft. descend Bluff 260 4/5 ft. Stake at temp. S.W. cor. of Sec. 10-32-15, continued line South at 3940 ft. on E & W hedge, at 5260 ft. a hedge fence to E. and stone fence to West, could find no quarter post. Then returned to S.E. cor. of Sec. 10-32-15 and corrected temp. cor. by moving South 15 1/2 ft. making it 2620 ft. South of quarter post on West line of Sec. 10-32-15, this half mile being rough I applied the shortage of 20 ft. to it. At this cor. to Secs. 9, 10, 15 & 16 T. 32 R. 15 I set a limestone 38" X 15" X 7" marked 1111 on N face and 111 on E. face, for permanent cor. I dug excavating for this corner we dug up a flat stone which corresponded nearly in size to corner given in Gov't field notes) At 1320 ft. east of S.E. cor. of Sec. 10-32-15 or true line I drove an iron braker rod 6 ft. long for permanent quarter-quarter corner, at 2640 ft. E. of S.E. cor. of Sec. 10-32-15 I connected temp. quarter post by moving it South 7 3/4 ft. on true line and set a limestone 20" X 8" X 7" marked X on north face for permanent quarter cor. on South line of Sec. 10-32-15 at 1320 ft East of last named quarter post and on true line I set a limestone 20" X 10" X 4" marked X for permanent quarter-quarter cor. Then went to quarter post on East line of Sec. 10-32-15 where I found an old stone standing as recorded in permanent survey of Sec. 11-32-15 and ran west on random and at 3280 ft intersected N & S line 3 ft. north of quarter post on west line of Sec. 10. Then corrected back on true quarter line. Then ran straight line from established quarter sec. cor. on South line of Sec. 10 to

NOTICE—Surveyor's Permanent Record, State of Kansas.

GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas,

189

M

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

center sec. 10-32-15 on quarter line I set a sandstone 24" X 9" X 4" marked X for S.E. cor. of 1/4 of NW 1/4, at 330 ft. south of last mentioned corner I set an irregular limestone 16" X 10" X 8" marked X for S.E. cor. of ten acres off North side of NW 1/4 of SW 1/4 ran thence East 60 ft. drove gas pipe, thence North at 561 ft. drove gas pipe 2 ft. S.W. of an oak 6" diam, thence North about 95 ft. to Elk River. From the S.E. cor. of 1/4 of NW 1/4 sec. 10-32-15 I ran North 231 ft. set an iron grate bar, 3 ft. long, thence West 99 ft. drove iron bolt 3 ft. long, thence North 62 ft. drove gas pipe in walnut stump, thence North about 35 ft. Elk River. At 1322 ft. E. of N.E. cor. of Sec. 10-32-15 I set a sandstone 32" X 8" X 4" marked X for N.E. cor. of 1/4 of NW 1/4 sec. 10-32-15. From the 1/4 sec. cor. on South line to center of Sec. 10-32-15 measured 2624 ft. I ran South from center of Sec. 10-32-15 on quarter line at 330 ft. set sandstone 25" X 6" X 6" marked X for cor. to ten acre tract, at 1312 ft. set limestone 14" X 8" X 7" marked X for quarter-quarter cor. I ran thence East 660 ft. I set a limestone 16" X 12" X 7" marked X for N.E. cor. of 1/4 of S.E. cor. of Sec. 10-32-15, thence South 15' within 75 ft. of South line of Sec. 10 and set iron bar in stone mound in edge of ravine, thence East 569 ft. to center of Public Road and drove iron pin, thence South 75 ft. to South line of Sec. 10 and drove iron pin. From the S.E. cor. of 1/4 of S.E. 1/4 of Sec. 10-32-15 I ran South into Sec. 15-32-15 and at 70 ft. I set limestone 18" X 10" X 6" marked X for South line of Right of Way, thence West 2640 ft. on line parallel with S line of Sec. 10 I drove iron pin on South line of Right of Way and 70 ft. south of S.W. cor. of S.E. 1/4 of S.E. 1/4 of Sec. 10-32-15. This completed the survey as shown by this plat. Dated at Independence, Kansas, this 20th day of March 1906.

H. F. Keller, Deputy Surveyor of Montgomery Co. Ks.