

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that H. F. Heller, Deputy Surveyor of Montgomery County Kansas, was ordered by H. A. Gasteneau to survey and subdivide Section 28, Township 32, South Range 15 East. The following parties were notified on March 26, 1906 that a survey of the above named section would be made beginning on April 3, 1906. Parties notified: Sam'l Swearingen, Jasper Swearingen, John Woods, Isaac Clemmer, F. Friepe, J. T. Green, J. B. Lee, A. J. Witte, J. A. Pickler, R. E. Burns, J. B. Pickler, J. A. Kyle, Nannie M. Swartz, C. L. Bondra, H. M. Jackson, H. A. Gasteneau, L. V. Joving, and J. P. V. Kanawall. On April 3, 1906, I proceeded to survey and subdivide the section as shown by this plat. M. L. Beckert and H. A. Beckert were selected as chainmen and duly sworn. I found the south west and north west corners, and also the quarter post on west line of sec 28-32-15 standing as recorded in permanent survey of sec 29-32-15. I began at the corner to sec 29, 21-28-29-32-15 and ran East on random. At 1320 ft drove stake, at 2634 $\frac{3}{4}$ ft. a point 4 $\frac{3}{4}$ ft. north of Old Stone of the description in Gov't field notes, except marks were obliterated. I decided this must be the Gov't $\frac{1}{4}$ Post on north line, sec 28-32-15. At 3950 ft. a point 4 $\frac{1}{4}$ ft. north of an old limestone set in road. At 5280 ft. drove stake in center of road and searched for corner but could find no monument. From last mentioned stake, at temp. north east corner of sec. 28-32-15 I ran East on random and at 5276 $\frac{3}{4}$ ft. line of sec 27-32-15 at a point 9 $\frac{3}{4}$ ft. north of north east corner of sec 27-32-15 which cor. I found standing. The Gov't field notes giving the north line of sec 27-32-15 as 4 links short. I returned and corrected stake at temporary north east corner of sec 28-32-15 by moving west 2 $\frac{1}{2}$ ft. and drove iron bolt in center of road as temporary corner. From this last mentioned bolt I ran south on random and at 1320 ft drove stake, at 2233 $\frac{1}{2}$ ft. offset 10 ft. to east. At 2640 a point on 10 ft. offset at 20 ft. east of an old stone in corner of hedge. This stone was same kind and size as given in Gov't field notes for $\frac{1}{4}$ Post on East line of sec 28-32-15 but marks were obliterated, at 5280 ft. drove stake in center of road. From old stone at south west corner of sec 28-32-15 I ran East on random. At 1320 ft. drove stake, at 2640 ft. drove stake, about 12 ft. E of N. E. hedge at 3960 ft. drove stake, at 5306 ft. stake driven at temp. south east corner, sec 28-32-15. I then corrected temp. south east corner of sec 28-32-15 by moving west 30 ft. and set a limestone 26" x 6" x 6" marked 111 on East face and 1 on south face for permanent cor. to sec 27, 28, 33 & 34. This made length of south line of sec. 28-32-15 to be 5276 ft. as given in Gov't field notes. At 1317 ft. west of the re-established south east corner, sec 28-32-15 and on true line I set a limestone 30" x 12" x 4" marked X for permanent quarter-quarter cor. For the quarter post on south line of sec 28-32-15, which post is on true line 2638 ft. west of south east cor. of said sec. 28-32-15, I set a limestone marked $\frac{1}{4}$ on north face for permanent quarter post. At 1319 ft. west of last mentioned quarter post I set a limestone 27" x 8" x 6" marked X for permanent quarter-quarter corner. I then offset 10 ft. to west of $\frac{1}{4}$ Post on south line, sec 28 (on account of hedge) and ran north on random, intersecting north line of sec 28-32-15 at 17 ft. west of $\frac{1}{4}$ Post on north line and corrected over to true line. I then ran from $\frac{1}{4}$ Post on west line said sec 28 through to $\frac{1}{4}$ Post on East line, where I set a limestone 30" x 8" x 6" marked $\frac{1}{4}$ on East face with old sandstone beside it. I corrected east and

west random to true quarter line and at the intersection of quarter lines I drove an iron shaft 1' 8" x 3 ft. in an East and west hedge for permanent center of sec 28-32-15. From $\frac{1}{4}$ Post on west line of sec. 28-32-15 to center of said sec 28 measured 2636 $\frac{3}{4}$ ft. so at 1318 $\frac{1}{2}$ ft. East from $\frac{1}{4}$ Post on west line and in true E & W quarter line. I set a limestone 23" x 6" x 6" marked X for permanent quarter-quarter corner. From center of sec 28-32-15 to $\frac{1}{4}$ Post on East line measured 2637 $\frac{1}{2}$ ft. so at 1318 $\frac{1}{2}$ ft. east of center of said sec 28 and on true E & W quarter line. I set a limestone 32" x 6" x 5" marked X for permanent quarter-quarter corner. At 1320 ft. south of north west corner of sec. 28-32-15 and on true sec. line I set a limestone 30" x 8" x 4" marked X for permanent quarter-quarter corner. At 1317 $\frac{1}{2}$ ft. east of north west corner of sec 28-32-15 on true line to quarter post on north line I set a limestone 26" x 6" x 5" marked X for permanent quarter-quarter corner. From the quarter post on the north line of sec 28-32-15 south on quarter line to east and west hedge is 1320 ft. to center of sec 28-32-15 is 2635 ft. This shows Gov't quarter post on north line of sec 28-32-15 to be 5 ft. south of a straight line connecting north west and north east corners of the section. In place of the iron bolt at North East corner of sec 28-32-15 I set a cast iron pipe 2 $\frac{1}{2}$ " x 36" with rock around for permanent northeast corner of sec 28-32-15. From the middle points on the boundaries of the north west $\frac{1}{4}$ of sec 28-32-15 I ran straight lines to opposite middle points and at their intersection I set a limestone 32" x 8" x 5" marked X for permanent center of N. W. $\frac{1}{4}$ sec 28-32-15.

This completed the survey as shown by this plat. Dated at Independence Kansas this 1st day of May 1906.

H. F. Heller Deputy Surveyor of Montgomery County Kans.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

_____, Kansas, _____ 189_____

M _____
You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189_____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

County Surveyor,

_____, County, State of Kansas.