

Geo. W. Crane & Co., Topeka, Kas.

To the County Surveyor Hibbard; Cherokee, Kansas: We, the undersigned property owners in Rutland Township, Montgomery County, Kansas, owning property in Sections 35 and 36, Township 32, Range, 13, do respectfully petition, that you resurvey and reestablish the corner between section 35 and 36, Township 32, Range 13, Montgomery County, Kansas, beginning at Mr. Woods St corner run North, on Sec line three east to North east corner of Sec 36 to Old Government Survey. O. W. Hedger, M. E. Hedger, J. E. Kincaid, A. D. Ringle, J. P. Stark, F. G. La Force, J. A. Hood, John M. Morris.

This is to certify that H. F. Keller, Deputy Surveyor of Montgomery Kansas, was ordered by O. W. Hedger, J. P. Stark and others to survey the north line of Sec 36, T32S, Range 13E, and to correctly establish north west corner of said sec. 36-32-13. On Feb 23, 1906 the following parties were notified that a survey of Sec 36-32-13 would be made beginning on the 7th day of March, 1906. Parties notified - M. E. Hedger, O. W. Hedger, F. G. La Force, J. H. Morris, Jasper A. Hood, P. Burnes, E. M. Burnes, F. E. Fitzgerald, H. Benjamin, S. Moyer, J. P. Stark, Chas. Goe, Benj. Caney, J. H. Butler, Nellie B. Scott, J. E. Kincaid, Asher Davidson, Chas. W. Fisher, J. T. Mitchell. On account of sickness and inclement weather the survey was adjourned. On April 4, 1906 the following parties were notified that a survey would be made of above mentioned section beginning on the 12th day of April, 1906. Parties notified - A. D. Ringle, J. T. Mitchell, Asher Davidson, J. E. Kincaid, J. P. Stark, H. Benjamin, F. E. Fitzgerald, J. A. Hood, J. H. Morris, F. G. La Force, M. E. Hedger, O. W. Hedger, Chas. Goe. On the 12th of April 1906 I proceeded to survey and subdivide said sec 36-32-13 as shown by this Plat. F. G. La Force and J. A. Evans were selected as chainmen and duly sworn. On the evening of 12th April I was compelled to adjourn survey on account of sickness and commenced again on April 17. F. G. La Force not being present J. Stroud was selected in his stead as chainman and duly sworn. I found the Gov't stone at south west corner of Sec 36-32-13 and also the quarter post on South line of said section standing, I began at this quarter post on South line Sec 36-32-13 and by backsighting and reversing ran East and at 2638 2/3 ft. found Gov't. cor. to Township 32 + 33, Range 13 + 14 East. This stone was broken off but on a piece of it I found Gov't marks and also found part of the stone standing in ground. I drove iron pin 1 1/2" x 1 1/2" x 18" and buried piece of Gov't stone beside, I set a tall flag at this corner and ran true line west and at 1319 1/2 ft. set sandstone 7 1/2" x 12" for permanent quarter quarter corner. I then went to a point on hillside a short distance north of Gov't 1/4 Post on East line of Sec 36-32-13 (which corner I found standing) and set my transit so as to sight a flag on this last mentioned quarter post and the flag at the cor. to Township 32 + 33, Range 13 + 14 E. Transit being in line with these two corners I reversed the telescope and ran north on true Range line, measuring north from Gov't 1/4 Post on East line Sec 36-32-13 and at 2640 ft. drove stake in center of road for location of permanent north east corner of Sec 36-32-13. From this last mentioned stake I ran west on random, and at 1320 ft. drove stake, at 2640 ft. drove stake, at 3960 ft. drove stake, at 5280 ft. a point six inches south of an old stone. This stone is shown in record of permanent survey of Sec 35-32-13 to be 2643 ft. from the 1/4 Post south of it and 2643 ft. from the 1/4 Post north of it, but its East and west distance from Range line was questioned & corrected on random on north of Sec 36-32-13 by moving west end north 8". At north east corner of Sec 36-32-13 I set a sandstone 27" x 10" x 4" marked 1 on south edge with iron pin driven beside for permanent north east corner of Sec 36-32-13. At 1320 ft. west of north east corner, sec 36-32-13 I set a sandstone 20" x 14" x 3" marked X for permanent quarter-quarter corner, at 2640 ft. west of said N. E. cor. sec 36-32-13 I set a sandstone 24" x 12" x 5" marked 1/4 on north face with iron pin driven beside for permanent 1/4 Post on north line, sec 36-32-13, at 3960 ft. west N. E. cor. said sec 36. I set a sandstone 22" x 10" x 4" marked X for permanent quarter-quarter corner. At 5280 ft. west of N. E. cor. sec 36-32-13 on true line I set a sandstone 24" x 6" x 5" marked 1 on south face and 1 on E face for permanent north west corner of Sec 36-32-13. This last mentioned corner was set 3 ft. east of an old stone set in survey of Sec 35-32-13. I then went to 1/4 Post on west line of Sec 36-32-13 which I found standing as recorded in permanent survey of Sec 35-32-13. This corner is about 10 ft. east of a straight line connecting north west and south west corners of Sec 36-32-13, so I checked the measurements from witness stumps and found its location according to Gov't field notes. From this last mentioned 1/4 Post I ran east on random and at 1320 ft. drove stake, at 2640 ft. drove stake, at 3960 ft. drove stake, at 5277 ft. intersect N & S line, at 31 ft. north of 1/4 Post on E. line of Sec 36-32-13. I then retraced and corrected stakes to true line. I then ran straight line from 1/4 Post on south line of Sec 36-32-13 to 1/4 Post on north line, and at the intersection of the true quarter lines I set a sandstone 28" x 9" x 5" marked X for permanent center of Sec 36-32-13. From center of said, sec 36 to 1/4 Post on East line measured 2640 ft. so on true line at 1320 ft. east of center of sec 36-32-13 I set a sandstone 22" x 9" x 5" marked X for permanent quarter-quarter corner. From center of Sec 36-32-13 to 1/4 Post on west line measured 2631 ft. so at 1315 1/2 ft. west of center of sec 36-32-13 on true quarter line I set a sandstone 27" x 5" x 5" marked X for permanent quarter-quarter corner.

This completed the survey as shown on this plat. Dated at Independence Kans. This 3d day of May, 1906.
H. F. Keller Deputy Surveyor, Montgomery County Kansas.

NOTICE—Surveyor's Permanent Record, State of Kansas. GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description. [Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.] Kansas, 189. M You are hereby notified that, at o'clock A. M., on the day of, 189, I will begin a survey on Section Town South, Range, in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish County Surveyor, County, State of Kansas.

Copy done

Row 14 Post

Range 14 E

20 1/2 x 32 1/2 x 3 1/2 Sandstone