

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that J. A. L. Penney, Deputy County Surveyor of Montgomery County, Kansas, in pursuance of a call of J. E. Cox, did on the 12th day of July, 1906, mail to each of the following parties interested or likely interested in said survey - to locate or establish the South and East lines of Section 4, Township 34, Range 15, and other boundaries of the South-west one quarter of said Section.

Viz - J. E. Cox, R. M. Dotson, J. E. Meyers,
W. H. Frost, N. H. Cox, A. Cummings,
J. E. Mench, D. B. Snell, W. D. Meachen,
Harrison Anderson, J. E. Wagner

That on the morning of the 17th of July, 1906, I would call the said survey at the home of the above J. E. Cox, at 8:30 A. M.

That at the above appointed time I did appear at the above mentioned place for the purpose of beginning said survey and that only J. E. Cox of the above did appear.

We went to the corner of Sections 3-4-9+10 and after Reet Frost and Arthur Sawyer were sworn and with Orville Cox as flagman, we began at a stone established by W. F. Kellar in his survey of June 1905, and ran West on a line S. 82°30'W. (government notes give this as 25' less than true variation). 2637 1/2 ft (government notes give both quarters 8' short), set temporary stake, covered with stone, then ran West on same line 2639 1/2 ft. to corner Sections 4-5-8+9 and set temporary stake. Then went north to corner of Sections 3-4-32+33, but could not locate any stone, went East to corner of Sections 3-4-33+34, but could not locate stone here so adjourned for the day.

On Friday, July 20, we went South to corner Sections 8-9-16+17 found stone marked "+" and established, Chained North 5276 ft (government notes give this Section 4 ft short) to corner

NOTICE—Surveyor's Permanent Record, State of Kansas.
(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

_____ Kansas, _____ 189____

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____ County Surveyor,
_____ County, State of Kansas.

Sections 4-5-8+9, where temporary stake was but found it gone also one at quarter East with stone. Ran line West again from corner Sections 3-4-9+10 and set both temporary stakes. (Came out 4'10" North of other stake at corner of Sections 3-4-8+9 and adjourned for the day.

On Saturday, July 21, began by going North for corner stone, spent A. M. without finding one, though we went as far as corner Sections 20+21+22+23, and corner of Sections 2-3-34+35. No one could we find.

anyone who thought they were there. But found one at corner of Sections 5-6-31+32 but had no data for this line so adjourned until Wednesday August 1, 1906.

On Wednesday, August 1, we began at corner Sections 3-4-9+10 and ran N. 5°20'W. (government notes give this line 25' more than true variation) 5306 2/3 (government notes give this line 26 2/3 ft long-connection) to corner of Sections 3-4-33+34, also ran flag line for point to check on after running 5280 ft to corner of Sections 4-5-32+33, set temporary stake then went South to corner of Sections 4-5-8+9 and ran check line to corner of Sections 4-5-8+9 and set line stone 21x18x6 marked "1111" on North face and "+" on top face to mark intersection of lines. This stone is 26 ft N. 19°E. of the N. E. corner of the first laid column of bridge. Thence North 2640 and set temporary stake at quarter line, thence North 2614 ft. to corner of Sections 3-4-32+33 (government notes give this quarter 36 ft short) and found temporary stake 3 ft 10 in. South. Then went to stone at corner of Sections 5-6-31+32 and Chained East 5280 ft to corner of Sections 4-5-32+33 and found stake 1 ft 6 in. too far West corrected and set temporary stake and adjourned for the day.

On Thursday, Aug 2, 1906, we set limestone at corner of Sections 4-5-32+33 Then went East from temporary stake at quarter to center of old stone then ran West 2638 (government notes make this true) and set stone at quarter between Sections 4+5. Then went to center of Section and ran South 2640 to quarter between Sections 4+9, found stake 4 ft 7 in. too far North, corrected and set set line stone.

this ended the survey as shown on this plat

Variation 7°55'

A. L. Penney, Deputy Surveyor,