

Geo. W. Crane & Co., Topeka, Kas.

M. E. Mann on the 9 day of Feb'y 1907 ordered survey of part of sec. 29, Tp. 34, R 17 E. Notice mailed to M. E. Mann, Mrs Frank Good, Mrs. Cork Dick, Mrs Jacob Good, Mrs Mattie Day, E. A. Brown, S. Cook and L. C. Cook of Coffeyville Kansas, to meet at the S. E. corner of Section 30, at 8 o'clock and Feb'y. 26, 1907. Met at place and time of notice. Frank Sprich and L. D. Winkles were selected as chairmen and by me duly sworn. Start at the South west corner of section 29, Tp. 34, R 17 E. Chain east on random line Va. 7³⁰E at 1584 feet set stake for West line of Osage Reserve, then east 1056 feet set stake for 8¹/₄ post but find I am 141 feet west of the 4 post. Chain east from the 1st post to the South East corner of sec 29. I find the distance to be 2447 feet. Adjourn for noon. At 1 o'clock I start at established 8¹/₄ post to Section 29. I find that the West Line of the Osage Reserve to be 1056 feet west of said established 8¹/₄ post. I find that the 49 mile post on the south line of the said Section 29, and at the intersection of the West Line of the Osage Reserve to be missing. I then go to the north line of the said section 29 at the intersection of the said West line of the Osage Reserve. I also find the 48 mile post missing. I then follow the said West line of the Osage Reserve south two miles from this point I find that the 50 mile post is missing I then proceed south on said line 1023 feet and find post to South West corner of the Osage Reserve. From this stone I chain north on true line 6303 feet to place of location of the 49 mile post I find this to be 62 feet south of a true line from the ^{South} 4¹/₄ of Section 29. At this point I drive iron rod, 7 feet north of the North west corner of Barn. Adjourn to 8 o'clock Feb'y 27. To meet at above located 49 mile post. Feb'y 27th 1907 at 8 a.m. met as per plan designated. Swear in G. W. Byrd and J. M. Adams as chairmen. Set my instrument on South west corner of Section 29, turn the object line on the flag at the 49 mile post on this true line and at 1338¹/₂ feet I plant line stone 28x7x4 marked + on top and on north and south edge, brick gloss in bottom of hole. I then chain north on true line 1323 set line stone proceed north on same line 1323 feet plant line stone marked + on top. This completed the survey.

Dated at Independence the 26 day of March 1907,

A. M. Parsons,
County Surveyor.

NOTICE—Surveyor's Permanent Record, State of Kansas.

| GEO. W. CRANE & CO., Printers and Binders, Topeka, Kas.

|

Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189—

189—

M

You are hereby notified that, at.....o'clock A. M., on the.....day of....., 189....., I will begin a survey on Section....., Town....., South, Range....., in which you are interested, and shall continue the same from day to day until completed. Commencing at the.....corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.