

This is to certify that J A M Parson, County Surveyor of Montgomery Co. Mo. was on the 9th day of February 1907 ordered to survey and subdivide sec. 9, Tp 34, R 16 E, by W. S. Shirley, Monro Ingram, John Ingram, J B. Hooper, Wm. Marlow, J F Smith, A P. Barton, Wash. Gentry & Calout and Price, of Independence, Mo. and J H. Newmaster, D L. King of Coffeyville Mo. to meet at the Residence of W S Shirley on the 27 day of Feb., 1907 at 8 o'clock a.m.

Met at appointed place at time appointed, Began the work Ed. Auring and J S Ewling were sworn as chainmen and Alfred Short as flagman, Go to the north east corner of the section and find stone. All parties present satisfied that it is Gov. stone and in correct position. Chain west find E. N. 1/4 stone also N 1/4 stone then east, find north west corner to be Gov. stone in place. Chain south from this stone 59° 15' E 2640 feet find west 1/4 stone and find I am on true line, continue south on said true line 2640 feet to south west cor. of section find stone gone set a lime stone 27x12x3 1/2 on true line 2640 feet south of west 1/4 stone for S W cor of section, mark on east edge on south side with brick glass bottle in bottom of hole under rock, chain east on random line at 1320 feet set temporary W. S. 1/4 stake east on same line 1320 feet set temporary S 1/4 stake east 264 feet and find I am 45 feet east of south east corner Gov. stone in place, Chain west at true from S E corner 2617 feet 6 in on true line set lime stone 18x12x4 mark 1/4 north side for S 1/4 stone continue west on true line 1308 feet 9 in set lime stone 26x10x4 for W. S. 1/4, on account of rain work was continued to March 8, 07, to 1 o'clock p.m.

On account of parties not being present and not willing for survey to proceed March 8, 07, word was agreed to be subject to call survey called by notice to above for March 17, 1908, On the date my Deputy A C. Gilliam proceeded with the survey as follows,

Sworn in J L. Dowlan and W S Short as chainmen and proceeded as follows,

Run random line from S E cor of sec. to N E cor of sec. and checked back, at half way or 2664 feet set East 1/4 stone on true line, sand stone 24x8x3 marked 1/4 on side.

Run random line from this East 1/4 stone west to W 1/4 stone find the distance to be 5236.52 feet, at 1309, 13 feet west of East 1/4 stone on true line set sand stone 24x12x6 marked X on top, at 1309, 13 feet west on same line set center of section sand stone 18x12x6 marked C 1/4, at this point I found all marked stone, at a point on true line west 1309, 13 feet west of C 1/4 stone set W 1/4 stone, sand stone 18x12x6 and sand stone marked X on top, also marked the north of the E 1/4 of the N E 1/4 as follows set the S E corner on the East line of section 999 feet south of N E corner of section set a sand stone 18x12x5, marked X on side set S W corner of this 30 acres at a point 1308, 4 feet west of the south east cor of 999 feet south of N E cor of section, sand stone 18x12x3 marked X on top.

This finished survey
Filed the 22 June 1908.

J A M Parson
County Surveyor

June 17, 1908, By request of Toole representative of parties owning land in the N E 1/4 of the SE 1/4 of sec. 9, located their corners, and same to be changed to land beginning at a point 330' south of the N E cor of the SE 1/4 then S 330' W 2648' N 330' E 2648' to place of beginning set stone at each corner.
Charged \$10.00

J A M Parson
County Surveyor

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.)

M. _____, Kansas, _____ 189____.
You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____ Town _____ South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.