

Geo. W. Crane & Co., Topeka, Kas.

Survey ordered by R. L. Madden on the 23rd day Feb 1907, notices to the following. R. L. Madden, M. Madden, ^(Mabel Henderson) D. M. Nees, Thomas Henderson, Patrick Cleman, W. J. Henderson, M. D. Turner, J. P. Davis, Jacob Scholl, Mabel Scholl, John Head, of Independence, Kansas, and John Hook, Eldorado Mo, and Wm Roland, C. P. Allen, R. S. Parkhurst of Independence Kansas. To meet at the residence of R. L. Madden, March 13, 1907 at 8 o'clock a.m., March 13th 1907, survey adjourned to March 19, 1907. ^{at 8 A.M.} March 19, 1907 at 8 o'clock a.m. met for survey, as per adjournment, I went to the North $\frac{1}{4}$ post of section 17, 32-16. I found stone and not being satisfied that the stone was a government stone. I swore A. J. Henderson and P. C. Cleman who testified that the stone was the stone set by the government and that it was in the same place set by the government survey, G. R. Springer and Joe Kirchhoff being selected and being satisfactory to all parties were duly sworn as chairmen, I set 9 feet west of the N $\frac{1}{4}$ post raw South on Va 8° 45' East 2641 feet to stone set for C $\frac{1}{4}$ Continue South 2639 feet find that I am 12 feet south of S $\frac{1}{4}$ which is partly out of the ground. I then go east to S.E. corner of section 16 find stone as set by County Surveyor, also stone set at S.E. corner of section 17, set by County Surveyor on a true line 9° 07' East, south line of section 16. I ran west from the S.E. corner of section 17 on a true line. I intersect the line run from the N $\frac{1}{4}$ post south, at the S $\frac{1}{4}$ post as it stands and from this find the S $\frac{1}{4}$ stone to consist. From this point I continue west on true line 634 to River, 245 feet to west bank of River, then 254 feet set stake for temporary W.S. corner, thence west on same line 320.5 feet to River, 370 feet to west bank of River, then a west on same line 129.5 feet set stake for temporary corner to sections 17, 18, 19 and 20. I then go west to the S $\frac{1}{4}$ stone in sec. 18, find same to be Government Stone. I chain east 2640 feet and find my temporary corner to sections 17, 18, 19 and 20 is 36 feet to far west, a fact which I verify by running in from the north from a located point. I then plant sand stone for corner to Sections 17, 18, 19 and 20, 27x12x5, marked on south side 1111 on east edge ^{dime size} with cross on top, also broke bottle at bottom of pole. I then check back to W.S. stake and move same east 36 feet, check back east, and find that my measurement across the Verdigris River at 634 feet west of S $\frac{1}{4}$ stone of section 17 should be 281 feet, I then start at the W.S. stake run north Va 8° 45' East, 660 feet, then west Va 9° 07' East 660 feet, then north Va 8° 45' East 478.5 feet ^{in date}, thence east Va 9° 07' East 990 feet to River. Adjourned to March 26, 1907, at 8 o'clock a.m., March 26, 1907, at 8 o'clock a.m., continued with the survey, go to the S $\frac{1}{4}$ stone of section 17, repeat stone in proper position, then chain east on true line 528 feet set stone, then go to the C $\frac{1}{4}$ chain east 528 feet Va 9° 07' East, then south 990 feet ^{dime size}, Va 8° 45' East, then south 1630 feet find that I am 9 feet south of center line between sections 17 and 20. I then re-check North and South $\frac{1}{4}$ line find it 12 feet short, at 1817 feet south of the N $\frac{1}{4}$ post on true line I set stone sand stone 14x12x4 marked N $\frac{1}{4}$ on west side, + on top, south on same line 2634 feet and 2634 feet north of the S $\frac{1}{4}$ post. I set lime stone 14x12x8 marked C $\frac{1}{4}$ on south side, + on top. East on true line 528 feet, set sand stone 16x12x6 marked + on top, thence south 989.3 feet set sand stone 16x12x8 marked + on top, west on true line to bank of River Va 9° 07' East, set lime stone 24x20x2 marked + on top, 6 feet west of hickory tree 10 inches diameter return to stone east, then south on true line 327.7 feet set sand stone 16x14x6 marked cross on top, then west on true line from the S $\frac{1}{4}$ stone, 634 feet to bank of river set sand stone 24x12x10 marked on south side 934 feet E w S $\frac{1}{4}$ S. should have been 634' E w S $\frac{1}{4}$ S, + on top. I then set at W.S. stake sand stone 16x12x4 marked W.S. + on top, at 660 feet North set sand stone 14x8x4 marked + on top, A.M.P. on south side, at 660 feet west set sand stone 16x12x3, + on top 3-26-07 on south side, at 478.5 feet ^{north} set sand stone 18x12x6, marked + on top, 990 feet east on Bank of River set sand stone 16x8x4 marked + on top. This finished the survey,

Dated at Independence this 15 day of April, 1907,

A. W. Persons
County Surveyor,

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. CRANE & CO., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

, Kansas, 189.

M

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.