

Geo. W. Crane & Co., Topeka, Kas.

I, W. M. Parsons Surveyor of Montgomery County, Kansas, do hereby certify that in the month of March, 1908, Mrs. E. Cox did order a survey of section 28, Tp. 31, R. 14 East, and the following notices were sent out to meet June 23, 1908 at the N.W. Cor of sec. 28-31-14, at 10 o'clock a.m. On account of rain did not get there until the following day, notified interested parties, and proceeded as follows, John Hansford and L. S. Parsons were selected and sworn in as chairmen, go to south east corner of section and after considerable digging find stone all satisfied it is government stone, set transit over stone run north on  $9^{\circ}20'$  Va E. 2640' set stake for temporary E  $\frac{1}{4}$  corner. Continue north 1320' on same line set stake for temporary N.E.  $\frac{1}{4}$  corner. Continue north same line 1320' cannot find N.E. corner to section, go to north east corner of sec. 28-31-14 run west on true line to north west corner of sec 28. at intersection of line from south established ~~the~~ corners to 28, 27, 21 and 22, Plant a lime stone 16x9x4, marked  $\equiv$  east edge || south side, find that the line between 27 and 28 is 10' long. Close the work for the day, June 25. proceed as follows, correct N.E.  $\frac{1}{4}$  by setting sand stone, 14x9x5, marked N.E.  $\frac{1}{4}$  on west side, 7.5' north of temporary stake on same line, correct E  $\frac{1}{4}$  corner by setting sand stone, 24x12x5 marked  $\frac{1}{4}$  west side, 5' north of temporary stake, chain west from North East corner Va  $9^{\circ}10'$ , East 2635.38' set stake for temporary N  $\frac{1}{4}$  corner. From this point I go north  $29^{\circ}$  to West 158' then west on Va  $8^{\circ}10'$  508' then reverse my angle and run 158' back to line, offset south 15' run west 817.7' set stake 15' north for W N  $\frac{1}{4}$  corner. From this temporary stake off set south 50' run west Va  $8^{\circ}10'$  450' off set south 5', continue west 250' off set 34' run west 520' off set north 89' set temporary stake for N.W. Cor of sec 28, noon, after noon start at S.E. corner of sec 28 chain west on true line 5280' set stake for S.W. corner of sec. 28, find corner and find distance to be correct return to S.W. corner of 28, set sand stone 21x6x6 marked east edge  $\equiv$  south side 1, for corner to section 28, 29, 32 and 33. Chain north Va  $9^{\circ}35'$  2640 set stake for temporary <sup>W  $\frac{1}{4}$  Cor</sup> to 28. Continue north on same line 1320' set stake for temporary N.W.  $\frac{1}{4}$ . continue north same line 1320' set stake for N.W. Cor. to sec. 28. I then go north to W  $\frac{1}{4}$  of sec. 22, which is a gov. stone. I run south to N.W. Cor of sec. 28 and find my true corner to be 16' north of temporary corner set from south and 32' west and 7' north of temporary corner running from N.E. Cor. west. I then correct north line by setting lime stone 24x8x3, marked  $\frac{1}{4}$  south side, 17' west and 3.5' north of temporary stake, I then correct <sup>W N</sup> ~~NW~~  $\frac{1}{4}$  corner by setting sand stone 21x12x4, marked  $\frac{1}{4}$  south side, 25' <sup>west</sup> ~~west~~ and 5.5' north. I then correct the NW corner and set sand stone, 16x10x5, marked  $\equiv$  east edge || south side. I then correct NW  $\frac{1}{4}$  by setting stake 12' north of temporary stake, I then correct W  $\frac{1}{4}$  corner by setting sand stone 19x12x3 8' north of temporary stake, run random line from W  $\frac{1}{4}$  corner to E  $\frac{1}{4}$  corner and set C  $\frac{1}{4}$ , sand 16x8x6 marked C  $\frac{1}{4}$  south side, on a true line mid way between the E and W  $\frac{1}{4}$  corners. I then chain north from W  $\frac{1}{4}$  1323.67' set stake. Then chain east from N.W.  $\frac{1}{4}$  to stake 1326' and at the point of contact of line run from W  $\frac{1}{4}$  stake set sand stone 17x12x4 marked on east side N.W. C  $\frac{1}{4}$ , for north west center  $\frac{1}{16}$ . This finished the work.

Dated at Independence, Kansas June 29, 1908,  
W. M. Parsons  
 County Surveyor

NOTICE—Surveyor's Permanent Record, State of Kansas.  
Geo. W. Crane & Co., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description. Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.

\_\_\_\_\_ Kansas, \_\_\_\_\_ 189\_\_\_\_

M \_\_\_\_\_

You are hereby notified that, at \_\_\_\_\_ o'clock A. M., on the \_\_\_\_\_ day of \_\_\_\_\_, 189\_\_\_\_, I will begin a survey on Section \_\_\_\_\_, Town \_\_\_\_\_, South, Range \_\_\_\_\_, in which you are interested, and shall continue the same from day to day until completed. Commencing at the \_\_\_\_\_ corner of said Section, I shall permanently establish \_\_\_\_\_

\_\_\_\_\_, County Surveyor,  
 \_\_\_\_\_ County, State of Kansas.