

Geo. W. Crane & Co., Topeka, Kas.

I, M. Parsons, County Surveyor of Montgomery County, Kansas, do hereby certify the following to be a true record of the survey of lands of Robt B Connor and others, in sections 10 and 11, Township 34, Range 16 East. Call made by S. V. Matthews April 20, 1908. Which went to meet at north 1/4 post of section 10, Tp 34, R 16, East, July 21, 1908, at 9 a.m. to S. V. Matthews for R B Connor, A. G. North, Hattie J. North, W. G. Gutter, David Walker, Mack Wesley, Leander Denton, J. W. Ingram, A. E. Wells and R C Grisham of Independence, Kansas, J. B. Hooper and Eliza Hooper of Coffeyville, Kansas. On the 21 day of July, 1908, met at place and time appointed, on account of hot weather and not being able to get any one to help, continued the survey to Sept. 9, 1908, met on September and commenced the survey by starting at S 1/4 stone of section 10-34-16, after swearing in C. E. Hanton as chairman, and acting myself as chairman. Chained north to N 1/4 stone. I find the section on this line to be 49 feet long. On a true line 1352.25 feet north of S 1/4 stone of section 10-34-16 I set Lime Stone 24x18x4. Marked S 1/2 on east side + on top I then run east 1320 feet set stake for temporary S.E.C 1/4. I then adjourn to October 7, 1908, at 1 o'clock p.m. October 7, 1908. Continued with the work, sworn in J. Smith as chairman. Start at stake set for temporary S.E.C 1/4 corner run north 2640 feet, Va 9° East set stake for temporary N.E.C 1/4 corner, thence east 1320 feet Va. 9° East set stake for temporary N.E. 1/4. I then run north 1320 feet Va 9° East, find I am 32.6 feet south and 2.5 feet west of Government stone at north east corner of section 10, Tp 34, R 16 E. Start at stake 2.5 feet east of stake for temporary N.E. 1/4 corner, run south on random line, Va 9° East, 200 feet off set west 5.6 feet, run South 460 feet off set east 5.6 feet set stake for temporary 1/4 corner continue south same line 660 feet set stake for temporary E 1/4 corner. Find government stone loose on top of ground. Continue south on same line 660 feet set stake for temporary 1/4 corner. Adjourn. October 8, 1908. at 7 a.m. resume, continue from 1/4 stake 660 feet set stake for temporary S.E. 1/4 corner, continue south same line 1320 feet and find I am 49 feet north and 25 feet west of Government South East Corner of section 10-Tp 34-R 16 from this I find the true Va North and South to be 9° 19' East. I then return to S.E. 1/4 and correct by setting sand stone 24x12x3 marked S.E. 1/4 on east side, 28.6 feet south and 21 feet east of temporary stake at S.E. 1/4. I then run line west to temporary S.E.C 1/4 and find the distance to be 1322.5 feet. I find my temporary stake to be 8.4 feet to far north. I then correct by setting Lime Stone 18x10x3 marked east side S.E.C 1/4. 1.5 feet east and 8.4 feet south of temporary stake. Adjourn for noon. At 1 p.m. I go to the 1/4 stake south of the E 1/4 stake and correct by setting sand stone 14x6x4 marked 1/4 east side, 18.4 feet south and 17.5 feet east of temporary stake. I then go to temporary E 1/4 and correct by setting Government stone, sand stone 24x12x4, marked 1/4 on east side, 14 feet and 8.2 feet south of temporary stake. I then go north to 1/4 stake and correct by setting sand stone 12x6x4 marked 1/4 north side + on top, 10.6 feet east and 2 feet north of temporary stake. I then go to N.E. 1/4 stake and correct by setting sand stone 26x14x4 marked west side N.E. 1/4, 7 feet east and 12.2 feet north of temporary stake (2.5 feet east of first stake). I then go to N.E.C 1/4 and correct by setting Lime Stone 12x10x5 marked + on top, 24 feet north and 15 feet east of temporary stake. I then go to

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.....

M.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

the stone at the 1/4 corner north of the E 1/4 corner and run east on Va 9° 19' E, 1193 feet set stake continue east same line 130.5 feet set stake for temporary 1/4 corner south of the N.W.C 1/4 of section 11, Tp. 34 R. 16. E. I then go back to stake set at 1193 feet and run north 670 feet Va 9° 19' set stake east of this point on Va 9° 19' E 130.5 feet for temporary N.W.C 1/4. Continue north point 130.5 west 200 feet then stake adjourn for night. Continue with the work 7 a.m. Oct. 9, 1908, run east 200 feet off set south 25 feet then east 500 feet off set north 400 feet then run east east 754 feet same Va. then south to bank of river, 100 feet, off set east 6 feet set pole marked in feet and tenths so that same might be seen from bank of river south. I then go to point 150 feet north run north Va 9° 19' E 200 feet off set east 20 feet then north 557.6 feet and find I am 46.3 feet north and 10 feet west of north 1/4 stone which I find as recorded. I find from record this 1/4 line to be full 5280 feet. I now return to the temporary N.W.C 1/4 and correct by setting sand stone 16x7x7 marked west side 1/4 and side N.W.C, 23 feet south and 15 feet east of temporary stake. I then return south to 1/4 stake and correct by setting sand stone 12x6x5, 18 feet south and 12.4 feet east of temporary stake. I then cross the river and take the line from stake set on north bank of river south of N 1/4 stone of 11-34-16 and find the distance across the river to be 228 feet by my Stadia wires and find I am 1089.3 feet south of the N 1/4 stone. Continue south on same line 230.5 feet and set stone sand stone 30x5x5 marked 1/4 east side N.W.C 1/4. 14 feet east. Adjourn for noon. At 1 p.m. go to S.W. 1/4 of Sec. 11, -34-16 run east on 8° 50' E 1327.7 feet set sand stone 14x14x6 marked S.W.C 1/4 run North 665 feet set sand stone 16x12x3 marked 1/4 on east side Va 9° E. This completed the work.

Dated this 19 day of October, 1908,

M. Parsons,
County Surveyor,