

Survey No. , Section 30 , Town 34. South, Range 16

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, Ed. H. Hibbard County Surveyor of Montgomery County, Kansas was ordered by P. H. Fox agent for H. J. Moss and Lamont to notify all parties in and adjoining Section 30 T. 34. R. 16 E. and establish all corners necessary in the subdivision of said Section thirty. The following named parties were notified that a survey of the above named Section would be made on March 16th 1893. J. Bonser E. A. Osborn Martha E. Morrison Peter Edsell, Edwin Fowler, P. H. Heckart, W. H. R. Montgomery, Annie J. Montgomery C. M. Ball et al. P. H. Fox agent, John Snyder et al. On March 16th 1893 I began the survey. Henry Fox and Lloyd H. Hockerd were detected as chain men and were duly sworn, & went to the South West corner of Section 30, T. 34, R. 16 a limestone standing from this point I ran East at 1308 ft. found a stone standing as S.E. corner to fractional 40, at 2630 found 1/4 post standing on South line of the Section. Found the 1/4 post on the South line of Sec. 30, T. 34, R. 16 as above & ran East at 2636 found Government corner at a point 1318 ft. West from the S.E. corner of Section 30, I set a lime stone 18x8x3" marked X for S.W. corner of S.E. 1/4 S.E. 1/4 Sec. 30, T. 34, R. 16. At a point 660 ft. West on the Section line from the 1/4 post on the South line of Sec. 30, I set a flag stone 17x8x2 1/2" for S.W. corner of E 1/2 of E 1/2 S.W. 1/4 Sec. 30. From the 1/4 post on the South line of Section 30, I ran North at 2640 down stake as temporary center at 2645 found part of an old stone as 1/4 post - Measured East from said 1/4 post on North line of Sec. 30 and located at 2640 down temporary corner stake, & then went to the South East corner of Sec. 30 and ran North at 2645 ft. found a sand stone bearing government marks I set this stone as it was out of the ground took back sight to South East corner of the Section 30, and ran line North intersecting the line running East from the 1/4 post on North line of Sec. 30, at a point 2650 ft. North of 1/4 post on East line of Sec. 30. Here I set a sand stone 16x14x4" marked IIII. Measured the distance from the North East corner of Sec. 30 to the 1/4 post on North line at 2630' point of location here I set a sand stone 14x10x4 1/2" marked 1/4. From the 1/4 post on the North line of Section 30 I ran West at 2620 down stake as temporary corner & found this corner from our found stumps of witnesses trees from which I located the Section corner, I put a check of this point & ran to the 1/4 post on the West line of Section 30 ran North at 2648 ft. point located from witness trees here I set a sand stone 30x14x6" marked IIII. for N.W. corner Section 30. I then went to the 1/4 post on the East side of Section 30 and ran West on the 1/4 line at 1320 down stake temporary corner to E 1/2 S.E. 1/4 at 2633 ft. intersecting 1/4 line running North & South & set a flag on this 1/4 post on E. & W. side of Sec. 30 connected this line by straight line at the intersection & set a sand stone 12x12x3 1/2" marked XX for center of Section 30. I connected the temporary N.W. cor. of E 1/2 S.E. 1/4, 3 1/2" to East here I set a sand stone 16x14x5" marked X. At a point on the 1/4 line 660 ft. West of the center of Section 30, I set a sand stone 16x14x5" marked X for N.W. corner of E 1/2 of E 1/2 of S.W. 1/4 Sec. 30.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.

Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 1893.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 1893, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

of Section 30, I set a sand stone 18x13x5" marked X for N.W. corner of E 1/2 of E 1/2 of S.W. 1/4 Sec. 30. This completed the survey. Variation 9° E.

Dated at Independence April 14th 1893
Ed. H. Hibbard -
Co. Surveyor.