

Geo. W. Crane & Co., Topeka, Kas.

I Spencer R Logan was ordered to survey and in sec 27-32-15 by Edna Hemphill & O. Hobbs and on August 9 1915 notified
 J. Fiske Mrs M M Swartz, J. Van Aundel Albert Johnson Martha Johnson J W Miller and Barr Wm Cinger.
 John Gang Engine Beland J D Ashby J C Weyer J L Hobbs Cal D. Malley C. B. Swearingen C. H. Will Magge Burns
 J P Wood C. E. Orwig Hattie Canale J M Clark H E Miller Cadie Randle Annie J Adams Wm V. Series J M Force H Mc Cormis
 That I would be at the O. L. Hobbs place at 10 AM. Aug 16 1915. at which time I went to that place and adjourned
 survey till Aug 20 1915 at 9 AM. in Aug 20 1915 I swore in James Huggins as chairman and chainman and chainman John D. Ashby
 to a limestone which I find standing at the south west section corner. Hence I set 20' west ran north 1° 40' west
 2640' where I found corner in place 50' east. connected to true line and continued north leaving temporary corners at 3960 + 5220'
 Noon from NW. sec corner ran 1320' to stone and thence continuing east at 2640' + 3960' set temporary corner and at 5220'
 introduced sec corner at NE cor and adjourned for day. Aug 21 started 10' W. temporary S & E cor ran south 5' W. to N & E
 corner leaving temporary at 1320 - 2640 + 3960 and introduced N & E at 5220' thence ran from NE sec cor south leaving Temp
 corners at 1320 + 2640 (Noon.) Commencing at SW 1/4 temporary corner ran north to NW 1/4 stone on North line leaving
 temporary corners at 1320 - 2640 - 3960'. Thence from W 1/4 stone ran east leaving temporary corners at 1320 + 5220'
 and introducing hole corners at 2640' + 3960'. Thence from temporary E & ran south 2640' leaving temporary corners
 at 990 + 1320' thence along South line of section leaving temporary corners at 1320 - 1650 1920 2720 2640 2970 3300
 3630 - 3960' and adjourned. Monday Aug 23 and Aug 24 at temp S & E cor set limestone 26 X 10 X 7 marked + 1/4 in
 S & E cor between sec 27 + 34. At SW 1/4 set limestone 30 X 10 X 8 M 1/2 + 1/2 in W 1/4 or between sec 27 + 34 thence at point
 2640' on SW exterior line and line + 1320' S of N & E stone set limestone 33 X 9 X 2 M 1/4 + 1/2 for W interior 1/6 stone thence at NW temporary
 cor set limestone 5' X 11' X 28" M = 1/2 + 1/2 for NE sec cor. Thence midway between NW sec cor + W 1/4 sec cor set limestone 24 X 12 X 11 M 1/2
 for NW set 1/6 stone on west line. Thence set sandstone 7' X 9' X 26" M 1/4 + 1/2 at temp 1/4 for N & E cor between sec 27 + 22, midway
 between this N & E and N. sec cor and 1320' from each set limestone 6' X 12 X 22 M + 1/2 for NE exterior 1/6 stone on N. line. Thence at 1320'
 corner of N sec cor. set limestone 6' X 2' X 8" M 1/4 + 1/2 Thence set line stone 1320' on N & E set stone on 3960' S of W 1/4
 stone. Thence 5' X 12 X 22" M + 1/2 for NW interior 1/6 stone and adjourned. Aug 30 set limestone 7' X 10 X 24 M + 1/2 for SE corner
 1/6 stone between sec 27 + 33 thence set limestone 7' X 12 X 26 M + 1/2 for SE sec cor. and quit in account of rain Sept 1.
 set pipe 2" X 30" at temporary E & cor 2640' from each and on true line between NE + SE sec corner.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
 Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

_____, Kansas, 189_____.

I, _____, do hereby certify that, at _____ o'clock A. M., on the _____ day of _____, 189_____, I will begin a
 survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same
 from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.