

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I J. C. Ozis County Surveyor of Montgomery County did survey Sec. 20 Town. 34 S. Range 17 E. 6 P. M. on the 23-24-25 of Aug. 1912 and 4th Sep. 1912. Sent notices to the following, Al. Bear, L. W. Fair, Jones Cunningham, H. H. Heritage, John W. Intjan, Milton Davis, Mrs. Mattie Day, Mat. Carl, and Childers. Milton Davis called the survey in Sep. of 1911 and as there had been so much trouble over previous surveys I wrote to the Dept. of the Interior for instructions which were sent together with a plat, which I have recorded in my book Records of Surveys #2, Page 37. I followed those instructions to the letter. Every one being notified met at the N. W. Cor of Sec. 20 on the 23 day of Aug. 1912. Al. Bear as Chain carrier. E. L. Richardson as transit man we proceeded to survey as follows. From an established Government corner stone on the North West Cor. of Sec. 20. I ran to the 47th mile stone on the North line of Sec. 20. a distance of 1515.8' I left a flag pole there. I then went to the North East Cor of Sec. 20 and found a government corner stone, I then ran a random line West 3953.45' or 240' south of the 47th mile stone where my flag pole was stationed. I then chained 1184' East from the 47th mile stone and set a stone 18x18x24" marked 1/4 for the 1/4 stone of Sec. 20. I then journaled until the 24th day of Aug. 1912 and Howard Foster was sworn in as chain carrier. I went to the South West corner of Sec. 20 took a point from the established government stone ran 1560.9' and established the 48th mile stone which was lost. I then went to the South East corner of Sec. 20 took a point from the established government stone ran and chained back to the 48th m. S. and found the distance to be 3780.50'. I then divided them as follows from the 48th m. S. to the 1/4 Post a distance of 1104.04'. from the South East Corner to the 1/4 Post 2676.46'. I then set a stone at this point of the established 1/4 Post of Sec. 20-34-17-. Mr. Childers and Mat. Carl then wanted a stone between them and they had land in Sec. 29 and there being no others but who were all ready interested we proceeded to set a stone for them by dividing the distance between the South East Corner and the said established 1/4 cor. a distance of 1338.23' and set a stone marked 1/4 for their corner. I then journaled until Aug. 27th 1912. We met on the 27th of Aug. 1912 and swore Frank Day in as Chain carrier. I took a point from the South 1/4 stone and ran a line to the North 1/4 stone then divided the distance (which was 5357') and drove an iron Pin for the Center of Sec. 20. This completed the survey called for J. C. Ozis

County Surveyor.
Recorded this 3rd day of Sep. 1912.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by E. A. Bailey, Topeka, Kansas.]

Kansas, 189.

M. You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189., I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.