

Survey No. , Section 19, Town 32 South, Range 14

I was ordered on April 22nd 1893, by M. J. Simmons to Survey and Subdivide Section 19, Township 32, R. 14 East. On April 28th 1893 the following parties were notified that a Survey of Section 19 would be made on May 10th 1893. *M. J. Simmons*
J. F. Mott, Noah Vaughn, Martin F. Koff, (Noah Vaughn aff.) Doyle, Geo. Chandler,
 F. T. Nail, (Jno. Stiff, aff.) Christian Widdor, B. S. Adams, Collins, Currie, H. P. Furlie,
 J. Davidson, M. J. Simmons, Clifford Hudley, A. R. Stoen, aff. for Equitable Mortgage Co.,
 and Chas. Brailey. On May 10th 1893, I began the Survey, Christian Widdor
 and Mathew Kains were selected as Chain Carriers, and were duly sworn,
 I went to the North West Corner of Section 19, T. 32, R. 14 E. Ran N. 0° 15' E. at 2513 ft. a stone 1/4
 post North line of Section 19. From this last named 1/4 post ran N. 0° 15' E. at 2640 ft. down
 stake temporary N.E. Corner Sec. 19. & then went with M.E. corner of Section 20 T. 32, R. 14 E.,
 and ran West at 2647 ft. 1/4 post at 5294 ft. down stake temporary N.E. corner Sec. 19,
 & then went to the 1/4 post on the East line of Sec. 19 Ran North at 2625 ft. stake set
 as temporary corner from the run from N.E. corner of Sec. 20. Here I set a sand stone
 27x11x5. Marked IIII for N.E. corner of Sec. 19 T. 32, R. 14 E. May 11th 1893 I measured from
 the 1/4 post on the East line of Sec. 19 South at 2648 ft. down stake as temporary S.E. corner to
 Sec. 19 & then went with the 1/4 post on the South line of Sec. 21, T. 32, R. 14 E. which I found
 standing, & ran West at 2647 ft. Cor. to Sec. 20 at 21, from this corner I ran West on
 the South line of Sec. 20, at 5293 ft. stake driven from the run from 1/4 post East side Sec.
 19. & then went to the South West Corner of Sec. 19, on the Range line between Sections
 19 & 24 (24 of R. 13) & ran N. 0° 15' E. at 2482 ft. dist. from by Geo. Field Notes down stake as temporary 1/4
 post South line of Sec. 19. From this temporary 1/4 post I ran on sand draining at 2656 ft. stake
 driven as temporary S.E. corner Sec. 19. & ran S. 16° South line Sec. 19, at a point 1324 ft. West of
 South East corner (When I had set a sand stone 18x12x4" Marked IIII for S.E. corner Sec. 19 T. 32 R.
 14 E.) & set a flag. For 1/4 post South line Sec. 19, & set a sand stone 33x10x10" Marked 1/4
 S ft. East of the temporary stake driven as temporary 1/4 post. From S.W. corner Sec. 19, &
 ran North on Range line at 2640 ft. 1/4 post a 5280
 N.W. corner of Sec. 19. & connected 1/4 posts of
 Sec. 19 by straight lines at the intersection set a
 sand stone 24x12x4 1/2 Marked X X for center of
 Sec. 19. From the center of Sec. 19 I ran East
 on 1/4 line at 1820 down stake as temporary cor. to
 N.W. 1/4 S.E. 1/4 at 2654 ft. 1/4 post East line Sec. 19, connected
 temporary N.E. corner of N.W. 1/4 S.E. 1/4 7 ft. East here
 & set a sand stone 24x14x3 Marked X. Midway between
 center Sec. 19 & 1/4 post South line set a sand stone 14x18x4"
 Marked X, for the center of the South East 1/4 of Sec. 19 T. 32 R. 14 E. set a lime stone 30x14x5"
 Marked X, midway between the center of Sec. 19 & the 1/4 post on the North line of Sec. 19, &
 set a lime stone 17x10x2 1/2 for N.W. corner S.W. 1/4 N.E. 1/4 Sec. 19, T. 32 R. 14 E.
 This completed the Survey, Var, 9° E.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
 Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.

You are hereby notified that, at o'clock A. M., on the day of 189., I will begin a
 survey on Section , Town , South, Range , in which you are interested, and shall continue the same
 from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

Marked X, for the center of the South East 1/4 of Sec. 19 T. 32 R. 14 E. set a lime stone 30x14x5"
 Marked X, midway between the center of Sec. 19 & the 1/4 post on the North line of Sec. 19, &
 set a lime stone 17x10x2 1/2 for N.W. corner S.W. 1/4 N.E. 1/4 Sec. 19, T. 32 R. 14 E.
 This completed the Survey, Var, 9° E.

Dated at Independence Montgomery Co.,
 Kansas June 8th 1893.

L. H. Hibbard
 Co. Surveyor.