

Survey No. , Section 14, Town 32, South, Range 14.

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I S. L. Hibbard County Surveyor of Montgomery Co. Kansas was ordered by Tr. E. for
to survey and subdivide sections 14, Township 32, Range 14, East. (Order Made on Dec. 18/1893.)
On Dec. 19/1893. The following named parties were notified that a survey would be made of the
above described sections, beginning on Dec. 27/1893, Maria Henry, H. S. Cook, Thomas Reed, Eliza A. Wood,
Philip Petrel, Robert Simmons, J. G. Gregory, L. E. + W. H. Fox, W. H. Bloom, A. B. + A. M. Hadley, Cyrena Macy,
A. C. Stick, apt. J. B. Foster, Geo. Reed, Catherine Moody, + F. A. Powell,
On Dec. 27/1893 I began the survey Robert Gregory + H. W. Webb were selected as chainmen and were
duly sworn, to faithfully and impartially perform their duties as chainmen. I went to the 1/4
post on the South line of Sec. 13, 7. + 8. as above which I found standing ran west on the sec line between
Secs 13 + 25 at 2645 ft. down stake as temporary S.E. corner to sec. 14 from this stake I ran west on sec line
between Secs 14 + 24 at 2650 ft. down stake as temporary 1/4 post South line sec. 14. From this temporary corner I ran
west 1320 down stake temporary corner S.W. corner S.E. 1/4 S.W. 1/4 of above described section at 2080 ft. Elk River at 2662 ft.
Came out 15 ft. South of a stone said to have been a corner but had been plowed out several times. In order
to make proper connection I went to the 1/4 post on the South line of Sec. 15 which I found standing. ran East
2644 ft. I connected corner 12 ft. North + 7 ft. East then I set a lime stone 20x5x3 marked 1111.
as S.W. corner to sec. 14. At the South East corner Sec. 14 I set a lime stone (1 ft. west of temporary corner)
24x6x5 marked 1111. For 1/4 post on South line of Sec. 14 I set a lime stone 20x12x6 marked 1/4
at a point 1326 ft. West of 1/4 post on South line of Sec. 14 I set a sand stone 18x6x5 marked 1/8 for S.W.
corner of South East 1/4 Sec. 14 7.32 R. 14 E. at a point 80 rods North of this last described corner I set
a sand stone 24x8x7 marked XX. For N.W. corner S.E. 1/4 S.W. 1/4 Sec. 14 7.32 R. 14 E. from the S.E. corner of Sec. 14
I ran North on sec. line between Secs 13 + 14 at 2640 ft. down stake as temporary corner I found distance true
a Walnut and a Lycium from which I relocated the corner. Then I set a sand stone 24x11x4
marked 1/4 for 1/4 post on East line Sec. 14. On acct. of 1/4 line running in Elk River I offset South 780 ft.
ran West 1210 ft. Elk river at 1400 ft. down stake on West side of Elk River ran North 780 ft. back to 1/4 line
ran East 80 ft. down stake temporary corner S.E. corner S.W. 1/4 N.E. 1/4 Sec. 14. Offset South from this temporary
corner on acct. of slope + brush 180 ft. ran West 800 ft.
at dock North 180 ft. to 1/4 line thence West 520 ft. down stake
as temporary corner Sec. 14 I adjusted my compass to a flag
set on the 1/4 post on the West side of Sec. 14 and found
the same bearing which made the East and West
1/4 line correct. I then went to the N.E. corner of Sec. 14
found the corner down but near the original point located
by the former from this stone I ran west on Rouben
line at 1320 point for corner to N.E. 1/4 N.E. 1/4. At 2632 ft. temporary
1/4 post from temporary 1/4 post North line Sec. 14 ran west 2658 ft.
former corner connected 1/4 post 2 ft. West North line Sec.

NOTICE—Surveyor's Permanent Record, State of Kansas.
[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]
Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.
Kans., 189.....
M.....
You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a
survey on Section Town South, Range in which you are interested, and shall continue the same
from day to day until completed. Commencing at the corner of said Section, I shall permanently establish
..... County Surveyor,
County, State of Kansas.

14. Ran South from temporary corner at 1320 down stake at 2640 corner line survey E + W. through center sec.
14. At 1/4 post of temporary corner as set from E + W. run. from this temp. corner I ran South on 1/4 line at
735 ft. Elk River at 1320 down stake as temporary S.E. corner N.E. 1/4 S.W. 1/4 Sec. 14. At new firing dark we adjourned the survey
until Jan. 3/1894. On Jan. 3/1894 I continued the survey John Brown + H. B. Roberts were sworn as chainmen
I began when we adjourned at N.E. corner S.E. 1/4 S.W. 1/4 Sec. 14 ran South came out 6 ft. East of 1/4 post
connected corner so rods North of 1/4 post and set a sand stone 25x6x2 1/2 marked X for N.E. corner S.E. 1/4 S.W. 1/4
Sec. 14 I then went to the N.E. corner of Sec. 14 and reset the corner lime stone 28x15x3 1/2 marked 1111
at a point 1327 ft. West of the North East corner of Sec. 14. I set a lime stone 22x10x5 marked X for
N.W. corner N.E. 1/4 N.E. 1/4 Sec. 14. Quarter post on North line Sec. 14 set a lime stone 16x12x5 marked 1/4
1320 ft. South of 1/4 post on 1/4 line I set a lime stone 14x9x2 1/2 marked X. for N.E. corner of S.E. 1/4 N.W. 1/4 Sec.
14. At the center of Section 14 at the intersection of the 1/4 lines I set a lime stone 22x7x3 marked
XX. for the center of sec. 14. P. S. William Macy was sworn as chainman + worked 1/2 day

Var. 8° 55"

Dated at Independence Montgomery Co. Kansas Jan. 27/1894
S. L. Hibbard County Surveyor.